

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

GENERAL NOTES

1. Reinforcement bars shall conform to the requirements of ASTM A 706 Gr 60. See Special Provisions.
2. Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
3. Concrete Sealer shall be applied to top inside face of parapets and abutment wingwalls, approach slabs, abutment seats and abutment backwalls, and seats for Piers 1 and 8. All surfaces to be sealed shall be cleaned thoroughly prior to sealer application. Cost Included with Concrete Sealer.
4. The existing structural steel coating contains lead. The Contractor shall take appropriate precautions to deal with the presence of lead on this project.
5. Stage construction shall be utilized to maintain traffic during construction.
6. Protective Coat shall be applied to the new Latex Concrete Overlay.

INDEX OF SHEETS

1. General Plan and Elevation (1 of 3)
2. General Plan and Elevation (2 of 3)
3. General Plan and Elevation (3 of 3)
4. General Notes, Bill of Material and Index of Sheets
5. Stage Construction Details
6. Bridge Deck and Approach Slab Repairs (1 of 3)
7. Bridge Deck and Approach Slab Repairs (2 of 3)
8. Bridge Deck and Approach Slab Repairs (3 of 3)

TOTAL BILL OF MATERIAL

ITEM	UNIT	SUPER	SUB	TOTAL
Protective Shield	Sq. Yd.	3,627		3,627
Bridge Deck Grooving	Sq. Yd.	4,861		4,861
Protective Coat	Sq. Yd.	5,188		5,188
Concrete Sealer	Sq. Ft.	10,756	1,109	11,865
Silicone Joint Sealer	Foot	84.0		84.0
Bridge Deck Latex Concrete Overlay, 2 1/4"	Sq. Yd.	5,117		5,117
Approach Slab Repair (Partial Depth)	Sq. Yd.	5.0		5.0
Bridge Deck Hydro-Scarification, 2 1/4"	Sq. Yd.	5,117		5,117
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	5.0		5.0
Deck Slab Repair (Full Depth, Type II)	Sq. Yd.	298.8		298.8
Cleaning and Painting Exposed Rebar (Special)	Sq. Ft.	200		200
Clean and Reseal Relief Joint	Foot	48.0		48.0
Clean Trough	Each	3		3

DESIGNED -	TJJ
CHECKED -	AAV
DRAWN -	RMG
CHECKED -	AAV

**GENERAL NOTES, BILL OF MATERIAL
AND INDEX OF SHEETS
STRUCTURE NO. 022-0094**

benesch

alfred benesch & company
Engineers • Surveyors • Planners
205 North Michigan Avenue, Suite 2400
Chicago, Illinois 60601
312-565-0450 Job No. 10050

SHEET NO. 4 8 SHEETS	F.A.I. RTE. 290	SECTION 22(1, 1-1, 2&3)RS-7	COUNTY DUPAGE	TOTAL SHEETS 546	SHEET NO. 361
	355				
FED. ROAD DIST. NO.			ILLINOIS FED. AID PROJECT		
CONTRACT NO. 60G51					