

GENERAL NOTES:

1. BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION REQUIRED)
2. THE CONTRACTOR WILL NOT BE ABLE TO SET UP A STORAGE AREA OR FIELD OFFICE ON STATE PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT.
3. THE RESIDENT ENGINEER SHALL CONTACT MR. WALLY CZARNY, AREA TRAFFIC FIELD ENGINEER AT (773) 685-8386 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.
4. THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE INSTALLATION OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.
5. DIMENSIONS: IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO ORDERING MATERIALS AND BEGINNING CONSTRUCTION.
6. ALL SAW CUTTING SHALL BE INCLUDED TO REMOVE ITEMS AND SHALL BE PERFORMED PRIOR TO BEGINNING REMOVAL. ANY ITEMS OF WORK REMOVED PRIOR TO SAW CUTTING WILL NOT BE MEASURED FOR PAYMENT.
7. THE THICKNESS OF HOT MIX ASPHALT MIXTURES SHOWN IN THE PLANS ARE NOMINAL. DEVIATIONS MAY OCCUR DUE TO IRREGULARITIES IN THE SURFACES OR BASIS ON WHICH THEY ARE TO BE PLACED. PLAN THICKNESS SHOULD BE CONSIDERED THE MINIMUM THICKNESS PERMITTED.
8. DEPRESSED CURB: RAMPS OR DEPRESSED CURBS ACCESSIBLE TO THE HANDICAPPED SHALL BE PROVIDED AT ALL CROSSWALKS. NON-ADA DEPRESSED CURB SHALL BE PROVIDED AT ALL ALLEYS OR DRIVEWAYS.
9. PAVEMENT GRADES: THE ELEVATIONS INDICATED ON THE PLANS ARE FINISHED GRADES OF PROPOSED PAVEMENT OR SURFACE COURSE, UNLESS OTHERWISE INDICATED.
10. ONLY THOSE TREES DESIGNATED BY THE ENGINEER SHALL BE REMOVED. THE CONTRACTOR SHALL PROTECT ALL REMAINING TREES FROM DAMAGE DUE TO HIS OPERATIONS.
11. ALL BRUSH CLEARING AND RIGHT OF WAY RESTORATION SHALL BE COMPLETED BY THE CONTRACTOR AND CONSIDERED INCIDENTAL TO THE PROJECT.
12. GRASS AREAS DISTURBED BY SIDEWALK CONSTRUCTION SHALL BE RESTORED WITH 6" OF TOPSOIL AND SODDED.
13. ANY DAMAGE TO DRIVEWAYS AND ENTRANCES SHALL BE RESTORED BY THE CONTRACTOR IN ACCORDANCE WITH THE CITY OF DES PLAINES DRIVEWAY APPROACH STANDARDS INCLUDED ON SHEET 10.

HIGHWAY STANDARDS

STANDARD NUMBER	DESCRIPTION
000001-05	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
280001-05	TEMPORARY EROSION CONTROL SYSTEMS
424001-05	CURB RAMPS FOR SIDEWALKS
542301-02	PRECAST REINFORCED CONCRETE FLARED END SECTION
542501-02	INLET - TYPE A
604001-03	FRAMES AND LIDS TYPE 1
606001-04	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
701011-02	OFF-RD MOVING OPERATIONS, 2L, 2W, DAY ONLY
701501-05	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
701801-04	LANE CLOSURE MULTILANE 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE
701901-01	TRAFFIC CONTROL DEVICES
720001-01	SIGN PANEL MOUNTING DETAILS
720006-02	SIGN PANEL ERECTION DETAILS
729001-01	APPLICATIONS OF TYPES A & B METAL POSTS (FOR SIGNS & MARKERS)
780001-02	TYPICAL PAVEMENT MARKINGS

SUMMARY OF QUANTITIES					SFTY-1B
ITEM #	SPECIALTY ITEM	PAY CODE	DESCRIPTION	UNIT	ALGONQUIN ROAD QUANTITY
1		20100110	TREE REMOVAL (6 TO 15 UNITS DIAMETER)	UNIT	42
2		20200100	EARTH EXCAVATION	CU YD	440
3		21101625	TOPSOIL FURNISH AND PLACE 6"	SQ YD	2435
4		25200100	SODDING	SQ YD	2435
5		35101600	AGGREGATE BASE COURSE, TYPE B 4"	SQ YD	1760
6		42400200	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	SQ FT	15840
7		42400800	DETECTABLE WARNINGS	SQ FT	60
8		44000600	SIDEWALK REMOVAL	SQ FT	106
9		54213657	PRECAST REINFORCED CONCRETE FLARED END SECTIONS 12"	EACH	1
10		550A0050	STORM SEWERS, CLASS A, TYPE 1 12"	FOOT	15
11		60234200	INLETS, TYPE A, TYPE 1 FRAME, OPEN LID	EACH	1
12		60300305	FRAMES AND LIDS TO BE ADJUSTED	EACH	1
13		60603800	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12	FOOT	135
14		67100100	MOBILIZATION	L SUM	1
15		70101700	TRAFFIC CONTROL AND PROTECTION	L SUM	1
16		70102620	TRAFFIC CONTROL AND PROTECTION, STANDARD 701501	L SUM	1
17		70102640	TRAFFIC CONTROL AND PROTECTION, STANDARD 701801	L SUM	1
18		72400500	RELOCATE SIGN PANEL ASSEMBLY - TYPE A	EACH	3
19		78000400	THERMOPLASTIC PAVEMENT MARKING - LINE 6"	FOOT	369
20		78000600	THERMOPLASTIC PAVEMENT MARKING - LINE 12"	FOOT	204
21		20017200	DOWEL BARS 1 1/4"	EACH	12
22		20062400	SAWING BITUMINOUS CONCRETE PAVEMENT	FOOT	135
23		X0656100	DRIVEWAY PAVEMENT REMOVAL AND REPLACEMENT	SQ YD	80