



PROPOSED TYPICAL SECTION
 STA 2+66.4 TO STA 139+50.5, JACKSON STREET

CONTRACTOR SHALL MILL BEFORE PATCHING

DESCRIPTION	MIX TYPE	PERCENT AIR VOID @ Ndes
HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70	IL 9.5MM	4% @ 70 Gyr.
LEVELING BINDER (MACHINE METHOD), N70	IL 9.5MM	4% @ 70 Gyr.
CLASS D PATCHES (HMA BINDER IL-19MM)	IL 19MM	4% @ 70 Gyr.

THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACE MIXTURES IS 112 LBS/SQYD/IN

FOR "PERCENT RAP" SEE DISTRICT ONE SPECIAL PROVISIONS

THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 70-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE "PG 64-22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS.

PROPOSED LEGEND

- ① HOT-MIX ASPHALT SURFACE COURSE, MIX D, N70, 1-1/2"
- ② LEVELING BINDER (MACHINE METHOD), N70, 1"
- ③ BITUMINOUS MATERIALS (PRIME COAT)
- ④ INDICATES HMA SURFACE REMOVAL (MILLING) 2-1/2"