



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

January 16, 2008

SUBJECT: FAI Route 80 (I-80)
Project ACIM-BRI-080-3 (127) 095
Section (50-5)HBK-2
LaSalle County
Contract No. 66600
Item No. 132, January 18, 2008 Letting
Addendum A

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised pages 2 & 11 of the Schedule of Prices.
2. Revised sheets 3 & 5 of the Plans.
3. Revised pages 5 & 12 of the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

Eric E. Harm
Interim Bureau Chief
Bureau of Design and Environment

A handwritten signature in black ink, appearing to read 'Ted B. Walschleger P.E.'.

By: Ted B. Walschleger, P. E.
Engineer of Project Management

cc: George F. Ryan, Region 2, District 3; Roger Driskell; Estimates

TBW:RS:jc

ILLINOIS DEPARTMENT OF TRANSPORTATION
 SCHEDULE OF PRICES
 CONTRACT
 NUMBER -

66600

State Job # - C-93-106-05
 PPS NBR - 3-40750-0000
 County Name - LASALLE- -
 Code - 99 - -
 District - 3 - -
 Section Number - (50-5)HBK-2

Project Number
 ACIM-BRI-0803/127/095

Route
 FAI 80

Item Number	Pay Item Description	Unit of Measure	Quantity	x	Unit Price	=	Total Price
20100210	TREE REMOV OVER 15	UNIT	97.000				
20101000	TEMPORARY FENCE	FOOT	960.000				
20200100	EARTH EXCAVATION	CU YD	54,312.000				
20201200	REM & DISP UNS MATL	CU YD	2,715.000				
20400800	FURNISHED EXCAV	CU YD	1,617.000				
20700400	POROUS GRAN EMB SPEC	CU YD	375.000				
20800150	TRENCH BACKFILL	CU YD	282.000				
* 21001000	GEOTECH FAB F/GR STAB	SQ YD	52,543.000				
21101505	TOPSOIL EXC & PLAC	CU YD	10,371.000				
25000210	SEEDING CL 2A	ACRE	14.750				
25000312	SEEDING CL 4A	ACRE	6.500				
25000322	SEEDING CL 5A	ACRE	6.500				
25000400	NITROGEN FERT NUTR	POUND	2,498.000				
25000500	PHOSPHORUS FERT NUTR	POUND	2,498.000				
25000600	POTASSIUM FERT NUTR	POUND	2,498.000				
			* REVISED : JANUARY 16, 2008				

ILLINOIS DEPARTMENT OF TRANSPORTATION
 SCHEDULE OF PRICES
 CONTRACT
 NUMBER - 66600

State Job # - C-93-106-05
 PPS NBR - 3-40750-0000
 County Name - LASALLE- -
 Code - 99 - -
 District - 3 - -
 Section Number - (50-5)HBK-2

Project Number
 ACIM-BRI-0803/127/095

Route
 FAI 80

Item Number	Pay Item Description	Unit of Measure	Quantity	x	Unit Price	=	Total Price
70106500	TEMP BR TRAF SIGNALS	EACH	1.000				
70106800	CHANGEABLE MESSAGE SN	CAL MO	18.000				
70300100	SHORT-TERM PAVT MKING	FOOT	6,523.000				
70300220	TEMP PVT MK LINE 4	FOOT	115,361.000				
70300240	TEMP PVT MK LINE 6	FOOT	1,811.000				
70300250	TEMP PVT MK LINE 8	FOOT	2,467.000				
70300260	TEMP PVT MK LINE 12	FOOT	369.000				
70300280	TEMP PVT MK LINE 24	FOOT	125.000				
70301000	WORK ZONE PAVT MK REM	SQ FT	44,884.000				
* 70400100	TEMP CONC BARRIER	FOOT	13,750.000				
* 70400200	REL TEMP CONC BARRIER	FOOT	12,180.000				
72000100	SIGN PANEL T1	SQ FT	99.000				
72400100	REMOV SIN PAN ASSY TA	EACH	1.000				
72400500	RELOC SIN PAN ASSY TA	EACH	1.000				
72400600	RELOC SIN PAN ASSY TB	EACH	5.000				
* REVISED : JANUARY 16, 2008							

Note 1: Geotextile fabric having a minimum weight of 6 ounces and meeting the requirements of Article 1080.02 of the Standard Specification may be necessary dependent upon subgrade soil conditions. The Engineer shall make the determination if Geotextile utilization is necessary.

Note 2: Geotextile fabric having a minimum weight of 6 ounces and meeting the requirements of Article 1080.02 of the Standard Specification shall be used as a separation layer.

Gradation #2:

Material: Subbase Granular Material, Type C, or RAP

The Subbase Granular Material, Type C shall meet a gradation of CA 6 or CA 10 and a minimum 'D' quality as specified in Section 1004 of the Standard Specifications. RAP shall contain a minimum of Class D quality course aggregates and shall meet the gradation limits as specified in Section 1031 of the Standard Specifications.

Gradation #1 shall be used in the lower 9 inches (230 mm). Gradation #2 shall be used in the upper 3 inches (70 mm) as a capping material.

The material shall be placed in two or more lifts or as directed by the Engineer. Each lift shall be rolled with a vibratory roller meeting the requirements of Article 1101.01 of the Standard Specifications to obtain the desired compaction. Construction equipment not necessary for the completion of the work shall not be allowed on the subgrade until completion of the recommended thickness of the Aggregate Subgrade. Any damage to the compacted Aggregate Subgrade due to the Contractor's activities or operations shall be corrected.

Method of Measurement: Aggregate Subgrade 12" (300 mm) will be measured in place and the area computed in square yards (square meters). The width shall be as shown on the plans.

Basis of Payment: This work will be paid for at the contract unit price per square yard (square meter) for AGGREGATE SUBGRADE 12" (300MM).

AGGREGATE SURFACE COURSE, TYPE B

(Effective January 1, 2007)

Add the following to Article 402.07 of the Standard Specifications:

The top layer shall be given a final rolling with a roller meeting the requirements of Article 1101.01.

Revised 01/16/2008

NIGHT WORK ON INTERSTATE 80

The Contractor shall complete the following work requiring temporary interstate lane closures (Standard 701401) during nighttime operations only. Nighttime operations shall be defined as 8:00 p.m. to 6:00 a.m. the following day.

- removing the existing bridge beams
- erecting the proposed bridge beams
- placing the temporary concrete barrier
- removing existing pavement markings
- milling
- resurfacing
- pavement marking
- removing and resetting raised pavement markers

MAINTENANCE OF LIGHTING SYSTEM

The work shall consist of the contractor assuming maintenance of the existing and proposed lighting for the duration of the project, and ensures the lights are operational when traffic is using the ramps.

This work shall be paid for at the unit calendar month for MAINTENANCE OF LIGHTING SYSTEM.

MAINTENANCE OF FIELD TILE SYSTEMS

This work consists of furnishing all equipment, labor, and materials to replace and maintain existing field tile systems as shown in the plans. All field tiles within state right of way shall be replaced in accordance with the plan detail, the special provisions, and section 611. Portions of a tile run that pass under I 80 shall be replaced in a future contract. Connections to existing tile to remain shall be made at field tile junction vaults. Exact locations of tiles and vaults shall be determined by the engineer.

CONCRETE MEDIAN

Description. This work shall consist of constructing full depth concrete median and curb and gutter as shown in the plans.

Method of Measurement. This work will be measured for payment in place and the area computed in square feet. This work will include the construction of concrete curb and gutter as shown in the plans. Concrete curb and gutter will not be measured separately for payment.

Basis of Payment. This work will be paid for at the contract unit price per square foot for CONCRETE MEDIAN. Concrete curb and gutter will not be paid for separately, but will be included within the unit price per square foot for CONCRETE MEDIAN.

Revised 01/16/2008