

CONTRACT NO. 76387

PAVING SCHEDULE								
LOCATION STATION TO STATION	BITUMINOUS MATERIALS (PRIME COAT) (TON)	AGGREGATE (PRIME COAT) (TON)	INCIDENTAL HOT-MIX ASPHALT SURFACING (TON)	HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N70 (TON)	LEVELING BINDER (MACHINE METHOD), N70 (TON)	HOT-MIX ASPHALT PAVEMENT (FULL DEPTH), 11" (SQ YD)	HOT-MIX ASPHALT SHOULDERS (TON)	AGGREGATE BASE COURSE, TYPE A (TON)
LT. 24+84.00 TO 25+65.00							7	
LT. 25+42.00 TO 26+10.00							20	
LT. 26+40.00 TO 26+72.00							9	
LT. 27+42.00 TO 27+84.00							3	
RT. 24+84.00 TO 25+40.00							5	
RT. 26+03.00 TO 26+30.00							8	
RT. 26+59.00 TO 27+84.00							37	
MAINLINE 24+84.00 TO 27+84.00	0.81	4.3		82	41			
STRUCTURE 26+19.03 TO 26+48.97						87		30
P.E. LT. 25+42.29	0.02	0.1	2.9					
C.E. RT. 25+76.16	0.07	0.4	10.2					
S.R. LT. 26+84.31	0.09	0.5	9.9					
LT. 24+84.00 TO 25+74.00								
LT. 25+74.00 TO 26+19.00						65		22
RT. 24+84.00 TO 25+83.00								
RT. 25+83.00 TO 26+19.00						52		18
LT. 26+48.97 TO 26+85.00						52		18
LT. 26+85.00 TO 27+84.00								
RT. 26+48.97 TO 26+94.00						65		22
RT. 26+94.00 TO 27+84.00								
TOTAL	1.0	5.3	23.0	82	41	321	89	110

SEEDING SCHEDULE*					
LOCATION STATION TO STATION	SEEDING CLASS 2 (ACRE)	NITROGEN FERTILIZER NUTRIENT (LB)	PHOSPHORUS FERTILIZER NUTRIENT (LB)	POTASSIUM FERTILIZER NUTRIENT (LB)	MULCH METHOD 2 (ACRE)
LT. 24+84.00 TO 25+30.00	0.007	0.60	0.60	0.60	0.007
LT. 25+39.00 TO 26+00.00	0.016	1.47	1.47	1.47	0.016
LT. 26+49.00 TO 26+74.00	0.004	0.33	0.33	0.33	0.004
LT. 26+94.00 TO 27+84.00	0.011	0.96	0.96	0.96	0.011
RT. 24+84.00 TO 25+76.00	0.013	1.18	1.18	1.18	0.013
RT. 26+06.00 TO 26+20.00	0.002	0.19	0.19	0.19	0.002
RT. 26+71.00 TO 27+84.00	0.013	1.17	1.17	1.17	0.013
TOTAL	0.07	5.9	5.9	5.9	0.1

* BDE REQUIRES MINIMUM 0.25 ACRES OF SEEDING, AS REFLECTED IN THE SUMMARY OF QUANTITIES

PIPE CULVERT SCHEDULE		
LOCATION STATION TO STATION	END SECTIONS, 15" (EACH)	PIPE CULVERTS, CLASS D, TYPE 1 15" (FOOT)
26' LT. 25+25.00	1	
26' RT. 25+51.00	1	
26' LT. 26+04.00	1	
26' RT. 26+24.00	1	
25' LT. 26+43.00	1	
25' LT. 27+23.00	1	
26' LT. 25+25.00 TO 26+04.00		79
26' RT. 25+51.00 TO 26+24.00		73
25' LT. 26+43.00 TO 27+23.00		80
TOTAL	6	232

EARTHWORK SCHEDULE				
LOCATION STATION TO STATION	EARTH EXCAVATION (CU YD)	EARTH EXCAVATION ADJ. FOR SHRINKAGE (25% SHRINKAGE) (CU YD)	EMBANKMENT (CU YD)	EARTHWORK BALANCE (CU YD)
24+50.00 TO 25+00.00	5.9	4.4	1.0	3.4
25+00.00 TO 25+50.00	12.7	9.5	7.8	1.7
25+50.00 TO 26+00.00	15.0	11.3	30.5	-19.2
26+00.00 TO 26+50.00	11.5	8.6	29.4	-20.8
26+50.00 TO 27+00.00	10.0	7.5	5.9	1.6
27+00.00 TO 27+50.00	14.7	11.0	0.2	10.9
27+50.00 TO 28+00.00	7.9	5.9	0.0	5.9
TOTAL	77.7	58.3	74.8	-16.5

PAVEMENT MARKING SCHEDULE			
LOCATION STATION TO STATION	THERMOPLASTIC PAVEMENT MARKING - LINE 4" (FOOT)	RAISED REFLECTIVE PAVEMENT MARKER (EACH)	RAISED REFLECTIVE PAVEMENT MARKER REMOVAL (EACH)
EDGE LINES 24+84.00 TO 27+84.00	600		
CTR. SKIP 24+84.00 TO 27+84.00	75	4	4
TOTAL	675	4	4

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
SCHEDULE OF QUANTITIES
 FAU ROUTE 9296
 SECTION 65BR
 MONROE COUNTY
 SCALE: VERT. NONE
 HORIZ. NONE
 DATE: JANUARY 2007
 DRAWN BY LLO
 CHECKED BY LEL