



TEMPORARY PAVEMENT DATA

STATION	OFFSET	STATION	OFFSET
33	4059+94 50' RT	41	4063+68 33' RT
34	4060+56 50' RT	42	4064+15 44' LT
35	4061+05 46' RT	43	4064+16 63' LT
36	4059+99 92' RT	44	7001+53 RAMP @
37	4060+69 92' RT	45	7001+54 4' LT
38	4063+11 33' RT	46	4063+16 44' LT
39	8998+79 14' LT	47	4063+85 88' RT
40	8999+38 23' RT	48	4063+94 87' RT

49 POINT AT STA. 4063+25, 27' RT INDICATES PAVEMENT MARKING EDGE LINE

NOTES

- SEE TEMPORARY PAVEMENT DETAIL ON MAINTENANCE OF TRAFFIC DETAILS SHEET.
- TEMPORARY CONCRETE BARRIER SHALL BE CONTINUOUSLY PINNED TO THE PAVEMENT AT LOCATIONS INDICATED ON THE MOT TYPICAL SECTIONS. SEE MAINTENANCE OF TRAFFIC GENERAL NOTES.
- HORIZONTAL AND VERTICAL TRANSITIONS SHALL BE INSTALLED AT THE LIMITS OF THE CURB AND GUTTER AS DIRECTED BY THE ENGINEER IN ACCORDANCE WITH THE MAINTENANCE OF TRAFFIC DETAILS.

