

LEGEND

- CONSTRUCTION JOINT
- LONGITUDINAL CONSTRUCTION JOINT NO. 6 X 2' LONG DEFORMED TIE BARS GROUTED-IN PLACE (EPOXY COATED)
- AT 2' C-C. (STANDARD 420001-07)
- TRANSVERSE CONSTRUCTION JOINT 1'-6" LONG DOWEL BARS (EPOXY COATED) AT 1' C-C (STANDARD 420101-04)
- SAWED JOINT
- LONGITUDINAL SAWED JOINT NO. 6 X 2'-6" LONG DEFORMED TIE BARS (EPOXY COATED) AT 2'-6" C-C (STANDARD 420001-07)
- TRANSVERSE CONSTRUCTION JOINT 1'-6" LONG DOWEL BARS (EPOXY COATED) AT 1' C-C (STANDARD 420001-07)
- SAWED/CONSTRUCTION JOINT WITHOUT BARS
- PAVEMENT SEPARATION JOINT (IDOT DISTRICT 1 STANDARD DETAIL BD52) (PAID FOR AS SLEEPER SLAB)
- LENGTH (IN FEET) OF PAVEMENT PANEL (BETWEEN TRANSVERSE JOINTS) IF DIFFERENT THAN 15.0'

- NOTES:**
1. ADDITIONAL SAWED CONTRACTION JOINTS MAY BE REQUIRED IN THE FIELD, AS DIRECTED BY THE ENGINEER. EXACT LOCATIONS TO BE VERIFIED IN THE FIELD AND APPROVED BY THE ENGINEER.
 2. ALL TRANSVERSE JOINTS SHALL BE A MAXIMUM OF 15.0 FEET UNLESS OTHERWISE NOTED. SEE STANDARD 420101-04 FOR ADDITIONAL INFORMATION.
 3. PAVEMENT ROUNDOUTS FOR MANHOLES AND VALVE VAULTS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STANDARD 420111-03.
 4. ALL ELEVATIONS NOT SHOWN SHALL FOLLOW THE TYPICAL SECTIONS AND PROFILES.
 5. PROPOSED ISLANDS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STANDARD 606301-04.
 6. ALL SIDEWALK RAMPS MUST BE ADA COMPLIANT (STANDARD 424001-07).


PT	STATION	OFFSET	ELEVATION
A	515+63.2	85.0' LT	669.62
B	515+50.6	65.1' LT	669.74
C	515+62.0	51.0' LT	670.08
D	515+28.0	52.5' LT	669.46
E	515+63.4	27.0' LT	670.36
F	515+63.4	15.0' LT	670.48
G	515+50.9	15.0' LT	670.30
H	515+28.0	15.0' LT	670.01
I	515+50.9	8.1' LT	670.36
J	515+40.7	4.6' LT	670.03
K	515+11.2	9.0' LT	669.88
L	515+09.5	9.0' LT	669.87
M	515+50.9	3.9' RT	671.48
N	515+28.0	3.0' RT	670.08
O	515+11.2	3.0' RT	669.92
P	515+63.4	15.0' RT	670.71
Q	515+50.9	15.0' RT	670.51
R	515+28.0	15.0' RT	670.13
S	515+63.4	27.0' RT	670.78
T	515+38.3	27.0' RT	670.33
U	515+28.0	27.0' RT	670.14
V	515+64.8	51.0' RT	670.89
W	515+38.3	51.0' RT	670.40
X	515+38.3	53.0' RT	670.40
Y	515+11.2	52.5' RT	669.83
Z	642+39.6	31.0' RT	670.88

PT	STATION	OFFSET	ELEVATION
AA	642+39.7	33.0' RT	670.58
AB	642+42.9	44.5' RT	670.67
AC	642+51.8	42.8' RT	670.54
AD	642+65.0	31.0' RT	670.66
AE	642+42.9	44.5' RT	670.67
AF	643+55.0	32.5' RT	669.82
AG	640+31.3	19.0' LT	669.52
AH	640+54.1	43.0' LT	669.55
AJ	640+54.1	41.0' LT	669.58
AJ	640+54.1	30.0' LT	669.42
AK	640+54.1	19.0' LT	669.91
AL	640+52.5	13.0' LT	669.92
AM	640+66.2	41.0' LT	669.77
AN	640+66.2	30.0' LT	669.60
AO	640+66.2	19.0' LT	670.10
AP	640+66.2	13.0' LT	670.13
AQ	640+66.2	9.0' LT	370.13
AR	640+75.3	19.0' LT	670.23
AS	640+75.3	13.0' LT	670.27
AT	641+84.4	41.0' LT	670.02
AU	640+95.0	22.5' LT	670.43
AV	640+95.3	19.0' LT	670.49
AW	640+95.8	13.0' LT	670.56
AX	640+96.0	10.2' LT	670.59
AY	641+97.6	9.0' RT	670.54
AZ	640+98.0	14.9' RT	670.46

PT	STATION	OFFSET	ELEVATION
BA	640+99.3	31.0' RT	670.23
BB	641+10.0	13.9' RT	670.60
BC	641+11.0	26.8' RT	670.42
BD	641+18.0	36.7' LT	670.47
BE	641+19.0	24.4' LT	670.66
BF	641+23.0	25.8' RT	670.55
BG	641+29.0	49.9' LT	670.37
BH	641+29.9	37.6' LT	670.56
BI	641+39.8	50.7' LT	670.44
BJ	641+53.3	14.8' LT	671.06
BK	641+53.8	2.5' LT	671.11
BL	641+59.9	40.0' LT	670.73
BM	641+61.8	15.5' LT	671.11
BN	641+62.8	3.3' LT	671.18
BO	641+63.8	9.6' RT	671.08
BP	641+71.8	670.98	670.79
BQ	641+72.8	28.7' LT	670.98
BR	641+76.8	21.5' RT	670.97
BS	641+84.8	29.7' LT	671.01
BT	641+85.7	17.4' LT	671.19
BU	641+96.8	30.0' LT	671.03
BV	641+97.7	18.4' LT	671.19
BW	641+98.5	8.0' LT	671.30
BX	641+98.7	6.1' LT	671.30
BY	641+99.4	3.0' RT	671.28
BZ	641+99.7	6.7' RT	671.24

PT	STATION	OFFSET	ELEVATION
CA	641+99.9	9.0' RT	671.22
CB	642+00.8	19.6' RT	671.06
CC	642+28.3	3.0' RT	671.22
CD	642+28.3	9.0' RT	671.23
CE	642+38.6	3.0' RT	671.20
CF	642+59.3	9.0' RT	671.15
CG	642+65.0	9.0' RT	671.12
CH	516+46.9	84.3' RT	670.62
CI	516+58.4	65.5' RT	670.55
CJ	516+79.7	52.5' RT	670.70
CK	516+79.7	52.5' RT	670.02
CL	516+86.1	51.0' RT	669.91
CM	517+90.0	40.5' RT	669.35
CN	516+79.7	15.0' RT	670.14
CO	517+09.4	15.0' RT	669.87
CP	516+79.7	9.0' RT	670.10
CQ	516+90.7	9.0' RT	669.95
CR	516+99.3	9.0' RT	669.84
CS	516+79.7	3.0' LT	670.14
CT	516+89.5	3.0' LT	670.05
CU	516+99.3	3.0' LT	669.96
CV	516+79.7	15.0' LT	669.97
CW	516+89.5	3.0' LT	669.86
CX	516+65.4	27.0' LT	670.03
CY	516+79.7	27.0' LT	669.80
CZ	516+62.8	51.0' LT	669.81

PT	STATION	OFFSET	ELEVATION
DA	516+63.4	58.7' LT	669.72
DB	516+65.4	51.0' LT	669.76
DC	516+72.2	51.0' LT	669.61
DD	516+72.2	53.0' LT	669.59
DE	516+99.3	52.5' LT	669.10
DF	516+68.4	75.5' LT	669.54
DG	516+61.4	100.0' LT	669.23
DH	516+59.3	207.9' LT	666.85
DI	514+89.8	15.0' LT	669.73



FILE NAME =	USER NAME = BAWtor.t	DESIGNED -	REVISED -
G:\CH11\0158\Road\Sheets\0160T35-INT	ERSEC-02.dgn	DRAWN -	REVISED -
	PLOT SCALE = 40.0000' / in.	CHECKED -	REVISED -
	PLOT DATE = 12/6/2012	DATE - 10/31/2012	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**WILLOW ROAD INTERSECTION PAVING PLAN
AT ILLINOIS ROUTE 43 / WAUKEGAN RD**

SCALE: SHEET NO. 265 OF 919 SHEETS

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
305	(1920.01,1518,2022&1922,4BR)	COOK	919	265
FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT			CONTRACT NO. 60T35	