

BEAM 8

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. W. Abut.	714+45.19	13.50	633.17	633.17
⊕ Brg. W. Abut.	714+46.44	13.50	633.17	633.17
A	714+56.44	13.50	633.21	633.33
B	714+66.44	13.50	633.24	633.45
C	714+76.44	13.50	633.25	633.53
D	714+86.44	13.50	633.25	633.56
E	714+96.44	13.50	633.25	633.54
F	715+06.44	13.50	633.23	633.46
G	715+16.44	13.50	633.20	633.34
⊕ Brg. E. Abut.	715+28.44	13.50	633.15	633.15
Bk. E. Abut.	715+29.69	13.50	633.14	633.14

BEAM 9

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. W. Abut.	714+45.19	20.25	633.03	633.03
⊕ Brg. W. Abut.	714+46.44	20.25	633.03	633.03
A	714+56.44	20.25	633.07	633.19
B	714+66.44	20.25	633.10	633.31
C	714+76.44	20.25	633.11	633.39
D	714+86.44	20.25	633.11	633.42
E	714+96.44	20.25	633.11	633.40
F	715+06.44	20.25	633.09	633.32
G	715+16.44	20.25	633.06	633.20
⊕ Brg. E. Abut.	715+28.44	20.25	633.01	633.01
Bk. E. Abut.	715+29.69	20.25	633.00	633.00

SOUTH SIDEWALK GUTTER LINE

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. W. Abut.	714+45.19	26.00	632.91	632.91
⊕ Brg. W. Abut.	714+46.44	26.00	632.91	632.91
A	714+56.44	26.00	632.95	633.08
B	714+66.44	26.00	632.98	633.22
C	714+76.44	26.00	632.99	633.31
D	714+86.44	26.00	632.99	633.34
E	714+96.44	26.00	632.99	633.32
F	715+06.44	26.00	632.97	633.23
G	715+16.44	26.00	632.94	633.10
⊕ Brg. E. Abut.	715+28.44	26.00	632.89	632.89
Bk. E. Abut.	715+29.69	26.00	632.88	632.88

BEAM 10

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. W. Abut.	714+45.19	27.00	632.93	632.93
⊕ Brg. W. Abut.	714+46.44	27.00	632.93	632.93
A	714+56.44	27.00	632.97	633.11
B	714+66.44	27.00	633.00	633.25
C	714+76.44	27.00	633.01	633.33
D	714+86.44	27.00	633.01	633.36
E	714+96.44	27.00	633.01	633.34
F	715+06.44	27.00	632.99	633.26
G	715+16.44	27.00	632.96	633.12
⊕ Brg. E. Abut.	715+28.44	27.00	632.91	632.91
Bk. E. Abut.	715+29.69	27.00	632.90	632.90

BEAM 11

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. W. Abut.	714+45.19	33.75	633.07	633.07
⊕ Brg. W. Abut.	714+46.44	33.75	633.07	633.07
A	714+56.44	33.75	633.11	633.24
B	714+66.44	33.75	633.14	633.38
C	714+76.44	33.75	633.15	633.46
D	714+86.44	33.75	633.15	633.49
E	714+96.44	33.75	633.15	633.47
F	715+06.44	33.75	633.13	633.39
G	715+16.44	33.75	633.10	633.25
⊕ Brg. E. Abut.	715+28.44	33.75	633.05	633.05
Bk. E. Abut.	715+29.69	33.75	633.04	633.04

FACE OF SOUTH PARAPET

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. W. Abut.	714+45.19	35.00	633.09	633.09
⊕ Brg. W. Abut.	714+46.44	35.00	633.09	633.09
A	714+56.44	35.00	633.13	633.26
B	714+66.44	35.00	633.16	633.40
C	714+76.44	35.00	633.17	633.49
D	714+86.44	35.00	633.17	633.52
E	714+96.44	35.00	633.17	633.50
F	715+06.44	35.00	633.15	633.41
G	715+16.44	35.00	633.12	633.28
⊕ Brg. E. Abut.	715+28.44	35.00	633.07	633.07
Bk. E. Abut.	715+29.69	35.00	633.06	633.06

12/5/2012 5:46:10 PM - G:\CHIN\058\Bridges\CADD\Sheets\0162844-D160135-08-SL LABEL.3.dgn



USER NAME = jrmickow	DESIGNED - JRM	REVISED -
	CHECKED - MDS	REVISED -
PLOT SCALE = 16x0.0000 '1' / 1x1	DRAWN - JRM	REVISED -
PLOT DATE = 12/5/2012	CHECKED - MDS	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**TOP OF SLAB ELEVATIONS
STRUCTURE NO. 016-2844**

SHEET NO. 8 OF 30 SHEETS

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
0305	(1920.01,1518,2022&1922.4B)R	COOK	919	458
			CONTRACT NO. 60T35	
ILLINOIS FED. AID PROJECT				