

SCHEDULE OF QUANTITIES

TEMPORARY PAVEMENT MARKING SCHEDULE																					
70300210				70300220						70300240			70300260				70300280				
TEMPORARY MARKING LETTERS & SYMBOLS				TEMPORARY PAVEMENT MARKING - LINE 4"						TEMPORARY PAVEMENT MARKING - LINE 6"			TEMPORARY PAVEMENT MARKING - LINE 12"				TEMPORARY PAVEMENT MARKING - LINE 24"				
STATION	SYMBOL	LANE	(WHITE)	STATION	TO	STATION	(WHITE)	(YELLOW)	(YELLOW)	STATION	LANE	(WHITE)	STATION	TO	STATION	(WHITE)	(YELLOW)	STATION	MARKING	LANE	(WHITE)
			(SQ. FT.)				(FOOT)	(FOOT)	(FOOT)			(FOOT)				(FOOT)	(FOOT)				(FOOT)
473+46.00	R.R. CROSSING	EB	61.2	222+07.73	TO	475+13.67	50,611.9	20,719.6	4,748.1	RAMP A	SB	163.0	2028+00.00	TO	2029+93.00	0.0	93.3	473+23.00	R.R. CROSSING	EB	11.8
477+13.00	R.R. CROSSING	WB	61.2	475+45.32	TO	481+00.00	1,065.4	1,109.4	0.0	RAMP C	NB	150.0	RAMP A			84.4	0.0	473+73.00	R.R. CROSSING	EB	11.8
2031+22.00	L.T. ARROW	TL	15.6	2026+75.96	TO	2027+39.95	0.0	128.0	0.0	TOTAL =		313.0	RAMP C			86.3	0.0	474+73.00	STOP BAR	EB	14.2
2031+46.00	L.T. ARROW	TL	15.6	2027+39.95	TO	2029+93.00	0.0	1,053.9	0.0	USE =		313.0	TOTAL =		170.7	93.3		475+87.00	STOP BAR	WB	14.2
2033+72.00	L.T. ARROW	TL	15.6	2030+62.00	TO	2034+56.00	0.0	787.7	200.0	TOTAL LENGTH =		265.0	USE =		171.0	94.0		476+87.00	R.R. CROSSING	WB	11.8
2033+96.00	L.T. ARROW	TL	15.6	2035+57.00	TO	2043+23.00	1,488.5	1,549.5	0.0	TOTAL LENGTH =		265.0	TOTAL LENGTH =		265.0			477+37.00	R.R. CROSSING	WB	11.8
2035+75.00	L.T. ARROW	TL	15.6	2043+75.00	TO	2055+96.00	2,945.5	2,716.5	0.0	TOTAL LENGTH =		265.0	TOTAL LENGTH =		265.0			RAMP A	STOP BAR	SB	18.0
2036+49.00	L.T. ARROW	TL	15.6	2056+66.00	TO	2066+06.00	1,645.5	1,889.0	0.0	TOTAL LENGTH =		265.0	TOTAL LENGTH =		265.0			RAMP A	STOP BAR	SB	18.0
2037+23.00	L.T. ARROW	TL	15.6	RAMP A			215.4	121.9	0.0	TOTAL LENGTH =		265.0	TOTAL LENGTH =		265.0			RAMP C	STOP BAR	NB	18.0
2037+97.00	L.T. ARROW	TL	15.6	RAMP B			163.7	142.9	0.0	TOTAL LENGTH =		265.0	TOTAL LENGTH =		265.0			RAMP C	STOP BAR	NB	18.0
2043+93.00	L.T. ARROW	TL	15.6	RAMP C			249.8	168.5	0.0	TOTAL LENGTH =		265.0	TOTAL LENGTH =		265.0			RAMP C	STOP BAR	NB	18.0
2044+61.00	L.T. ARROW	TL	15.6	RAMP D			123.8	84.7	0.0	TOTAL LENGTH =		265.0	TOTAL LENGTH =		265.0			TOTAL =		147.6	
2045+29.00	L.T. ARROW	TL	15.6	TOTAL =			58509.5	30471.6	4948.1	TOTAL LENGTH =		265.0	TOTAL LENGTH =		265.0			USE =		148.0	
2045+97.00	L.T. ARROW	TL	15.6	USE =			58510.0	30472.0	4949.0	TOTAL LENGTH =		265.0	TOTAL LENGTH =		265.0			TOTAL =		147.6	
2046+65.00	L.T. ARROW	TL	15.6	TOTAL LENGTH =			93931.0			TOTAL LENGTH =		265.0	TOTAL LENGTH =		265.0			USE =		148.0	
2053+38.00	L.T. ARROW	TL	15.6	NOTE: QUANTITIES FOR SOLID YELLOW LINES ARE ESTIMATED FROM FIELD MEASUREMENTS, LOCATIONS SHOULD BE NOTED IN THE FIELD PRIOR TO REMOVAL.																	
2054+18.00	L.T. ARROW	TL	15.6																		
2054+98.00	L.T. ARROW	TL	15.6																		
2055+78.00	L.T. ARROW	TL	15.6																		
TOTAL =			387.6																		
USE =			388.0																		

NOTE: EXACT LOCATION OF STOP BARS SHALL BE AS DIRECTED BY THE ENGINEER.

63200310 GUARDRAIL REMOVAL SCHEDULE

STATION	TO	STATION	LENGTH (FOOT)	
RT	227+30.66	TO RT	229+93.78	263.1
LT	227+85.99	TO LT	230+86.68	300.7
RT	265+87.86	TO RT	271+75.79	587.9
LT	267+48.28	TO LT	272+22.46	474.2
RT	284+90.45	TO RT	290+65.20	574.8
LT	285+30.09	TO LT	287+54.15	224.1
RT	338+00.00	TO RT	340+75.50	275.5
LT	338+75.50	TO LT	341+51.00	275.5
RT	352+38.00	TO RT	355+13.50	275.5
TOTALS =			3251.2	
USE =			3252.0	

PROPOSED GUARDRAIL SCHEDULE

SIDE	APP/DEP	63000001														78201000		63000025				78200405
		63100167 / 63100169						78201000		63000001				63000025		78200405						
		TRAFFIC BARRIER TERMINAL, TYPE 1 (SPECIAL) TANGENT / FLARED						TERMINAL MARKER		STEEL PLATE BEAM GUARDRAIL TYPE A, 6 FOOT POSTS				STEEL PLATE BEAM GUARDRAIL ATTACHED TO STRUCTURES		GUARDRAIL MARKERS						
		STATION	TO	STATION	TANG. (EACH)	FLARED (EACH)	DIR. APPLIED (EACH)	STATION	TO	STATION	LENGTH (FOOT)	STATION	TO	STATION	LENGTH (FOOT)	TYPE A EACH						
RT	APP	227+30.61	TO	227+80.61	1.0		1.0	227+80.61	TO	229+05.61	125.0					4.0						
RT	DEP	229+05.61	TO	229+55.61	1.0		1.0															
LT	DEP	228+34.00	TO	228+84.00	1.0		1.0	228+84.00	TO	229+96.50	112.5					4.0						
LT	APP	229+96.50	TO	230+46.50	1.0		1.0															
RT	APP	265+84.22	TO	266+34.22	1.0		1.0	266+34.22	TO	270+96.72	425.0	267+61.83	TO	267+74.33	12.5	6.0						
RT	DEP	270+96.72	TO	271+46.72	1.0		1.0					270+61.83	TO	270+86.83	25.0							
LT	DEP	267+52.53	TO	268+02.53	1.0		1.0	268+02.53	TO	271+65.03	325.0	267+95.05	TO	268+07.55	12.5	5.0						
LT	APP	271+65.03	TO	272+15.03		1.0	1.0					270+57.55	TO	270+82.55	25.0							
RT	APP	285+09.68	TO	285+59.68	1.0		1.0	285+59.68	TO	289+84.68	400.0	286+54.68	TO	286+67.18	12.5	6.0						
RT	DEP	289+84.68	TO	290+34.68	1.0		1.0					289+54.68	TO	289+67.18	12.5							
LT	DEP	285+52.76	TO	286+02.76	1.0		1.0	286+02.76	TO	287+02.76	100.0					4.0						
LT	APP	287+02.76	TO	287+52.76	1.0		1.0															
LT	DEP	288+60.69	TO	289+10.69	1.0		1.0	289+10.69	TO	290+23.19	112.5					4.0						
LT	APP	290+23.19	TO	290+73.19	1.0		1.0															
RT	APP	338+14.13	TO	338+64.13	1.0		1.0	338+64.13	TO	340+01.63	125.0	339+71.63	TO	339+84.13	12.5	4.0						
RT	DEP	340+01.63	TO	340+51.63	1.0		1.0															
LT	DEP	339+13.84	TO	339+63.84	1.0		1.0	339+63.84	TO	340+88.84	112.5	339+68.84	TO	339+81.34	12.5	4.0						
LT	APP	340+88.84	TO	341+38.84	1.0		1.0															
RT	APP	352+57.32	TO	353+07.32	1.0		1.0	353+07.32	TO	354+32.32	100.0	353+89.82	TO	354+14.82	25.0	4.0						
RT	DEP	354+32.32	TO	354+82.32	1.0		1.0															
LT	DEP	352+60.18	TO	353+10.18	1.0		1.0	353+10.18	TO	354+47.68	112.5	353+40.18	TO	353+65.18	25.0	4.0						
LT	APP	354+47.68	TO	354+97.68	1.0		1.0															
TOTAL =					21.0	1.0	22.0	TOTAL =					2,050.0	TOTAL =					175.0	49.0		
USE =					21.0	1.0	22.0	USE =					2,050.0	USE =					175.0	49.0		