

SHOULDER SCHEDULE												
LOCATION STATION TO STATION FAP 662/67 (IL 4/97)				LENGTH (FT)	WIDTH (FT)		AREA (SQ YD)	PAVED SHOULDER REMOVAL (SQ YD)	HOT-MIX ASPHALT SHOULDERS,			BITUMINOUS MATERIALS (PRIME COAT) (TON)
									2 1/2" (TON)	2 1/4" (TON)	VARIBLE DEPTH (TON)	
<b>IL 4 (VETERANS PKWY)</b>												
<b>NORTHBOUND</b>												
OUTSIDE	STA. 216+00.00	TO	STA. 222+63.36	663.36	10		737.1		103.2			0.28
OUTSIDE	STA. 225+41.84	TO	STA. 231+03.53	561.69	4		249.6		34.9			0.09
OUTSIDE	STA. 231+03.53	TO	STA. 232+15.45	111.92	4	TO	10	87.0	12.2			0.03
OUTSIDE	STA. 232+15.45	TO	STA. 238+27.42	611.97	10		680.0		95.2			0.26
OUTSIDE	STA. 240+92.18	TO	STA. 254+42.30	1,350.12	10		1500.1		210.0			0.57
OUTSIDE	STA. 256+62.84	TO	STA. 258+99.17	236.33	5		131.3		18.4			0.05
OUTSIDE	STA. 258+99.17	TO	STA. 259+66.50	67.33	5	TO	6	41.1	5.8			0.02
<b>STA. EQ. 259+66.50 BK = 259+53.69 AH</b>												
OUTSIDE	STA. 259+53.69	TO	STA. 261+00.70	147.01	6.00	TO	10	130.7	18.3			0.05
OUTSIDE	STA. 261+00.70	TO	STA. 263+97.87	297.17	9		297.2		41.6			0.11
OUTSIDE	STA. 263+97.87	TO	STA. 274+50.00	1,052.13	10		1169.0		163.7		130.9	0.44
INSIDE	STA. 216+00.00	TO	STA. 223+26.98	726.98	6		484.7		67.9			0.18
INSIDE	STA. 223+26.98	TO	STA. 223+55.18	28.20	6.00	TO	0	9.4	1.3			0.00
INSIDE	STA. 228+16.48	TO	STA. 228+38.73	22.25	4	TO	6	12.4	1.7			0.00
INSIDE	STA. 228+38.73	TO	STA. 238+47.80	1,009.07	6		672.7		94.2			0.26
INSIDE	STA. 240+90.95	TO	STA. 254+92.74	1,401.79	6		934.5		130.8			0.36
INSIDE	STA. 255+90.75	TO	STA. 258+25.28	234.53	6		156.4		21.9			0.06
INSIDE	STA. 258+25.28	TO	STA. 259+27.16	101.88	14.00	TO	6.00	113.2	15.8			0.04
INSIDE	STA. 259+24.28	TO	STA. 259+66.50	42.22	6		28.1		3.9			0.01
<b>STA. EQ. 259+66.50 BK = 259+53.69 AH</b>												
INSIDE	STA. 259+53.69	TO	STA. 274+50.00	1,496.31	6		997.5		139.7			0.38
<b>SUB-TOTAL</b>									<b>1180.5</b>		<b>130.9</b>	<b>3.20</b>
<b>IL 4 (VETERANS PKWY)</b>												
<b>SOUTHBOUND</b>												
OUTSIDE	STA. 216+00.00	TO	STA. 217+83.57	183.57	10		204.0		28.6			0.08
OUTSIDE	STA. 217+83.57	TO	STA. 220+21.90	238.33	10	TO	4	185.4	26.0			0.07
OUTSIDE	STA. 220+21.90	TO	STA. 222+97.31	275.41	4		122.4		17.1			0.05
OUTSIDE	STA. 225+88.51	TO	STA. 232+14.41	625.90	10		695.4		97.4			0.26
OUTSIDE	STA. 232+14.41	TO	STA. 238+50.27	635.86	10		706.5		98.9			0.27
OUTSIDE	STA. 240+88.65	TO	STA. 249+89.65	901.00	10		1001.1		140.2			0.38
OUTSIDE	STA. 249+89.65	TO	STA. 252+36.40	246.75	10.00	TO	4.00	191.9	26.9			0.07
OUTSIDE	STA. 252+36.40	TO	STA. 254+76.88	240.48	4		106.9		15.0			0.04
OUTSIDE	STA. 256+97.47	TO	STA. 259+66.50	269.03	10		298.9		41.8			0.11
<b>STA. EQ. 259+66.50 BK = 259+53.69 AH</b>												
OUTSIDE	STA. 259+53.69	TO	STA. 274+50.00	1,496.31	5	TO	8	1080.7	151.3			0.41
INSIDE	STA. 216+00.00	TO	STA. 217+25.77	125.77	6		83.8		11.7			0.03
INSIDE	STA. 217+25.77	TO	STA. 217+47.01	21.24	6	TO	4	11.8	1.7			0.00
INSIDE	STA. 217+47.01	TO	STA. 221+81.27	434.26	4		193.0		27.0			0.07
INSIDE	STA. 219+78.60	TO	STA. 222+14.23	249.63	0	TO	12	166.4	23.3			0.06
INSIDE	STA. 222+14.23	TO	STA. 224+02.45	188.22	8		167.3		23.4			0.06
INSIDE	STA. 222+15.23	TO	STA. 225+71.45	356.22	0	TO	5	99.0	13.9			0.04
INSIDE	STA. 225+71.45	TO	STA. 228+16.64	245.19	5		136.2		19.1			0.05
INSIDE	STA. 228+16.64	TO	STA. 238+30.11	1,013.47	6		675.6		94.6			0.26
INSIDE	STA. 240+89.78	TO	STA. 248+42.56	752.78	6		501.9		70.3			0.19
INSIDE	STA. 248+42.56	TO	STA. 250+01.02	158.46	6	TO	4	88.0	12.3			0.03
INSIDE	STA. 250+01.02	TO	STA. 251+86.46	185.44	4		82.4		11.5			0.03
INSIDE	STA. 251+78.09	TO	STA. 252+86.20	108.11	6	TO	13	114.1	16.0			0.04
INSIDE	STA. 252+86.20	TO	STA. 255+43.33	257.13	5.5		157.1		22.0			0.06
INSIDE	STA. 256+42.36	TO	STA. 259+66.50	324.14	6		216.1		30.3			0.08
<b>STA. EQ. 259+66.50 BK = 259+53.69 AH</b>												
INSIDE	STA. 259+53.69	TO	STA. 274+50.00	1,496.31	6		997.5		139.7			0.38
<b>SUB-TOTAL</b>									<b>1159.7</b>		<b>0.0</b>	<b>3.15</b>