



SECTION A-A

Horiz. Dim. at Rt. L's

* Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.

Note:
Hatched areas indicate concrete removal.

DESIGNED GGE
 CHECKED ARS
 DRAWN Kyle M. Steffen
 CHECKED GGE ARS

EXAMINED
 PASSED
 ACTING ENGINEER OF STRUCTURAL SERVICES
 ACTING ENGINEER OF BRIDGES AND STRUCTURES

DATE NOVEMBER 13, 2012
 REVISED
 REVISED

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

CONCRETE REMOVAL DETAILS
 SN 084-0180

SHEET NO. 4 OF 7 SHEETS

| F.A. RTE. | SECTION | COUNTY | TOTAL SHEETS | SHEET NO. |
|---------------------------|------------------|----------|--------------|-----------|
| 67 | 1RS1,2RS1,5RS-61 | SANGAMON | 116 | 92 |
| CONTRACT NO. 72F23 | | | | |
| ILLINOIS FED. AID PROJECT | | | | |