

WIDENING SCHEDULE

		PORTLAND CEMENT CONCRETE BASE COURSE WIDENING, 12"	PAVEMENT FABRIC	PAVED SHOULDER REMOVAL	SHOULDER RUMBLE STRIPS, 16"
		SO YD	SO YD	SO YD	FOOT
CORNER	LOCATION				
SN 025-0016 (FB)					
SW	2738+14 TO 2740+69	170.0	170.0	170.0	255
NW	2738+14 TO 2740+69	170.0	170.0	170.0	255
SE	2741+90 TO 2743+70	120.0	120.0	120.0	180
NE	2741+90 TO 2743+70	120.0	120.0	120.0	180
SN 025-0017 (WB)					
NE	2742+06 TO 2744+61	170.0	170.0	170.0	255
SE	2742+06 TO 2744+61	170.0	170.0	170.0	255
NW	2739+05 TO 2740+85	120.0	120.0	120.0	180
SW	2739+05 TO 2740+85	120.0	120.0	120.0	180
TOTALS		1160	1160	1160	1740

PAVEMENT MARKING SCHEDULE

STATION TO STATION	PAINT PAVEMENT MARKING - LINE 4"	PAINT PAVEMENT MARKING - LINE 6"	PAVEMENT MARKING REMOVAL	SHORT TERM PAVEMENT MARKING	WORK ZONE PAVEMENT MARKING REMOVAL	RAISED REFLECTIVE PAVEMENT MARKER (BRIDGE)
	FOOT	FOOT	SO FT	FOOT	SO FT	EACH
SN 025-0016 (FB)						
2738+14.00 TO 2740+69.00	510.0	63.8	170.0	45.9	15.3	
2740+69.00 TO 2741+90.00	242.0	30.3	40.3	21.8	7.3	4.0
2741+90.00 TO 2743+70.00	360.0	45.0	120.0	32.4	10.8	
SN 025-0017 (WB)						
2739+05.00 TO 2740+85.00	360.0	45.0	120.0	32.4	10.8	
2740+85.00 TO 2742+06.00	242.0	30.3	40.3	21.8	7.3	4.0
2742+06.00 TO 2744+61.00	510.0	63.8	170.0	45.9	15.3	
TOTALS						
	2224.0	278.0	661.0	200.0	67.0	8.0