

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	STATION	SHEET NO.
F.A.P. 315	34-6, 55-1	HANCOCK	433	234

SHEET NO. 36
36 SHEETS

Contract #68206



Illinois Department of Transportation
Division of Highways
DOT

SOIL BORING LOG

Page 1 of 2
Date 2/8/00

ROUTE		IL 336	DESCRIPTION	Proposed IL 336 over E. Fork of Lamoine R.				LOGGED BY				D. ANDERSON																																																																																																																																																																																																																																			
SECTION		24, 31, 32		LOCATION		SEC. TWP. RNG.																																																																																																																																																																																																																																									
COUNTY		McDon. & Hancock		DRILLING METHOD		HSA				HAMMER TYPE		AUTO																																																																																																																																																																																																																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td rowspan="2">STRUCT. NO. Station</td> <td rowspan="2">D P T H</td> <td rowspan="2">B O W S</td> <td rowspan="2">U O S S</td> <td rowspan="2">M I S S</td> <td rowspan="2">Surface Water Elev. Stream Bed Elev.</td> <td rowspan="2">ft ft</td> <td rowspan="2">D P T H</td> <td rowspan="2">B O W S</td> <td rowspan="2">U O S S</td> <td rowspan="2">M I S S</td> <td colspan="4"></td> </tr> <tr> <td colspan="4"></td> </tr> <tr> <td>BORING NO. Station Offset Ground Surface Elev.</td> <td></td> <td></td> <td></td> <td></td> <td>Groundwater Elev. First Encounter Upon Completion After 24 Hrs.</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>																STRUCT. NO. Station	D P T H	B O W S	U O S S	M I S S	Surface Water Elev. Stream Bed Elev.	ft ft	D P T H	B O W S	U O S S	M I S S									BORING NO. Station Offset Ground Surface Elev.					Groundwater Elev. First Encounter Upon Completion After 24 Hrs.																																																																																																																																																																																																							
STRUCT. NO. Station	D P T H	B O W S	U O S S	M I S S	Surface Water Elev. Stream Bed Elev.	ft ft	D P T H	B O W S	U O S S	M I S S																																																																																																																																																																																																																																					
BORING NO. Station Offset Ground Surface Elev.					Groundwater Elev. First Encounter Upon Completion After 24 Hrs.																																																																																																																																																																																																																																										
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td rowspan="2">TOPSOIL FILL: DK BR SILTY CLAY LOAM, A-6 W/ROOTS & FIBERS 528.90</td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2">2</td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2">25.0</td> <td colspan="7">GR GRAVELLY SAND, A-1-a W/LIMESTONE FRAGMENTS</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="2">DK BR, BR & GR SILTY CLAY LOAM, A-6 526.90</td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2">3</td> <td rowspan="2">1.1</td> <td rowspan="2">18.0</td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2"></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="4">BR & RD BR SILTY CLAY LOAM, A-6 526.90</td> <td rowspan="4"></td> <td rowspan="4"></td> <td rowspan="4">0</td> <td rowspan="4"></td> <td rowspan="4"></td> <td rowspan="4"></td> <td rowspan="4"></td> <td rowspan="4"></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="2">DK GR SILTY CLAY, A-7-6 521.90</td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2">1</td> <td rowspan="2">0.9</td> <td rowspan="2">34.0</td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2"></td> <td colspan="7">Borehole continued with rock coring.</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="2">RD BR & GR TO SILTY LOAM, A-4 520.40</td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2">1</td> <td rowspan="2"></td> <td rowspan="2">22.0</td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2"></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="4">RD BR & GR TO GR SILTY LOAM, A-4 518.40</td> <td rowspan="4"></td> <td rowspan="4"></td> <td rowspan="4">0</td> <td rowspan="4">1.0</td> <td rowspan="4">24.0</td> <td rowspan="4"></td> <td rowspan="4"></td> <td rowspan="4"></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="2">GR SILTY CLAY LOAM, A-6 514.40</td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2">0</td> <td rowspan="2"></td> <td rowspan="2">28.0</td> <td rowspan="2"></td> <td rowspan="2"></td> <td rowspan="2"></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="4">BR TO RD BR & GR SAND, A-1-b 512.90</td> <td rowspan="4"></td> <td rowspan="4"></td> <td rowspan="4">5</td> <td rowspan="4"></td> <td rowspan="4">18.0</td> <td rowspan="4"></td> <td rowspan="4"></td> <td rowspan="4"></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>																TOPSOIL FILL: DK BR SILTY CLAY LOAM, A-6 W/ROOTS & FIBERS 528.90			2					25.0	GR GRAVELLY SAND, A-1-a W/LIMESTONE FRAGMENTS																	DK BR, BR & GR SILTY CLAY LOAM, A-6 526.90			3	1.1	18.0																			BR & RD BR SILTY CLAY LOAM, A-6 526.90			0																															DK GR SILTY CLAY, A-7-6 521.90			1	0.9	34.0				Borehole continued with rock coring.															RD BR & GR TO SILTY LOAM, A-4 520.40			1		22.0																			RD BR & GR TO GR SILTY LOAM, A-4 518.40			0	1.0	24.0																													GR SILTY CLAY LOAM, A-6 514.40			0		28.0																			BR TO RD BR & GR SAND, A-1-b 512.90			5		18.0																												
TOPSOIL FILL: DK BR SILTY CLAY LOAM, A-6 W/ROOTS & FIBERS 528.90			2					25.0	GR GRAVELLY SAND, A-1-a W/LIMESTONE FRAGMENTS																																																																																																																																																																																																																																						
DK BR, BR & GR SILTY CLAY LOAM, A-6 526.90			3	1.1	18.0																																																																																																																																																																																																																																										
BR & RD BR SILTY CLAY LOAM, A-6 526.90			0																																																																																																																																																																																																																																												
DK GR SILTY CLAY, A-7-6 521.90			1	0.9	34.0				Borehole continued with rock coring.																																																																																																																																																																																																																																						
RD BR & GR TO SILTY LOAM, A-4 520.40			1		22.0																																																																																																																																																																																																																																										
RD BR & GR TO GR SILTY LOAM, A-4 518.40			0	1.0	24.0																																																																																																																																																																																																																																										
GR SILTY CLAY LOAM, A-6 514.40			0		28.0																																																																																																																																																																																																																																										
BR TO RD BR & GR SAND, A-1-b 512.90			5		18.0																																																																																																																																																																																																																																										

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-99)



Illinois Department of Transportation
Division of Highways
DOT

ROCK CORE LOG

Page 2 of 2
Date 2/8/00

ROUTE		IL 336	DESCRIPTION	Proposed IL 336 over E. Fork of Lamoine R.				LOGGED BY				D. ANDERSON																																																													
SECTION		24, 31, 32		LOCATION		SEC. TWP. RNG.																																																																			
COUNTY		McDon. & Hancock		CORING METHOD																																																																					
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td rowspan="2">STRUCT. NO. Station</td> <td rowspan="2">CORING BARREL TYPE & SIZE NX</td> <td rowspan="2">D E P T H</td> <td rowspan="2">C O R E</td> <td rowspan="2">R E C O R D</td> <td rowspan="2">Q U E R Y</td> <td rowspan="2">CORE T I E M E N G T H</td> <td rowspan="2">S T R E T I N G</td> <td colspan="8"></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>BORING NO. Station Offset Ground Surface Elev.</td> <td>Core Diameter Top of Rock Elev. Begin Core Elev.</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>																STRUCT. NO. Station	CORING BARREL TYPE & SIZE NX	D E P T H	C O R E	R E C O R D	Q U E R Y	CORE T I E M E N G T H	S T R E T I N G																			BORING NO. Station Offset Ground Surface Elev.	Core Diameter Top of Rock Elev. Begin Core Elev.																														
STRUCT. NO. Station	CORING BARREL TYPE & SIZE NX	D E P T H	C O R E	R E C O R D	Q U E R Y	CORE T I E M E N G T H	S T R E T I N G																																																																		
BORING NO. Station Offset Ground Surface Elev.	Core Diameter Top of Rock Elev. Begin Core Elev.																																																																								
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td colspan="2">GR LIMESTONE</td> <td colspan="2">502.90</td> <td></td> <td>86</td> <td>45</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="2">End of Boring</td> <td colspan="2">491.90</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>																GR LIMESTONE		502.90			86	45										End of Boring		491.90																																							
GR LIMESTONE		502.90			86	45																																																																			
End of Boring		491.90																																																																							

Color pictures of the cores
Cores will be stored for examination until
The "Strength" column represents the uniaxial compressive strength of the core sample (ASTM D-2888)

BBS, form 138 (Rev. 8-99)

DESIGNED	KLH
CHECKED	FMI
DRAWN	KBF
CHECKED	KPH



BORING LOGS
ILLINOIS ROUTE 336 OVER
EAST FORK OF THE LAMOINE RIVER
F.A.P. ROUTE 315 - SECTION 34-6, 55-1
HANCOCK COUNTY; STA. 1432+02.61
STRUCTURE NO. 034-0511 (E.B.)
STRUCTURE NO. 034-0512 (W.B.)