

NAME: DENNIS L. KILBANE
DATE: _____
DRAWN BY: D.L.K.
FIELD CHECK: D.L.K.
APPROVED BY: _____
NO. 062-049333
EXPIRES 11-30-07

SHEET NO. 22 of 23

FILE: 0003/PLANS/SHEETS/ROAD
PROJECT: GARBFIELD AVENUE PAYMENT REHABILITATION
DRAWN BY: D.L.K.
FIELD CHECK: D.L.K.
APPROVED BY: _____

PROJECT: GREEN TREE PARKWAY TO W. ROCKLAND ROAD
DISTRICT ONE TYPICAL PAVEMENT MARKINGS
PROJECT NO. 0503
DATE OF ISSUE: 07/13/06

REVISIONS: _____
DATE: _____
BY: _____
AS BUILT: _____
BY: _____

VILLAGE OF LIBERTYVILLE
118 West Cook Avenue
Libertyville, Illinois 60048
(847) 362-2430

TYPICAL LANE AND EDGE LINE MARKING

NOTE: MEDIANS WITH BARRIER CURB DO NOT REQUIRE AN EDGE LINE

TYPICAL CROSSWALK MARKING

TYPICAL TURN LANE MARKING

TYPICAL PAINTED MEDIAN MARKING

TYPICAL ISLAND MARKING

TYPE OF MARKING	WIDTH OF LINE	PATTERN	COLOR	SPACING / REMARKS
CENTERLINE ON 2 LANE PAVEMENT	100 (4)	SKIP-DASH	YELLOW	3 m (10') LINE WITH 9 m (30') SPACE
CENTERLINE ON MULTI-LANE UNDIVIDED PAVEMENT	2 @ 100 (4)	SOLID	YELLOW	280 (11) C-C
NO PASSING ZONE LINES FOR ONE DIRECTION FOR BOTH DIRECTIONS	100 (4) 2 @ 100 (4)	SOLID SOLID	YELLOW YELLOW	140 (5 1/2) C-C FROM SKIP-DASH CENTERLINE 280 (11) C-C OMIT SKIP-DASH CENTERLINE BETWEEN
LANE LINES	100 (4) 125 (5) ON FREEWAYS	SKIP-DASH SKIP-DASH	WHITE WHITE	3 m (10') LINE WITH 9 m (30') SPACE
DOTTED LINES (EXTENSIONS OF CENTER LANE OR TURN LANE MARKINGS)	SAME AS LINE BEING EXTENDED	SKIP-DASH	WHITE	600 (21) LINE WITH 18 m (60') SPACE
EDGE LINES	100 (4)	SOLID	YELLOW-LEFT WHITE-RIGHT	OUTLINE MOUNTABLE MEDIANS IN YELLOW. EDGE LINES ARE NOT USED NEXT TO BARRIER CURB
TURN LANE MARKINGS	150 (6) LINE FULL SIZE LETTERS & SYMBOLS (2.4 m (8")	SOLID	WHITE	SEE TYPICAL TURN LANE MARKING DETAIL
TWO WAY LEFT TURN MARKING	2 @ 100 (4) EACH DIRECTION 2.4 m (8') LEFT ARROW	SKIP-DASH AND SOLID IN PAIRS	YELLOW WHITE	3 m (10') LINE WITH 9 m (30') SPACE FOR SKIP-DASH 140 (5 1/2) C-C BETWEEN SOLID LINE AND SKIP-DASH LINE SEE TYPICAL TWO-WAY LEFT TURN MARKING DETAIL
CROSSWALK LINES (PEDESTRIAN & BICYCLE) A. DIAGONALS (BIKE & PEDESTRIAN) B. LONGITUDINAL BARS (SCHOOL)	2 @ 150 (6) 300 (12) @ 45° 300 (12) @ 90°	SOLID SOLID SOLID	WHITE WHITE WHITE	NOT LESS THAN 1.8 m (6') APART 600 (21) APART 600 (21) APART SEE TYPICAL CROSSWALK MARKING DETAILS.
STOP LINES	600 (24)	SOLID	WHITE	PLACE 1.8 m (6') IN ADVANCE OF AND PARALLEL TO CROSSWALK. IF PRESENT OTHERWISE, PLACE AT DESIRED STOPPING POINT, PARALLEL TO CROSSWALK CENTERLINE, WHERE POSSIBLE
PAINTED MEDIANS	2 @ 100 (4) WITH 300 (12) DIAGONALS @ 45° NO DIAGONALS USED FOR 1.2 m (4') WIDE MEDIANS	SOLID	YELLOW WHITE WHITE	280 (11) C-C FOR THE DOUBLE LINE SEE TYPICAL PAINTED MEDIAN MARKING.
EDGE MARKING AND CHANNELIZING LINES	200 (8) WITH 500 (12) DIAGONALS @ 45°	SOLID	WHITE	DIAGONALS: 4.5 m (15') C-C (LESS THAN 50 km/h (30 MPH) 6 m (20') C-C (50 km/h (30 MPH) TO 70 km/h (45 MPH) 9 m (30') C-C (OVER 70 km/h (45 MPH))
RAILROAD CROSSING	600 (24) TRANSVERSE LINES "R" 15 L & 18" LETTERS: 400 (16) LINE FOR "X"	SOLID	WHITE	SEE STATE STANDARD T8000L AREA (FT.) "X"=5.0 m ² (54.0 SQ. FT.)
SHOULDER DIAGONALS	300 (12) @ 45°	SOLID	WHITE - RIGHT YELLOW - LEFT	15 m (50') C-C (LESS THAN 50 km/h (30 MPH) 25 m (75') C-C (50 km/h (30 MPH) TO 70 km/h (45 MPH) 45 m (150') C-C (OVER 70 km/h (45 MPH))

FOR FURTHER DETAILS ON PAVEMENT MARKING REFER TO STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION ADOPTED JANUARY 1, 1997 AND STATE STANDARD T8000L

ALL DIMENSIONS ARE IN MILLIMETERS (BRACKET) UNLESS OTHERWISE SHOWN.

ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT ONE
TYPICAL PAVEMENT MARKINGS

REVISIONS	DATE
EVERS	03-19-90
T. RAMMACHER	10-27-94
ALEX HOUSE	10-09-96
T. RAMMACHER	10-17-96
T. RAMMACHER	01-06-00

SCALE: NONE
DATE: 10/11/01
DRAWN BY: CAD
CHECKED BY: _____
TC-13

Thu Oct 11 14:34:58 2001
C:\msd\projects\ctd\std\vol3.dgn LV:35
V1:123