

# GENERAL NOTES

ROUTE NO.	SEC.	COUNTY	TOTAL SHEETS	SHEET NO.
FAP 203	13BR-1	Whiteside	26	3A
FED ROAD DIST. NO.	ILLINOIS	PROJECT		
Contract #64A51				

A quantity of 160 Ton Sub Granular Material B and 100 Ton Bituminous Concrete Surface Course, N50 has been included to be used to maintain Hillside Road, Hill Road, and Smit Road as determined by the Resident Engineer. Included within this pay item shall be the spreading of the material and compaction to the satisfaction of the Resident Engineer.

A quantity of Calcium Chloride applied has been included in the contract to be applied as needed to control dust. The Resident Engineer shall determine quantity as needed.

Fenton Township Commissioner and Whiteside County Engineer shall be informed 1 week prior to the construction beginning. Above listed shall be invited to the pre-construction meeting.

The Resident Engineer, prior to closing the road and after the project is finished, shall contact the corresponding Townships of Fenton and Whiteside County to videotape the following roads: Hillside, Hill & Smit Roads.

The following Mixture Requirements are applicable for this project:

Mixture Uses(s):	Mainline Surface Course		
PG:	PG 64-22		
RAP%: (Max)	10%		
Design Air Voids	4.2 @ N50		
Mixture Composition (Gradation Mixture)	IL 9.5 or 12.5		
Friction Aggregate	C		
20 Year ESAL	4.3		

All dimensions shown are in feet unless otherwise noted. Pavement thickness and marking widths are shown in inches unless noted.

The contractor will not be allowed to set up a yard or field office on state property without written permission from the Department.

The removal and re-erection of existing steel plate beam guardrail shall be performed according to the applicable portions of Section 633 of the Standard Specifications.

If, during the completion of this project, the existing mail boxes become a hindrance, the contractor shall be required to carefully remove and reinstall the mail boxes as directed by the engineer at no additional cost to the Department.

The excavated materials from earth excavation, widening, grading and shaping ditches, and excavating and grading shoulders shall be used to build up the shoulders throughout the job to conform with the typical section and shoulder widening for terminals as shown on the plans. No excavated materials shall be disposed of without consent from the Resident Engineer.

A quantity of 30 cubic yards of Furnished Excavation has been included to further build up the shoulders, if the engineer determines that the excavated materials from the job are insufficient to bring the shoulders to the proper slope.

Program #6  
(Arch. Size)  
Enlarge  
200%  
Enlarge 107%