

J:\2009\246 IDOT PTB I53 Item 21\Cadd\Design\016-1101\W.O.15 Oriole SteelPlans\016-1101.dgn 2/12/2011 2:42:33 PM

GIRDER 1

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back S. Abut.	7+06.37	-27.42	656.16	656.16
☉ Brg. S. Abut.	7+09.87	-27.42	656.24	656.24
A	7+19.87	-27.42	656.43	656.48
B	7+29.87	-27.42	656.62	656.70
C	7+39.87	-27.42	656.78	656.89
D	7+49.87	-27.42	656.94	657.06
E	7+59.87	-27.42	657.08	657.19
F	7+69.87	-27.42	657.20	657.29
G	7+79.87	-27.42	657.31	657.32
H	7+89.87	-27.42	657.40	657.43
I	7+99.87	-27.42	657.48	657.49
☉ Pier 2	8+08.87	-27.42	657.54	657.54
J	8+18.87	-27.42	657.59	657.59
K	8+28.87	-27.42	657.62	657.65
L	8+38.87	-27.42	657.65	657.70
M	8+48.87	-27.42	657.65	657.73
N	8+58.87	-27.42	657.64	657.73
O	8+68.87	-27.42	657.62	657.72
P	8+78.87	-27.42	657.58	657.67
Q	8+88.87	-27.42	657.53	657.59
R	8+98.87	-27.42	657.46	657.49
☉ Brg. N. Abut.	9+05.37	-27.42	657.41	657.41
Back N. Abut.	9+08.87	-27.42	657.38	657.38

☉ ORIOLE AVENUE & PROFILE GRADE

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back S. Abut.	6+97.50	0.00	656.29	656.29
☉ Brg. S. Abut.	7+01.00	0.00	656.37	656.37
A	7+11.00	0.00	656.58	656.62
B	7+21.00	0.00	656.77	656.85
C	7+31.00	0.00	656.95	657.14
D	7+41.00	0.00	657.12	657.22
E	7+51.00	0.00	657.27	657.37
F	7+61.00	0.00	657.41	657.49
G	7+71.00	0.00	657.53	657.56
H	7+81.00	0.00	657.63	657.66
I	7+91.00	0.00	657.73	657.74
☉ Pier 2	8+00.00	0.00	657.80	657.80
J	8+10.00	0.00	657.86	657.87
K	8+20.00	0.00	657.91	657.93
L	8+30.00	0.00	657.94	657.99
M	8+40.00	0.00	657.96	658.03
N	8+50.00	0.00	657.97	658.05
O	8+60.00	0.00	657.96	658.04
P	8+70.00	0.00	657.93	658.01
Q	8+80.00	0.00	657.89	657.95
R	8+90.00	0.00	657.84	657.86
☉ Brg. N. Abut.	8+96.50	0.00	657.80	657.80
Back N. Abut.	9+00.00	0.00	657.77	657.77

GIRDER 8

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back S. Abut.	6+88.63	27.42	655.77	655.77
☉ Brg. S. Abut.	6+92.13	27.42	655.85	655.85
A	7+02.13	27.42	656.07	656.12
B	7+12.13	27.42	656.28	656.37
C	7+22.13	27.42	656.48	656.59
D	7+32.13	27.42	656.66	656.78
E	7+42.13	27.42	656.82	656.93
F	7+52.13	27.42	656.97	657.06
G	7+62.13	27.42	657.10	657.11
H	7+72.13	27.42	657.22	657.26
I	7+82.13	27.42	657.33	657.34
☉ Pier 2	7+91.13	27.42	657.41	657.41
J	8+01.13	27.42	657.49	657.49
K	8+11.13	27.42	657.55	657.58
L	8+21.13	27.42	657.60	657.65
M	8+31.13	27.42	657.63	657.70
N	8+41.13	27.42	657.65	657.74
O	8+51.13	27.42	657.65	657.75
P	8+61.13	27.42	657.64	657.73
Q	8+71.13	27.42	657.61	657.67
R	8+81.13	27.42	657.57	657.60
☉ Brg. N. Abut.	8+87.63	27.42	657.54	657.54
Back N. Abut.	8+91.13	27.42	657.51	657.51

GIRDER 2

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back S. Abut.	7+03.84	-19.58	656.10	656.10
☉ Brg. S. Abut.	7+07.34	-19.58	656.17	656.17
A	7+17.34	-19.58	656.37	656.41
B	7+27.34	-19.58	656.56	656.63
C	7+37.34	-19.58	656.73	656.92
D	7+47.34	-19.58	656.89	656.99
E	7+57.34	-19.58	657.03	657.13
F	7+67.34	-19.58	657.15	657.23
G	7+77.34	-19.58	657.27	657.30
H	7+87.34	-19.58	657.36	657.39
I	7+97.34	-19.58	657.45	657.45
☉ Pier 2	8+06.34	-19.58	657.51	657.51
J	8+16.34	-19.58	657.56	657.57
K	8+26.34	-19.58	657.60	657.62
L	8+36.34	-19.58	657.63	657.67
M	8+46.34	-19.58	657.64	657.70
N	8+56.34	-19.58	657.63	657.71
O	8+66.34	-19.58	657.61	657.70
P	8+76.34	-19.58	657.58	657.65
Q	8+86.34	-19.58	657.53	657.58
R	8+96.34	-19.58	657.47	657.49
☉ Brg. N. Abut.	9+02.84	-19.58	657.42	657.42
Back N. Abut.	9+06.34	-19.58	657.39	657.39

GIRDER 5

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back S. Abut.	6+96.23	3.92	656.20	656.20
☉ Brg. S. Abut.	6+99.73	3.92	656.28	656.28
A	7+09.73	3.92	656.49	656.53
B	7+19.73	3.92	656.69	656.77
C	7+29.73	3.92	656.87	657.06
D	7+39.73	3.92	657.04	657.15
E	7+49.73	3.92	657.19	657.29
F	7+59.73	3.92	657.33	657.41
G	7+69.73	3.92	657.45	657.49
H	7+79.73	3.92	657.56	657.59
I	7+89.73	3.92	657.66	657.67
☉ Pier 2	7+98.73	3.92	657.73	657.73
J	8+08.73	3.92	657.79	657.80
K	8+18.73	3.92	657.85	657.87
L	8+28.73	3.92	657.88	657.93
M	8+38.73	3.92	657.90	657.97
N	8+48.73	3.92	657.91	657.99
O	8+58.73	3.92	657.90	657.99
P	8+68.73	3.92	657.88	657.95
Q	8+78.73	3.92	657.84	657.90
R	8+88.73	3.92	657.79	657.81
☉ Brg. N. Abut.	8+95.23	3.92	657.75	657.75
Back N. Abut.	8+98.73	3.92	657.72	657.72

GIRDER 3

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back S. Abut.	7+01.30	-11.75	656.20	656.20
☉ Brg. S. Abut.	7+04.80	-11.75	656.27	656.27
A	7+14.80	-11.75	656.48	656.52
B	7+24.80	-11.75	656.67	656.74
C	7+34.80	-11.75	656.84	657.03
D	7+44.80	-11.75	657.00	657.11
E	7+54.80	-11.75	657.15	657.25
F	7+64.80	-11.75	657.28	657.36
G	7+74.80	-11.75	657.39	657.43
H	7+84.80	-11.75	657.50	657.52
I	7+94.80	-11.75	657.58	657.59
☉ Pier 2	8+03.80	-11.75	657.65	657.65
J	8+13.80	-11.75	657.70	657.71
K	8+23.80	-11.75	657.75	657.77
L	8+33.80	-11.75	657.78	657.82
M	8+43.80	-11.75	657.79	657.86
N	8+53.80	-11.75	657.79	657.87
O	8+63.80	-11.75	657.77	657.86
P	8+73.80	-11.75	657.74	657.82
Q	8+83.80	-11.75	657.70	657.75
R	8+93.80	-11.75	657.64	657.66
☉ Brg. N. Abut.	9+00.30	-11.75	657.59	657.59
Back N. Abut.	9+03.80	-11.75	657.56	657.56

GIRDER 6

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back S. Abut.	6+93.70	11.75	656.03	656.03
☉ Brg. S. Abut.	6+97.20	11.75	656.11	656.11
A	7+07.20	11.75	656.32	656.36
B	7+17.20	11.75	656.52	656.60
C	7+27.20	11.75	656.71	656.90
D	7+37.20	11.75	656.88	656.99
E	7+47.20	11.75	657.04	657.14
F	7+57.20	11.75	657.18	657.26
G	7+67.20	11.75	657.31	657.34
H	7+77.20	11.75	657.42	657.45
I	7+87.20	11.75	657.52	657.53
☉ Pier 2	7+96.20	11.75	657.59	657.59
J	8+06.20	11.75	657.66	657.67
K	8+16.20	11.75	657.72	657.74
L	8+26.20	11.75	657.76	657.80
M	8+36.20	11.75	657.78	657.85
N	8+46.20	11.75	657.79	657.87
O	8+56.20	11.75	657.79	657.87
P	8+66.20	11.75	657.77	657.84
Q	8+76.20	11.75	657.73	657.79
R	8+86.20	11.75	657.69	657.71
☉ Brg. N. Abut.	8+92.70	11.75	657.65	657.65
Back N. Abut.	8+96.20	11.75	657.62	657.62

GIRDER 4

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back S. Abut.	6+98.77	-3.92	656.26	656.26
☉ Brg. S. Abut.	7+02.27	-3.92	656.34	656.34
A	7+12.27	-3.92	656.54	656.59
B	7+22.27	-3.92	656.74	656.81
C	7+32.27	-3.92	656.92	657.10
D	7+42.27	-3.92	657.08	657.19
E	7+52.27	-3.92	657.23	657.33
F	7+62.27	-3.92	657.36	657.44
G	7+72.27	-3.92	657.48	657.52
H	7+82.27	-3.92	657.59	657.62
I	7+92.27	-3.92	657.68	657.69
☉ Pier 2	8+01.27	-3.92	657.75	657.75
J	8+11.27	-3.92	657.81	657.81
K	8+21.27	-3.92	657.86	657.88
L	8+31.27	-3.92	657.89	657.93
M	8+41.27	-3.92	657.91	657.97
N	8+51.27	-3.92	657.91	657.99
O	8+61.27	-3.92	657.90	657.98
P	8+71.27	-3.92	657.87	657.95
Q	8+81.27	-3.92	657.83	657.88
R	8+91.27	-3.92	657.77	657.80
☉ Brg. N. Abut.	8+97.77	-3.92	657.73	657.73
Back N. Abut.	9+01.27	-3.92	657.70	657.70

GIRDER 7

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back S. Abut.	6+91.16	19.58	655.81	655.81
☉ Brg. S. Abut.	6+94.66	19.58	655.89	655.89
A	7+04.66	19.58	656.11	656.16
B	7+14.66	19.58	656.32	656.39
C	7+24.66	19.58	656.51	656.70
D	7+34.66	19.58	656.68	656.79
E	7+44.66	19.58	656.84	656.94
F	7+54.66	19.58	656.99	657.07
G	7+64.66	19.58	657.12	657.15
H	7+74.66	19.58	657.24	657.27
I	7+84.66	19.58	657.34	657.35
☉ Pier 2	7+93.66	19.58	657.42	657.42
J	8+03.66	19.58	657.49	657.50
K	8+13.66	19.58	657.55	657.57
L	8+			