



To determine "f": After all structural steel has been erected, elevations of the top flanges of the beams shall be taken at intervals shown below. These elevations subtracted from the "Theoretical Grade Elevations Adjusted for Dead Load Deflection" shown on Sht's. S4 thru S6, minus slab thickness, equals the fillet heights "f" above top flange of beams.

Note:
The above deflections are not to be used in the field if the Engineer is working from the grade elevations adjusted for dead load deflections as shown on Sht's. S4 thru S6.

FILE NAME = I:\1023099_Central_Ave_Structural\CHOD Sheets\10160P17-03-deck.slv.dgn

	USER NAME = IDOT	DESIGNED - J.C.N./B.N.S.	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	TOP OF SLAB ELEVATIONS-I STRUCTURE NO. 016-2458	F.A.I. RTE. 80	SECTION 1415-803HB-R	COUNTY COOK	TOTAL SHEETS 51	SHEET NO. 18
	PLOT SCALE = 50,000/000 1" = 50'	CHECKED - B.N.S.	REVISED -			CONTRACT NO. 60P17				
	PLOT DATE = 11/17/2011	DRAWN - F.M.	REVISED -			ILLINOIS FED. AID PROJECT				
	DATE - NOVEMBER 17, 2011	REVISED -								