

BEAM 7

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. W. ABUT.	13+77.84	15.17	758.05	758.05
℄. BRG. W. ABUT.	13+81.16	15.17	758.00	758.00
A	13+91.16	15.17	757.86	757.94
B	14+01.16	15.17	757.71	757.87
C	14+11.16	15.17	757.56	757.78
D	14+21.16	15.17	757.40	757.67
E	14+31.16	15.17	757.23	757.54
F	14+41.16	15.17	757.06	757.39
G	14+51.16	15.17	756.88	757.21
H	14+61.16	15.17	756.70	757.01
I	14+71.16	15.17	756.50	756.78
J	14+81.16	15.17	756.31	756.53
K	14+91.16	15.17	756.10	756.26
L	15+01.16	15.17	755.89	755.98
℄. BRG. E. ABUT.	15+11.91	15.17	755.66	755.66
BK. E. ABUT.	15+15.23	15.17	755.59	755.59

BEAM 8

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. W. ABUT.	13+79.43	22.92	757.87	757.87
℄. BRG. W. ABUT.	13+82.75	22.92	757.82	757.82
A	13+92.75	22.92	757.68	757.75
B	14+02.75	22.92	757.53	757.68
C	14+12.75	22.92	757.37	757.59
D	14+22.75	22.92	757.21	757.48
E	14+32.75	22.92	757.04	757.35
F	14+42.75	22.92	756.87	757.20
G	14+52.75	22.92	756.69	757.02
H	14+62.75	22.92	756.50	756.82
I	14+72.75	22.92	756.31	756.59
J	14+82.75	22.92	756.11	756.34
K	14+92.75	22.92	755.91	756.07
L	15+02.75	22.92	755.70	755.78
℄. BRG. E. ABUT.	15+13.50	22.92	755.47	755.47
BK. E. ABUT.	15+16.82	22.92	755.39	755.39

BEAM 9

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. W. ABUT.	13+81.03	30.67	757.68	757.68
℄. BRG. W. ABUT.	13+84.35	30.67	757.64	757.64
A	13+94.35	30.67	757.49	757.57
B	14+04.35	30.67	757.34	757.49
C	14+14.35	30.67	757.19	757.40
D	14+24.35	30.67	757.02	757.30
E	14+34.35	30.67	756.85	757.17
F	14+44.35	30.67	756.68	757.01
G	14+54.35	30.67	756.50	756.83
H	14+64.35	30.67	756.31	756.63
I	14+74.35	30.67	756.12	756.40
J	14+84.35	30.67	755.92	756.14
K	14+94.35	30.67	755.72	755.87
L	15+04.35	30.67	755.50	755.59
℄. BRG. E. ABUT.	15+15.10	30.67	755.27	755.27
BK. E. ABUT.	15+18.42	30.67	755.20	755.20

BEAM 10

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. W. ABUT.	13+82.62	38.42	757.72	757.72
℄. BRG. W. ABUT.	13+85.94	38.42	757.68	757.68
A	13+95.94	38.42	757.53	757.61
B	14+05.94	38.42	757.38	757.53
C	14+15.94	38.42	757.22	757.44
D	14+25.94	38.42	757.06	757.33
E	14+35.94	38.42	756.89	757.20
F	14+45.94	38.42	756.72	757.05
G	14+55.94	38.42	756.53	756.87
H	14+65.94	38.42	756.35	756.66
I	14+75.94	38.42	756.15	756.43
J	14+85.94	38.42	755.95	756.18
K	14+95.94	38.42	755.75	755.90
L	15+05.94	38.42	755.53	755.62
℄. BRG. E. ABUT.	15+16.69	38.42	755.30	755.30
BK. E. ABUT.	15+20.01	38.42	755.22	755.22

BEAM 11

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. W. ABUT.	13+84.21	46.17	757.86	757.86
℄. BRG. W. ABUT.	13+87.53	46.17	757.82	757.82
A	13+97.53	46.17	757.67	757.75
B	14+07.53	46.17	757.52	757.67
C	14+17.53	46.17	757.36	757.58
D	14+27.53	46.17	757.20	757.47
E	14+37.53	46.17	757.03	757.34
F	14+47.53	46.17	756.85	757.18
G	14+57.53	46.17	756.67	757.00
H	14+67.53	46.17	756.48	756.79
I	14+77.53	46.17	756.28	756.56
J	14+87.53	46.17	756.08	756.30
K	14+97.53	46.17	755.87	756.03
L	15+07.53	46.17	755.66	755.74
℄. BRG. E. ABUT.	15+18.28	46.17	755.42	755.42
BK. E. ABUT.	15+21.60	46.17	755.35	755.35



FILE NAME =	USER NAME =	DESIGNED - LRT / AG	REVISED -
		CHECKED - DAO / LRT	REVISED -
	PLOT SCALE = N.T.S.	DRAWN - TCS / AG	REVISED -
	PLOT DATE = 09/01/2011	CHECKED - AG	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

TOP OF SLAB ELEVATIONS SHEET 3 OF 3
STRUCTURE NO. 049-0534

SHEET NO. OF SHEETS

FOR INFORMATION ONLY

F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
1199	2011-056-F	LAKE	19	16
ILLINOIS FED. AID PROJECT			CONTRACT NO. 60P69	