

PORTLAND CEMENT CONCRETE
SIDEWALK, 5 INCH

LOCATION	QUANTITY
STATION	(SQ FT)
98+41 TO 99+76 RT	690
100+66 TO 102+23 RT	775
98+00 TO 99+64 LT	815
100+24 TO 101+00 LT	380
TOTAL	2660

DETECTABLE WARNINGS

LOCATION	QUANTITY
STATION	OFFSET (SQ FT)
98+45	RT 15
TOTAL	15

PAVEMENT REMOVAL

LOCATION	QUANTITY
STATION	(SQ YD)
97+76.50 TO 99+45.25	1196
100+58.09 TO 102+22.50	1166
TOTAL	2362

HOT-MIX ASPHALT SURFACE REMOVAL, 2"

LOCATION	QUANTITY
STATION	(SQ YD)
102+22.50 TO 102+72.44	342
TOTAL	342

DRIVEWAY PAVEMENT REMOVAL

LOCATION	QUANTITY
STATION	(SQ. YD.)
COMMERCIAL ENTRANCE	58
98+05.15 TO 98+52.69	
TOTAL	58

COMBINATION CURB AND
GUTTER REMOVAL

LOCATION	QUANTITY
STATION	OFFSET (FOOT)
97+76.50 TO 99+39.94	LT 164
97+76.50 TO 99+45.45	RT 169
100+24.98 TO 102+22.50	LT 198
100+61.74 TO 102+22.50	RT 161
TOTAL	692

SIDEWALK REMOVAL

LOCATION	QUANTITY
STATION	OFFSET (SQ FT)
98+41 TO 99+76	RT 643
100+37 TO 102+23	RT 903
98+00 TO 99+62	LT 778
100+24 TO 101+00	LT 363
TOTAL	2687

APPROACH SLAB REMOVAL

LOCATION	QUANTITY
STATION	(SQ YD)
99+40.21 TO 99+70.95	183
100+28.89 TO 100+61.18	191
TOTAL	374

MEDIAN REMOVAL

LOCATION	QUANTITY
STATION	(SQ FT)
99+45.29 TO 99+70.95	344
100+28.89 TO 100+61.18	374
101+92.32 TO 102+74.75	228
TOTAL	946

HOT-MIX ASPHALT SHOULDERS, 6"

LOCATION	QUANTITY
STATION	OFFSET (SQ. YD.)
98+47 TO 99+75	RT 27
94+95 TO 98+00	LT 98
100+37 TO 102+01	RT 37
101+00 TO 102+73	LT 53
TOTAL	215

STORM SEWERS, CLASS A, TYPE 2, 24"

LOCATION	QUANTITY
STATION	OFFSET (FOOT)
99+38 TO 99+68	LT 30
TOTAL	30

STORM SEWER REMOVAL 24"

LOCATION	QUANTITY
STATION	OFFSET (FOOT)
99+38 TO 99+68	LT 30
TOTAL	30

FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)

LOCATION	QUANTITY
STATION	OFFSET (EACH)
98+06.78	17.3 RT 1
98+07.03	17.7 LT 1
98+14.43	0.4 RT 1
98+56.72	33.4 RT 1
98+69.31	47.3 RT 1
98+79.15	32.6 LT 1
99+33.96	19.1 RT 1
99+38.03	18.5 LT 1
100+64.26	34.0 RT 1
100+68.39	0.5 RT 1
100+69.00	34.8 LT 1
101+93.34	33.4 LT 1
101+94.54	33.5 RT 1
102+07.00	37.8 LT 1
TOTAL	14

COMBINATION CONCRETE CURB
AND GUTTER, TYPE B-6.24

LOCATION	QUANTITY
STATION	OFFSET (FOOT)
97+76.43 TO 99+44.66	RT 168
97+76.58 TO 98+00.00	LT 23
100+66.11 TO 102+22.48	RT 156
101+00.00 TO 102+22.52	LT 123
TOTAL	470

STEEL PLATE BEAM GUARD RAIL, TYPE A, 6 FOOT POSTS

LOCATION	QUANTITY
STATION	OFFSET (FOOT)
95+69.59 TO 97+56.85	LT 187.5
99+04.16 TO 99+16.66	RT 12.5
101+09.80 TO 101+22.30	RT 12.5
101+43.15 TO 101+93.05	LT 50.0
TOTAL	262.5