



- PAVEMENT MARKING KEY**
- 1 4" SOLID - WHITE
  - 2 12" SOLID - YELLOW
  - 3 4" SOLID - YELLOW @ 11" C-C
  - 4 24" STOP BAR - WHITE
  - 5 12" SOLID - WHITE
  - 6 6" SOLID - WHITE
  - 7 6"-6'/2" DASH-WHITE
  - 8 4" SOLID - YELLOW
  - 9 4" 30"/10" DASH WHITE

**TEMPORARY CONCRETE BARRIER LAYOUT (TO FF)**

| LOCATION | STATION   | OFFSET    |
|----------|-----------|-----------|
| E        | 180+31.77 | 1.41' LT  |
| F        | 181+07.37 | 9.23' LT  |
| G        | 181+96.03 | 11.00' LT |
| H        | 183+85.87 | 11.00' LT |
| I        | 184+36.36 | 6.79' LT  |

- LEGEND**
- ARROW BOARD
  - ▨ TEMPORARY PAVEMENT
  - ▨ TEMPORARY PAVEMENT CONSTRUCTED IN EARLIER STAGE
  - ▨ CONSTRUCTION ZONE
  - ⊥ TYPE III BARRICADE WITH FLASHING LIGHTS
  - ⊥ TYPE II BARRICADE
  - ⊥ DRUM OR VERTICAL BARRICADE
  - DIRECTION INDICATOR BARRICADE WITH STEADY BURN MONODIRECTIONAL LIGHT
  - ⊥ FL FLASHING LIGHT

**REVISIONS**

| NAME | DATE |
|------|------|
|      |      |
|      |      |
|      |      |
|      |      |
|      |      |

ILLINOIS DEPARTMENT OF TRANSPORTATION  
**MAINTENANCE OF TRAFFIC**  
 PRE-STAGE 2  
 U.S. RTE. 30 (LINCOLN HIGHWAY)  
 STA. 174+00 TO STA. 202+00  
 SCALE : 1" = 50'  
 DATE : / / DRAWN BY : BAE  
 CHECKED BY : GB