



**PAVEMENT MARKING KEY**

- 1 4" SOLID - WHITE
- 2 12" SOLID - YELLOW
- 3 4" SOLID - YELLOW @ 11" c-c
- 4 24" STOP BAR - WHITE
- 5 12" SOLID - WHITE
- 6 6" SOLID - WHITE
- 7 6"-6 1/2" DASH-WHITE
- 8 4" SOLID - YELLOW
- 9 4" 30'/10' DASH WHITE

**TEMPORARY CONCRETE BARRIER LAYOUT (TO FF)**

LOCATION	STATION	OFFSET
J	254+68.94	51.00' LT
K	257+47.44	51.00' LT
L	257+72.01	57.14' LT
M	255+05.45	7.92' LT
N	255+55.79	12.13' LT
O	257+45.33	12.14' LT
P	257+69.74	6.04' LT

- LEGEND**
- ARROW BOARD
  - TEMPORARY PAVEMENT
  - TEMPORARY PAVEMENT CONSTRUCTED IN EARLIER STAGE
  - CONSTRUCTION ZONE
  - TYPE III BARRICADE WITH FLASHING LIGHTS
  - TYPE II BARRICADE
  - DRUM OR VERTICAL BARRICADE
  - DIRECTION INDICATOR BARRICADE WITH STEADY BURN MONODIRECTIONAL LIGHT
  - FLASHING LIGHT

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION  
**MAINTENANCE OF TRAFFIC**  
 PRE-STAGE 2  
 U.S. RTE. 30 (LINCOLN HIGHWAY)  
 STA. 230+00 TO STA. 260+00  
 SCALE : 1" = 50'  
 DATE : / /  
 DRAWN BY : BAE  
 CHECKED BY : GB