

**GIRDER 1**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	84+20.71	-26.38	614.06	614.06
C/L Brg. N. Abut.	84+23.00	-26.38	614.19	614.19
A1	84+33.00	-26.38	614.76	614.81
B1	84+43.00	-26.38	615.34	615.43
C1	84+53.00	-26.38	615.92	616.04
D1	84+63.00	-26.38	616.50	616.64
E1	84+73.00	-26.38	617.07	617.22
F1	84+83.00	-26.38	617.65	617.79
G1	84+93.00	-26.38	618.23	618.35
H1	85+03.00	-26.38	618.80	618.91
I1	85+17.58	-26.38	619.65	619.68
J1	85+27.58	-26.38	620.22	620.24
K1	85+37.58	-26.38	620.80	620.80
C/L Pier 1	85+43.83	-26.38	621.16	621.16
A2	85+53.83	-26.38	621.74	621.74
B2	85+63.83	-26.38	622.31	622.33
C2	85+73.83	-26.38	622.89	622.93
D2	85+83.83	-26.38	623.47	623.52
E2	85+93.83	-26.38	624.04	624.12
F2	86+03.83	-26.38	624.62	624.70
G2	86+13.83	-26.38	625.20	625.28
H2	86+23.83	-26.38	625.78	625.85
I2	86+33.83	-26.38	626.35	626.41
J2	86+43.83	-26.38	626.93	626.97
K2	86+53.83	-26.38	627.51	627.52
L2	86+63.83	-26.38	628.08	628.09
C/L Pier 2	86+75.21	-26.38	628.74	628.74
A3	86+85.21	-26.38	629.32	629.32
B3	86+95.21	-26.38	629.89	629.92
C3	87+05.21	-26.38	630.47	630.52
D3	87+15.21	-26.38	631.05	631.12
E3	87+25.21	-26.38	631.63	631.72
F3	87+35.21	-26.38	632.20	632.31
G3	87+45.21	-26.38	632.78	632.89
H3	87+55.21	-26.38	633.36	633.46
I3	87+65.21	-26.38	633.93	634.02
J3	87+75.21	-26.38	634.51	634.57
K3	87+85.21	-26.38	635.09	635.12
L3	87+95.21	-26.38	635.66	635.67
C/L Pier 3	88+01.80	-26.38	636.04	636.04
A4	88+11.80	-26.38	636.62	636.61
B4	88+21.80	-26.38	637.20	637.19
C4	88+28.05	-26.38	637.56	637.55
D4	88+38.05	-26.38	638.14	638.15
E4	88+48.05	-26.38	638.71	638.74
F4	88+58.05	-26.38	639.29	639.32
G4	88+68.05	-26.38	639.87	639.90
H4	88+78.05	-26.38	640.44	640.47
I4	88+88.05	-26.38	641.02	641.04
J4	88+98.05	-26.38	641.60	641.60
C/L Pier 4	89+08.80	-26.38	642.22	642.22
A5	89+18.80	-26.38	642.80	642.80
B5	89+28.80	-26.38	643.37	643.39
C5	89+38.80	-26.38	643.95	643.97
D5	89+48.80	-26.38	644.53	644.56
E5	89+58.80	-26.38	645.10	645.14
F5	89+68.80	-26.38	645.68	645.71
G5	89+78.80	-26.38	646.26	646.28
H5	89+88.80	-26.38	646.83	646.84
I5	89+98.80	-26.38	647.41	647.41
C/L Pier 5	90+04.25	-26.38	647.74	647.74
A6	90+14.25	-26.38	648.35	648.35
B6	90+24.25	-26.38	648.94	648.96
C6	90+34.25	-26.38	649.52	649.54
D6	90+44.25	-26.38	650.08	650.11
E6	90+54.25	-26.38	650.61	650.65
F6	90+64.29	-26.37	651.11	651.14
G6	90+74.34	-26.34	651.61	651.62
C/L Brg. S. Abut.	90+84.39	-26.30	652.11	652.11
Bk. S. Abut.	90+86.73	-26.29	652.23	652.23

**GIRDER 2**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	84+20.71	-20.63	614.16	614.16
C/L Brg. N. Abut.	84+23.00	-20.63	614.29	614.29
A1	84+33.00	-20.63	614.87	614.92
B1	84+43.00	-20.63	615.44	615.54
C1	84+53.00	-20.63	616.02	616.14
D1	84+63.00	-20.63	616.60	616.74
E1	84+73.00	-20.63	617.17	617.33
F1	84+83.00	-20.63	617.75	617.90
G1	84+93.00	-20.63	618.33	618.46
H1	85+03.00	-20.63	618.91	619.00
I1	85+17.58	-20.63	619.75	619.79
J1	85+27.58	-20.63	620.32	620.34
K1	85+37.58	-20.63	620.90	620.91
C/L Pier 1	85+43.83	-20.63	621.26	621.26
A2	85+53.83	-20.63	621.84	621.84
B2	85+63.83	-20.63	622.42	622.43
C2	85+73.83	-20.63	622.99	623.03
D2	85+83.83	-20.63	623.57	623.63
E2	85+93.83	-20.63	624.15	624.22
F2	86+03.83	-20.63	624.72	624.81
G2	86+13.83	-20.63	625.30	625.38
H2	86+23.83	-20.63	625.88	625.95
I2	86+33.83	-20.63	626.45	626.52
J2	86+43.83	-20.63	627.03	627.07
K2	86+53.83	-20.63	627.61	627.63
L2	86+63.83	-20.63	628.19	628.19
C/L Pier 2	86+75.21	-20.63	628.84	628.84
A3	86+85.21	-20.63	629.42	629.43
B3	86+95.21	-20.63	630.00	630.02
C3	87+05.21	-20.63	630.57	630.63
D3	87+15.21	-20.63	631.15	631.23
E3	87+25.21	-20.63	631.73	631.83
F3	87+35.21	-20.63	632.30	632.42
G3	87+45.21	-20.63	632.88	632.99
H3	87+55.21	-20.63	633.46	633.56
I3	87+65.21	-20.63	634.04	634.12
J3	87+75.21	-20.63	634.61	634.67
K3	87+85.21	-20.63	635.19	635.22
L3	87+95.21	-20.63	635.77	635.78
C/L Pier 3	88+01.80	-20.63	636.15	636.15
A4	88+11.80	-20.63	636.72	636.72
B4	88+21.80	-20.63	637.30	637.29
C4	88+28.05	-20.63	637.66	637.66
D4	88+38.05	-20.63	638.24	638.26
E4	88+48.05	-20.63	638.82	638.87
F4	88+58.05	-20.63	639.39	639.46
G4	88+68.05	-20.63	639.97	640.03
H4	88+78.05	-20.63	640.55	640.60
I4	88+88.05	-20.63	641.12	641.16
J4	88+98.05	-20.63	641.70	641.71
C/L Pier 4	89+08.80	-20.63	642.32	642.32
A5	89+18.80	-20.63	642.90	642.90
B5	89+28.80	-20.63	643.47	643.49
C5	89+38.80	-20.63	644.05	644.08
D5	89+48.80	-20.63	644.63	644.67
E5	89+58.80	-20.63	645.21	645.25
F5	89+68.80	-20.63	645.78	645.82
G5	89+78.80	-20.63	646.36	646.39
H5	89+88.80	-20.63	646.94	646.95
I5	89+98.80	-20.63	647.51	647.51
C/L Pier 5	90+04.25	-20.63	647.84	647.84
A6	90+14.25	-20.63	648.42	648.43
B6	90+24.25	-20.63	649.00	649.03
C6	90+34.25	-20.63	649.57	649.61
D6	90+44.25	-20.63	650.12	650.18
E6	90+54.25	-20.63	650.65	650.71
F6	90+64.28	-20.62	651.16	651.21
G6	90+74.32	-20.59	651.66	651.69
C/L Brg. S. Abut.	90+84.36	-20.55	652.17	652.17
Bk. S. Abut.	90+86.70	-20.54	652.28	652.28

**GIRDER 3**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	84+20.71	-14.88	614.25	614.25
C/L Brg. N. Abut.	84+23.00	-14.88	614.38	614.38
A1	84+33.00	-14.88	614.96	615.01
B1	84+43.00	-14.88	615.53	615.63
C1	84+53.00	-14.88	616.11	616.23
D1	84+63.00	-14.88	616.69	616.83
E1	84+73.00	-14.88	617.26	617.42
F1	84+83.00	-14.88	617.84	617.99
G1	84+93.00	-14.88	618.42	618.55
H1	85+03.00	-14.88	619.00	619.09
I1	85+17.58	-14.88	619.84	619.88
J1	85+27.58	-14.88	620.41	620.43
K1	85+37.58	-14.88	620.99	621.00
C/L Pier 1	85+43.83	-14.88	621.35	621.35
A2	85+53.83	-14.88	621.93	621.93
B2	85+63.83	-14.88	622.51	622.52
C2	85+73.83	-14.88	623.08	623.12
D2	85+83.83	-14.88	623.66	623.71
E2	85+93.83	-14.88	624.24	624.31
F2	86+03.83	-14.88	624.81	624.90
G2	86+13.83	-14.88	625.39	625.47
H2	86+23.83	-14.88	625.97	626.04
I2	86+33.83	-14.88	626.54	626.60
J2	86+43.83	-14.88	627.12	627.16
K2	86+53.83	-14.88	627.70	627.72
L2	86+63.83	-14.88	628.28	628.28
C/L Pier 2	86+75.21	-14.88	628.93	628.93
A3	86+85.21	-14.88	629.51	629.52
B3	86+95.21	-14.88	630.09	630.11
C3	87+05.21	-14.88	630.66	630.72
D3	87+15.21	-14.88	631.24	631.32
E3	87+25.21	-14.88	631.82	631.92
F3	87+35.21	-14.88	632.39	632.51
G3	87+45.21	-14.88	632.97	633.08
H3	87+55.21	-14.88	633.55	633.65
I3	87+65.21	-14.88	634.13	634.21
J3	87+75.21	-14.88	634.70	634.76
K3	87+85.21	-14.88	635.28	635.31
L3	87+95.21	-14.88	635.86	635.87
C/L Pier 3	88+01.80	-14.88	636.24	636.24
A4	88+11.80	-14.88	636.81	636.81
B4	88+21.80	-14.88	637.39	637.38
C4	88+28.05	-14.88	637.75	637.75
D4	88+38.05	-14.88	638.33	638.35
E4	88+48.05	-14.88	638.90	638.96
F4	88+58.05	-14.88	639.48	639.55
G4	88+68.05	-14.88	640.06	640.12
H4	88+78.05	-14.88	640.64	640.69
I4	88+88.05	-14.88	641.21	641.24
J4	88+98.05	-14.88	641.79	641.80
C/L Pier 4	89+08.80	-14.88	642.41	642.41
A5	89+18.80	-14.88	642.99	642.99
B5	89+28.80	-14.88	643.56	643.58
C5	89+38.80	-14.88	644.14	644.17
D5	89+48.80	-14.88	644.72	644.76
E5	89+58.80	-14.88	645.30	645.34
F5	89+68.80	-14.88	645.87	645.91
G5	89+78.80	-14.88	646.45	646.48
H5	89+88.80	-14.88	647.03	647.04
I5	89+98.80	-14.88	647.60	647.60
C/L Pier 5	90+04.25	-14.88	647.92	647.92
A6	90+14.25	-14.88	648.49	648.50
B6	90+24.25	-14.88	649.06	649.09
C6	90+34.25	-14.88	649.61	649.66
D6	90+44.25	-14.88	650.16	650.22
E6	90+54.25	-14.88	650.69	650.75
F6	90+64.28	-14.87	651.21	651.26
G6	90+74.30	-14.84	651.72	651.75
C/L Brg. S. Abut.	90+84.33	-14.80	652.22	652.22
Bk. S. Abut.	90+86.67	-14.79	652.34	652.34