



PT	LOCATION	DESCRIPTION	LID OR EOP	INLET INVERT	OUTLET INVERT	SYM
1	8' LT STA 59+50	INLETS TA T15F&G	101.36	98.43		
2	56' LT STA 59+50	PRC END SECTION 15"			97.95	

NOTE: TEMPORARY BENCH MARK WITH ASSUMED ELEVATION OF 100.00 IS ON SOUTHEAST BOLT OF SIGN FOUNDATION AT APPROX. 35' LT STA 59+75

COMBINATION CURB AND GUTTER REMOVAL LT STA 59+40 TO 59+70	30 FEET
CONCRETE MEDIAN SURFACE REMOVAL LT STA 59+40 TO 59+70	240 SQ FT
CLASS D PATCHES, TYPE II, 14 INCH LT STA 59+50	9.3 SQ YD
SHOULDER REMOVAL AND REPLACEMENT 10" LT STA 59+50	6.7 SQ YD
COMBINATION CONCRETE CURB AND GUTTER, TYPE M-6.06 LT STA 59+40 TO 59+70	30 FEET
CONCRETE MEDIAN SURFACE, 4 INCH LT STA 59+40 TO 59+70	240 SQ FT

PT. TO PT.	TYPE 1 15" LIN FT	TRENCH BACKFILL CU YD
1-2	42	5.5
TOTALS	42	5.5