

NEW PAVEMENT SCHEDULE										
LOCATION		BITUMINOUS MATERIALS (PRIME COAT)	LEVELING BINDER (MACHINE METHOD) N90, 3/4"	HMA FULL DEPTH 16"	POLYMERIZED HMA SURFACE COURSE, 1 1/2"	PCC BASE COURSE 9 1/2"	HMA BINDER COURSE IL 19.0, N90, 13 3/4"	AGGREGATE BASE COURSE TYPE A 12"	DRILL AND GROUT DOWEL BARS	STRIP REFLECTIVE CRACK CONTROL TREATMENT
		(TON)	(TON)	(SQ YD)	(TON)	(SQ YD)	(TON)	(SQ YD)	(EACH)	(FOOT)
IL 159										
23+59.8	TO	1+88(RAMP D)	1.3	25	51	606		606	297	593
29+20.9	TO	33+84.5	0.4	8	15	184		184	233	465
36+20.2	TO	39+85.27	0.9	17	33	397		397	183	365
RAMP "B"										
14+32.74	TO	18+77.30	1.2	22	44		393	526	223	445
17+21	TO	19+59.4	0.8	16	32		288	385	119	238
RAMP "C"										
13+14.61	TO	19+24.53	1.2	23	47		415	555	305	610
RAMP F										
0+00	TO	24+50	8.1					3705	656	1312
TOTAL:			13.9	111	3705	223	1187	1095	2014	4028

AGGREGATE SHOULDERS					
LOCATION			RT/LT	AGGREGATE SHOULDERS TYPE A, 6"	AGGREGATE WEDGE SHOULDER, TYPE B
STA	TO	STA		(SQYD)	(TON)
IL 159					
23+44	TO	29+56	RT		17
29+22	TO	31+39.39	LT		6
36+25	TO	39+85.27	LT		10
RAMP "B"					
14+32.74	TO	18+77.30	RT		9
14+32.74	TO	17+21	LT		6
17+21	TO	19+59.4	LT		5
RAMP "C"					
13+09.61	TO	19+12.6	RT		12
13+09.61	TO	19+12.6	LT		12
17+21	TO	19+59.4	LT		5
RAMP F					
0+00	TO	24+50	RT	544	
2+37.48	TO	11+38.08	LT	200	
TOTAL :				745	47

CURB AND GUTTER						
LOCATION			CONCRETE CURB & GUTTER TYPE B9.24	CONCRETE CURB & GUTTER TYPE B6.06	CONCRETE CURB TYPE B	PROTECTIVE COAT
STA	TO	STA	(FOOT)	(FOOT)	(FOOT)	(SQ YD)
IL 159						
28+39.73	TO	29+04.71	128			28
28+63.89	TO	28+92.67		89		20
29+55.71	TO	33+84.25	854			190
38+50.27	TO	39+11.46	120			27
RAMP B						
19+52.45	TO	19+70		58		13
RAMP F						
11+01.25	TO	12+57.5			12	3
TOTAL :			1102	147	12	280

CONCRETE MEDIAN					
LOCATION			CONCRETE MEDIAN SURFACE 4"	CONCRETE MEDIAN TYPE SB-9.24	PROTECTIVE COAT
STA	TO	STA	(SQ FT)	(SQ FT)	(SQ YD)
IL 159					
28+39.73	TO	29+02.47	825	20	94
28+63.89	TO	28+92.67	310	20	37
29+58.48	TO	33+84.25	4135		459
38+50.27	TO	39+12.25	775	20	88
RAMP "B"					
19+52.45	TO	19+70	190		21
I-64					
536+35	TO	536+73	143		16
TOTAL			6378	60	715

HOT-MIX ASPHALT SHOULDERS, 8"				
LOCATION			RT/LT	AREA
STA	TO	STA		(SQ YD)
IL 159				
23+81.92	TO	1+88 (RAMP D)	RT	262
29+20.9	TO	33+33.72	LT	397
36+20.2	TO	39+85.27	LT	325
RAMP "B"				
14+32.74	TO	18+77.30	RT	296
17+21	TO	19+59.4	LT	106
RAMP "C"				
13+09.61	TO	19+12.6	LT	266
RAMP F				
0+00	TO	24+50	RT	1633
2+37.48	TO	11+38.08	LT	400
TOTAL :				3685

RAISED PAVEMENT MARKERS						
LOCATION			RAISED REFLECTOR PAVEMENT MARKER ONE WAY CRYSTAL	RAISED REFLECTOR PAVEMENT MARKER REMOVAL	RAISED REFLECTOR PAVEMENT MARKER ONE WAY CRYSTAL (BRIDGE)	PRISMATIC CURB REFLECTOR
STA	TO	STA	(EACH)	(EACH)	(EACH)	(EACH)
IL 159						
23+44	TO	30+00	48	47		36
30+00	TO	36+00	33	28	16	28
36+00	TO	40+85	39	34		17
RAMP B						
14+27.74	TO	18+00	17	14		
18+00	TO	19+75	13	13		11
RAMP C						
13+09.61	TO	19+22	18	15		
RAMP F						
1+52	TO	12+75	13			
12+75	TO	24+50	7			
TOTAL:			188	151	16	92