



PT. TO PT.	TYPE 1	TYPE 1	TYPE 1	TRENCH BACKFILL
	15"	18"	24"	
	LIN FT	LIN FT	LIN FT	CU YD
15-14	26			3.4
14-13		2		0.3
13-10		205		73.4
12-11	26			3.4
11-10	2			0.3
10-7			295	99.7
9-8	26			3.4
8-7	2			0.3
7-4			315	125.2
6-3	10			1.2
3-2	26			4
2-5	10			1.9
5-4	2			0.3
4-1A			115	148.8
1A-1			20	
TOTALS	130	207	745	466

PT	LOCATION	DESCRIPTION	LID OR EOP	INLET INVERT	OUTLET INVERT	SYM
1	25.0' LT STA 1382+25	PRC FLAR END SEC 24"			598.98	
1A	24.0' LT STA 1382+45	MH TA 4' DIA T1F&CL	605.02	596.08	599.08	⊙
2	13.5' LT STA 1383+50	INLETS TB T10F&G	604.52	601.23	601.13	—
3	13.5' RT STA 1383+50	INLETS TB T10F&G	604.52	601.72	601.62	—
4	18.0' LT STA 1383+60	MH TA 4' DIA T1F&CL	604.95	600.83-W, 599.76-S	596.66	⊙
5	13.5' LT STA 1383+60	INLETS TB T10F&G	604.52	601.03	600.93	—
6	13.5' RT STA 1383+60	INLETS TA T10F&G	604.52		601.82	—
7	18.0' LT STA 1386+75	MH TA 4' DIA T1F&CL	606.35	602.61-W, 601.76-S	601.34	⊙
8	13.5' LT STA 1386+75	INLETS TB T10F&G	605.90	602.81	602.71	—
9	13.5' RT STA 1386+75	INLETS TA T10F&G	605.90		603.20	—
10	18.0' LT STA 1389+70	MH TA 4' DIA T1F&CL	607.90	604.17-W, 603.59-S	603.09	⊙
11	13.5' LT STA 1389+70	INLETS TB T10F&G	607.46	604.37	604.27	—
12	13.5' RT STA 1389+70	INLETS TA T10F&G	607.46		604.76	—
13	18.0' LT STA 1391+70	MH TA 4' DIA T1F&CL	609.79	604.83	604.41	⊙
14	13.5' LT STA 1391+69	INLETS TB T10F&G	608.25	605.18	604.93	—
15	13.5' RT STA 1391+84	INLETS TA T10F&G	608.30		605.57	—