

PAVEMENT MARKING SCHEDULE

LOCATION		THERMOPLASTIC PAVEMENT MARKING SKIP - DASH CENTERLINE 4" YELLOW FOOT	THERMOPLASTIC PAVEMENT MARKING EDGE LINE 4" WHITE	SHORT-TERM PAVEMENT MARKING	TEMPORARY PAVEMENT MARKING - LINE 4"	WORK ZONE PAVEMENT REMOVAL SQ FT	RAISED REFLECTIVE PAVEMENT MARKER 2-WAY AMBER EACH	RAISED REFLECTIVE PAVEMENT MARKER REMOVAL EACH	PAVEMENT MARKING REMOVAL SQ FT
STATION	TO STATION	FOOT	LT FOOT RT FOOT	FOOT	FOOT	SQ FT	EACH	EACH	SQ FT
SECTION 95-AC									
10+22.7	TO 25+25.5	380		1498	1524	136	3402	1180	
SECTION 32B-I									
511+00	TO 534+00	580		2294	2325	208	5199	1803	
OLD US 51/COUNTY HWY 5/N 1ST ST									
0+00	TO 7+50	190		750	750	108	1690	600	10
TOTAL =				10291		452	10291	3583	10

\* QUANTITY FOR CONFLICTING PAVEMENT MARKINGS WHICH FALL OUTSIDE THE STATIONING LISTED.

TREE REMOVAL SCHEDULE

LOCATION			DIAMETER		
SECTION 95-AC	STATION	OFFSET (FT)	RT/LT	6" TO 15" (UNITS)	OVER 15" (UNITS)
14+61.3	51.5	RT		10	
14+73.8	49.3	RT		12	
14+85.2	49.1	RT		12	
14+89.4	41.4	RT		8	
14+94.1	51.9	RT		8	
14+97.8	49.4	RT		8	
15+08.5	48.3	RT		8	
15+23.4	42.8	RT		15	
15+33.1	45.7	RT			20
15+37.4	37.0	RT		8	
15+57.5	54.9	RT		12	
15+67.5	40.0	RT			30
15+70.4	27.2	LT		8	
15+75.6	38.2	RT		6	
15+78.5	28.7	LT		12	
15+90.4	38.6	RT		12	
15+97.4	39.5	RT		12	
16+04.3	15.3	LT		12	
16+15.7	29.8	RT		12	
16+35.2	33.8	RT		15	
16+42.8	31.4	RT		8	
16+46.8	24.7	RT		6	
TOTAL =				204	50

EROSION CONTROL SCHEDULE

LOCATION			PERIMETER EROSION BARRIER	EROSION CONTROL BLANKET	INLET AND PIPE PROTECTION	POTASSIUM FERTILIZER NUTRIENT	PHOSPHORUS FERTILIZER NUTRIENT	NITROGEN FERTILIZER NUTRIENT	MULCH, METHOD 2	SEEDING CLASS 2	SEEDING CLASS 4B	TEMPORARY DITCH CHECK	TEMPORARY EROSION CONTROL SEEDING
STATION	TO STATION	LT/RT	FOOT	SQ YD	EACH	POUND	POUND	POUND	ACRE	ACRE	ACRE	FOOT	POUND
SECTION 32B-I													
10+22.7	TO 14+50	LT			1								
10+22.7	TO 14+50	RT			3								
14+50	TO 14+98	LT	50			10	10	10	0.4	0.1			30
14+50	TO 14+98	RT	54			10	10	10	0.4	0.1			30
14+98	TO 16+00	LT				10	10	10	0.4		0.1		30
14+98	TO 17+17.2	RT				10	10	10	0.4	0.1			30
16+00	TO 16+50	LT	52	65		10	10	10	0.4		0.1		30
16+50	TO 21+50	LT	502			10	10	10	0.4		0.1		30
17+17.2	TO 17+54.2	RT			2								
17+54.2	TO 21+76.6	RT				20	20	20	0.8	0.2		18	60
21+50	TO 21+81.6	LT				10	10	10	0.4		0.1		30
21+81.6	TO 22+08.6	LT			2								
21+76.6	TO 22+02.6	RT			2								
22+02.6	TO 25+16.1	RT			1	10	10	10	0.4	0.1		36	30
22+08.6	TO 25+13.9	LT			1	10	10	10	0.4	0.1		36	30
SECTION 95-AC													
531+98	TO 533+01	LT	265		2	10	10	10	0.4	0.1			30
534+25	TO 534+46					10	10	10	0.4	0.1			30
534+94	TO 535+15		58			10	10	10	0.4	0.1			30
535+15	TO 539+38.7					40	40	40	1.6	0.4			120
OLD US 51/COUNTY HWY 5/N 1ST ST													
0+00	TO 4+04.66	LT	404			10	10	10	0.4	0.1			30
0+00	TO 2+54.89	RT				10	10	10	0.4	0.1			30
2+54.89	TO 4+04.66	RT	137			10	10	10	0.4	0.1			30
TOTAL =			1522	65	14	210	210	210	8.4	1.7	0.4	90	630

ROW MARKERS SCHEDULE

LOCATION			FURNISHING & ERECTING RIGHT-OF-WAY MARKERS
SECTION 95-AC	STATION	OFFSET (FT)	RT/LT (EACH)
14+53.41	42.90	RT	1
16+49.81	34.69	RT	1
15+59.01	47.20	RT	1
15+74.54	37.45	RT	1
20+50	33.13	LT	1
20+50	36.87	RT	1
24+83.66	39.23	RT	1
25+08.5	63.23	RT	1
25+11.72	63.08	RT	1
24+78.66	30.80	RT	1
25+03.79	55.66	RT	1
25+07.6	55.76	RT	1
TOTAL =			12

TREE SCHEDULE

LOCATION		TREE, QUERCUS PALUSTRIS (PIN OAK), 2-1/2" CALIPER, BALLED AND BURLAPPED	TREE, QUERCUS RUBRA (RED OAK), 2" CALIPER, BALLED AND BURLAPPED	TREE, CORNUS ALTERNIFOLIA (PAGODA DOG WOOD), 3' HEIGHT, CLUMP FORM, BALLED AND BURLAPPED	TREE, CORNUS FLORIDA (FLOWERING DOG WOOD), 2" CALIPER, TREE FORM, BALLED AND BURLAPPED
STATION	TO STATION	EACH	EACH	EACH	EACH
SECTION 32B-I					
531+98	TO 533+01	9	9	2	2
TOTAL =		9	9	2	2