



LEGEND	
	Work area
	Drum with steady burning light
	Type III barricade
	Temporary concrete barrier
	Traffic signal
	Impact attenuator
	Detector loops

NOTE: THE TEMPORARY CONCRETE BARRIER WALL SHALL BE SECURED TO THE PAVEMENT WITH SIX PINS THROUGHOUT THE LENGTH OF THE PATCH  
 • SET TRAFFIC CONTROL PROTECTION PER STANDARD 701321, 704001 & DISTRICT STANDARD 75.2 FOR OTHER DEVICES NOT SHOWN IN WORK ZONE

FILE NAME =	USER NAME = dosedd	DESIGNED -	REVISED -	<b>STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION</b>	<b>STAGE II CONSTRUCTION CULVERT STA 444 + 02</b>				F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
ct\pw_work\PWIDOT\DOSSDD\dms34371\d11204atg.dgn		DRAWN -	REVISED -		301	21T-2	STEPHENSON	56	23				
PLOT SCALE = 20.0000' / IN.		CHECKED -	REVISED -		SCALE: SHEET NO. OF SHEETS STA. TO STA.				FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT				
PLOT DATE = Thu Dec 04 07:22:05 2008		DATE -	REVISED -						CONTRACT NO. 64C63				