

RAISED REFLECTIVE PAVEMENT MARKER

| LOCATION | EACH |
|----------------------|------|
| US 150 S.N. 090-0038 | |
| 44+95.00 | 1 |
| 45+75.00 | 1 |
| 46+55.00 | 1 |
| 47+35.00 | 1 |
| 48+15.00 | 1 |
| 48+95.00 | 1 |
| 49+75.00 | 1 |
| 50+55.00 | 1 |
| 51+35.00 | 1 |
| 52+15.00 | 1 |
| 52+95.00 | 1 |
| 53+75.00 | 1 |
| 54+55.00 | 1 |
| | |
| US 150 S.N. 090-0040 | |
| 85+04.00 | 1 |
| 85+84.00 | 1 |
| 86+64.00 | 1 |
| 87+44.00 | 1 |
| 88+24.00 | 1 |
| 89+04.00 | 1 |
| 90+64.00 | 1 |
| 91+44.00 | 1 |
| 92+24.00 | 1 |
| 93+04.00 | 1 |
| 93+84.00 | 1 |
| 94+64.00 | 1 |
| TOTAL | 25 |

RAISED REFLECTIVE PAVEMENT MARKER (BRIDGE)

| LOCATION | EACH |
|----------------------|------|
| US 150 S.N. 090-0040 | |
| 89+84.00 | 1 |
| TOTAL | 1 |

PREFORMED PLASTIC PAVEMENT MARKING, TYPE B - LINE 4"

| LOCATION | FOOT |
|----------------------------|------|
| WHITE (SOLID) | |
| US 150 S.N. 090-0038 | |
| 45+10.00 54+30.00 LT | 920 |
| 45+10.00 54+30.00 RT | 920 |
| | |
| US 150 S.N. 090-0040 | |
| 85+35.00 89+14.86 LT | 380 |
| 90+42.07 94+50.00 LT | 408 |
| 85+35.00 89+19.10 RT | 385 |
| 90+46.30 94+50.00 RT | 404 |
| | |
| YELLOW (10' DASH 30' SKIP) | |
| US 150 S.N. 090-0038 | |
| 45+10.00 54+30.00 | 230 |
| | |
| N EAST LANE | |
| 10+50.00 13+46.36 | 74 |
| | |
| CATHERINE STREET | |
| 51+80.00 50+12.00 | 42 |
| | |
| US 150 S.N. 090-0040 | |
| 85+35.00 89+16.98 | 96 |
| 90+44.19 94+50.00 | 102 |
| | |
| WHITE (SOLID) | |
| US 150 S.N. 090-0040 | |
| 89+14.86 TO 90+42.07 LT | 128 |
| 89+19.10 TO 90+46.30 RT | 128 |
| | |
| YELLOW (10' DASH 30' SKIP) | |
| US 150 S.N. 090-0040 | |
| 89+16.98 TO 90+44.19 | 32 |
| TOTAL | 4249 |

PREFORMED PLASTIC PAVEMENT MARKING, TYPE B - LINE 24"

| LOCATION | FOOT |
|------------------|------|
| N EAST LANE | |
| 13+37.80 | 15 |
| | |
| CATHERINE STREET | |
| 50+17.00 | 45 |
| TOTAL | 60 |

STORM SEWER, CLASS A, TYPE 1 12"

| LOCATION | FOOT |
|-------------------------|------|
| US 150 S.N. 090-0038 | |
| 49+06.46 TO 49+08.11 RT | 5 |
| TOTAL | 5 |

STORM SEWER, (PVC), SDR 26, 18"

| LOCATION | FOOT |
|-------------------------|------|
| US 150 S.N. 090-0038 | |
| 49+06.46 TO 49+43.06 RT | 43 |
| 49+00.75 TO 49+56.08 LT | 60 |
| TOTAL | 103 |

STORM SEWER, CLASS A, TYPE 2 18"

| LOCATION | FOOT |
|-------------------------|------|
| US 150 S.N. 090-0038 | |
| 49+56.08 TO 49+56.08 LT | 33 |
| TOTAL | 33 |

INLETS, TYPE A, TYPE 1 FRAME, OPEN LID

| LOCATION | EACH |
|----------------------|------|
| US 150 S.N. 090-0038 | |
| 49+08.11 57.30' RT | 1 |
| TOTAL | 1 |

CHANGEABLE MESSAGE SIGN

| LOCATION | CAL. MO. |
|----------------------|----------|
| US 150 S.N. 090-0040 | |
| EAST APPROACH | 14 |
| WEST APPROACH | 14 |
| | |
| US 150 S.N. 090-0040 | |
| EAST APPROACH | 14 |
| WEST APPROACH | 14 |
| TOTAL | 56 |