



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

March 2, 2020

SUBJECT: FAU Route 2710 (Des Plaines River Rd)
Project STP-95BX(149)
Section 2019-098-RS-SW& SR
Cook County
Contract No. 62J88
Item No. 25, March 6, 2020 Letting
Addendum B

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised page ii of the Table of Contents to the Special Provisions
2. Added page 118 to the Special Provisions
3. Revised sheet 3 of the Plans

Prime contractors must utilize the enclosed material when preparing their bid and must include any changes to the Schedule of Prices in their bid.

Very truly yours,

A handwritten signature in black ink, appearing to read 'Jack A. Elston'.

Jack A. Elston, P.E.
Bureau Chief, Design and Environment

MTS

EMULSIFIED ASPHALTS (BDE)	66
ENGINEER’S FIELD OFFICE AND LABORATORY (BDE)	69
EQUIPMENT PARKING AND STORAGE (BDE)	72
FUEL COST ADJUSTMENT (BDE)	72
GROOVING FOR RECESSED PAVEMENT MARKINGS (BDE).....	75
HOT-MIX ASPHALT – LONGITUDINAL JOINT SEALANT (BDE).....	77
HOT MIX ASPHALT - PAY FOR PERFORMANCE USING PERCENT WITHIN LIMITS - JOBSITE SAMPLING (BDE)	81
HOT MIX ASPHALT – QUALITY CONTROL FOR PERFORMANCE (BDE)	86
MANHOLES, VALVE VAULTS, AND FLAT SLAB TOPS (BDE)	91
PORTLAND CEMENT CONCRETE (BDE)	92
REMOVAL AND DISPOSAL OF REGULATED SUBSTANCES (BDE)	93
SUBCONTRACTOR AND DBE PAYMENT REPORTING (BDE)	103
SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE).....	104
TEMPORARY PAVEMENT MARKING (BDE).....	104
TRAFFIC CONTROL DEVICES - CONES (BDE).....	107
TRAINING SPECIAL PROVISIONS (BDE)	107
IDOT TRAINING PROGRAM GRADUATE ON-THE-JOB TRAINING SPECIAL PROVISION.	110
WARM MIX ASPHALT (BDE)	112
WEEKLY DBE TRUCKING REPORTS (BDE).....	113
WORK ZONE TRAFFIC CONTROL DEVICES (BDE).....	114
REBUILD EXISTING HANDHOLE	116
REBUILD EXISTING HANDHOLE TO HEAVY-DUTY HANDHOLE	117
CONTRAST PREFORMED PLASTIC PAVEMENT MARKING (BDE)	118

CONTRAST PREFORMED PLASTIC PAVEMENT MARKING (BDE)

Effective: November 1, 2017

Revise the first paragraph of Article 780.07(b) of the Standard Specifications to read:

“(b) Type B or C - Standard Application. Standard application of conventional preformed plastic pavement markings shall consist of applying the markings to the pavement surface or to the bottom of a groove recessed in the pavement surface as specified on the plans. Standard application of contrast preformed plastic pavement markings shall consist of applying the markings to the bottom of a groove recessed in the pavement surface. Both conventional and contrast preformed plastic pavement markings shall only be applied when the air temperature is at least 50 °F (10 °C) and rising and the pavement temperature is at least 70 °F (21 °C). However, application of the markings will not be allowed after October 15.”

Add the following paragraph after the fourth paragraph of Article 780.14 of the Standard Specifications:

“The applied line width specified for contrast pavement markings shall include both the white/yellow reflective portion and the black nonreflective portion of the marking.”

Revise the first paragraph of Article 1095.03 of the Standard Specifications to read:

“**1095.03 Preformed Plastic Pavement Markings.** The material shall consist of a white or yellow (as specified) weather resistant, reflective film meeting the requirements specified herein. Where contrast markings are specified, the white or yellow reflective film shall be bordered along both the left and right edges by a 1 1/2 in. (38 mm) wide black weather resistant, nonreflective film also meeting the requirements specified herein.”

Revise the table in Article 1095.03(a) of the Standard Specifications to read:

“Components	Minimum Percent By Weight	
	White or Yellow	Black
Resins and Plasticizers	20 %	20 %
Pigment and Fillers	30 %	30 %
Graded Glass Beads	25 %	- - “

Revise the first paragraph of Article 1095.03(h) of the Standard Specifications to read:

“Glass beads shall be uniformly distributed throughout the white or yellow portions of the material only. A top coating of beads shall be bonded to or directly embedded into the surface of the markings in order to produce immediate retroreflectivity.”

Added 3/2/2020