

03-06-2020 LETTING ITEM 183

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

PLANS FOR PROPOSED
SURFACE TRANSPORTATION PROGRAM - BRIDGE
SECTION 18-06125-00-BR LAWRENCE COUNTY


PROJECT ST15(541)
JOB NO. C-97-072-20
T.R. 142

CONTRACT NO. 95867


Joint Utility Locating Information for Excavators

JULIE 1-800-892-0123

ROUTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
T.R. 142	18-06125-00-BR	LAWRENCE	20	1
CONTRACT 95867		ILLINOIS	PROJECT ST15(541)	



INDEX OF SHEETS	
SHEET	ITEM
1	COVER SHEET
2	SUMMARY OF QUANTITIES
3	ROADWAY PLAN AND PROFILE
4	GENERAL PLAN AND ELEVATION
5	SUPERSTRUCTURE SPAN 1 OR 3
6	SUPERSTRUCTURE DETAILS SPAN 1 OR 3
7	SUPERSTRUCTURE SPAN 2
8	SUPERSTRUCTURE DETAILS SPAN 2
9	STEEL RAILING, TYPE S-1
10	STEEL RAILING, TYPE S-1 DETAILS
11	SOUTH ABUTMENT DETAILS
12	NORTH ABUTMENT DETAILS
13	PIER DETAILS
14	PILE DETAILS
15	BORING LOGS
16-20	CROSS SECTIONS




NOTE: SCALES VALID FOR 24" X 36" SHEETS

- STANDARD DRAWINGS
- STANDARD 000001-07
 - STANDARD 280001-07
 - STANDARD 515001-04
 - STANDARD 701901-08
 - STANDARD 720001-01
 - STANDARD 720006-04
 - STANDARD 728001-01
 - STANDARD 725001-01
 - STANDARD BLR 21-9
 - STANDARD BLR 23-4
 - STANDARD BLR 26-3
 - STANDARD BLR 27-1

SECTION 18-06125-00-BR BEGINS STA. 1+50.00


THREE-SPAN PRECAST PRESTRESSED CONCRETE DECK BEAM BRIDGE
 96'-4" BK - BK ABUTMENTS
 STEEL H PILE / SPILLTHROUGH ABUTMENTS
 STEEL H PILE / SOLID WALL PIERS
 28' DECK
 EXISTING STRUCTURE NO. 051-3079
 PROPOSED STRUCTURE NO. 051-3306



SECTION 18-06125-00-BR
ENDS STA. 8+85.00

FUNCTIONAL CLASSIFICATION - LOCAL ROAD
 ADT = 150
 DESIGN SPEED = 30 MPH

NET LENGTH SECTION 18-06125-00-BR = 735.00 Ft. = 0.139 Mi.



Brandon M. Bridges
 12-5-2019

LICENSE EXPIRES 11/30/2021


CHARLESTON ENGINEERING, INC.
 CONSULTING ENGINEERS
 105 NORTH KITCHELL
 P.O. BOX 397
 OLNEY, ILLINOIS 62450
 (618) 392-0736
 ILLINOIS DEPARTMENT OF PROFESSIONAL REGULATION REGISTRATION #184 003513

APPROVED *December 10, 2019*
Harm
 COUNTY ENGINEER


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION
 PASSED *Dec 26, 2019*
Saphel
 DISTRICT SEVEN ENGINEER OF
 LOCAL ROADS AND STREETS

Releasing For
 Bid Based on
 Limited Review
Dec 26, 2019
Jeffrey P. Moore
 REGION FOUR ENGINEER


ROUTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
T.R. 142	18-06125-00-BR	LAWRENCE	20	2
CONTRACT 95867		ILLINOIS	PROJECT ST15(541)	



TYPICAL SECTION
PROPOSED




TYPICAL SECTION
EXISTING



AGGREGATE DITCH DETAIL
LT. STA. 3+45 TO 4+75
RT. STA. 3+65 TO 4+60

DESIGN DATA

LOCAL ROAD
ADT = 150




ENTRANCE DETAIL

RT. STA. 2+64 - PE
LT. STA. 3+27 - FE
RT. STA. 3+46 - PE

*SEE SHEET 3 FOR REQUIRED DIMENSION

AGGREGATE SURFACE COURSE, TYPE B
6" DEPTH AT PRIVATE ENTRANCES
COMPACTED AND GRASS SEEDED
EARTH SURFACE AT FIELD ENTRANCES
(NO AGGREGATE SURFACE)



TRENCH DETAIL

THROUGH AGGREGATE OR GRASS SURFACES
NOTES:
1. DIMENSION H = 6" FOR PRIVATE ENTRANCES (PE)
2. DIMENSION H = 0" FOR FIELD ENTRANCES (FE)

SUMMARY OF QUANTITIES

CODE NO.	ITEM	UNIT	QUANTITY
Δ LR631020	TRAFFIC BARRIER TERMINAL, TYPE 1	EACH	1
X2501000	SEEDING, CLASS 2 (SPECIAL)	ACRE	0.80
X2830495	AGGREGATE DITCH (SPECIAL)	TON	105
Z0065000	SETTING PILES IN ROCK	EACH	17
20100500	TREE REMOVAL, ACRES	ACRE	0.4
20200100	EARTH EXCAVATION	CU YD	525
20200200	ROCK EXCAVATION	CU YD	35
20300100	CHANNEL EXCAVATION	CU YD	1025
20400800	FURNISHED EXCAVATION	CU YD	920
28100807	STONE DUMPED RIPRAP, CLASS A4	TON	700
35101400	AGGREGATE BASE COURSE, TYPE B	TON	70
40200800	AGGREGATE SURFACE COURSE, TYPE B	TON	750
50100100	REMOVAL OF EXISTING STRUCTURES	EACH	1
50300225	CONCRETE STRUCTURES	CU YD	129
50300280	CONCRETE ENCASMENT	CU YD	2.1
50400305	PRECAST PRESTRESSED CONCRETE DECK BEAMS (17" DEPTH)	SQ FT	2642
50800105	REINFORCEMENT BARS	POUND	10,420
Δ 50900205	STEEL RAILING, TYPE S1	FOOT	192
51201600	FURNISHING STEEL PILES HP12X53	FOOT	598
51202305	DRIVING PILES	FOOT	104
51203600	TEST PILE STEEL HP12X53	EACH	1
51204650	PILE SHOES	EACH	4
51500100	NAME PLATES	EACH	1
54200223	PIPE CULVERTS, CLASS D, TYPE 1 18"	FOOT	40
54200229	PIPE CULVERTS, CLASS D, TYPE 1 24"	FOOT	100
Δ 63100075	TRAFFIC BARRIER TERMINAL, TYPE 5A	EACH	1
67100100	MOBILIZATION	L. SUM	1
Δ 72000200	SIGN PANEL - TYPE 2	SQ FT	18
Δ 72501000	TERMINAL MARKER - DIRECT APPLIED	EACH	4
Δ 72800100	TELESCOPING STEEL SIGN SUPPORT	FOOT	16

Δ SPECIALTY ITEMS

ROUTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
T.R. 142	18-06125-00-BR	LAWRENCE	20	3
CONTRACT 95867		ILLINOIS	PROJECT ST15(541)	

RODNEY A. NEWELL, TRUSTEE OF THE RODNEY A. NEWELL REVOCABLE TRUST
 EVELYN K. NEWELL, TRUSTEE OF THE EVELYN K. NEWELL REVOCABLE TRUST

STA. 5+03.00 PROPOSED STRUCTURE 051-3306
 THREE SPAN PRECAST PRESTRESSED CONCRETE DECK BEAM BRIDGE
 94'-6" TOTAL SPAN, 17" DEPTH BEAMS
 STEEL PILE / SPILLTHROUGH ABUTMENTS
 STEEL PILE / SOLID CONCRETE PILE BENT PIERS
 28.0' DECK
 15' FORWARD LEFT SKEW

EXISTING TELEPHONE LINE
 FRONTIER COMMUNICATIONS
 307 N. JEFFERSON
 ROBINSON, ILLINOIS 62454
 PH. 618-562-9957

EXISTING WATER LINE
 SOUTH LAWRENCE WATER CORPORATION
 RT 1 BOX 246A
 SUMNER, ILLINOIS 62460
 PH. 812-881-1786

EXISTING OVERHEAD ELECTRIC LINE
 NORRIS ELECTRIC CO-OP
 ROUTE 130 SOUTH
 NEWTON, ILLINOIS 62448
 PH. 618-783-8765

RT. STA. 2+64
 CONSTRUCT P.E. 12' WIDTH
 PIPE CULVERT 60" X 24"
 CL-D, TY-1
 U.S.F.L. = 426.27
 D.S.F.L. = 425.60

RT. STA. 3+46
 CONSTRUCT P.E. 12' WIDTH
 PIPE CULVERT 40" X 24"
 CL-D, TY-1
 U.S.F.L. = 425.11
 D.S.F.L. = 424.23

RICHARD E. VANDERMARK

CONSTRUCTION LIMITS OF SECTION 18-06125-00-BR
 TO BE INSIDE OF PROPOSED RIGHT-OF-WAY AND
 CONSTRUCTION EASEMENT BOUNDARY AS SHOWN, FROM
 STA. 1+00.00 TO STA. 8+85.00 (STATION RANGE
 INCLUDES PROPOSED ROADWAY AND DITCH TYPICAL
 SECTION TRANSITION TO EXISTING TYPICAL SECTION).

SECTION 18-06125-00-BR ENDS STA. 8+85.00

P.O.T. STA. 8+85.00
 N: 739,022.21
 E: 1,159,019.99
 COORDINATES BASED ON NAD83
 ILLINOIS EAST STATE PLANE
 COORDINATE SYSTEM

SCALES:
 1" = 50' HOR
 1" = 5' VER


P.O.T. STA. 1+50.00
 N: 738,307.91
 E: 1,158,905.84
 COORDINATES BASED ON NAD83
 ILLINOIS EAST STATE PLANE
 COORDINATE SYSTEM

P.I. STA. 7+99.22
 N: 738,938.48
 E: 1,159,060.34
 COORDINATES BASED ON NAD83
 ILLINOIS EAST STATE PLANE
 COORDINATE SYSTEM


NOTE: PLACE RIPRAP IN DITCHES AFTER EXCAVATION

B.M. RT. STA. 4+26
 31.8' RT OF PROPOSED C ALIGNMENT
 NL IN POWER POLE
 ELEV. 425.82


STA. 5+00.00 EXISTING STRUCTURE 051-3079
 TWO-SPAN STEEL FILLED SPANDREL WALL ARCH
 BEARING ON CONCRETE FOOTINGS
 44.0' SPAN
 19.2' WIDE DECK
 NO SKEW




450	EARTHWORK	CU YD	AGG. SURF. CSE. TYPE B	TON	450
445	EARTH EXCAVATION CHANNEL EXCAVATION EMBANKMENT FURNISHED EXCAVATION	525* 1025** 1475*** 920	STA. 1+50 TO 8+85 RT. STA. 2+64 RT. STA. 3+46	710 20 20 TOTAL 750 TONS	445
440	*QUANTITY INCLUDES 45 C.Y. EXCAVATION FOR CONCRETE STRUCTURES AND AGGREGATE BASE COURSE, TYPE B. COST OF EXCAVATION FOR CONCRETE STRUCTURES INCLUDED IN ITEM "EARTH EXCAVATION." EARTH EXCAVATION QUANTITY ALSO INCLUDES 45 C.Y. OF OVERDIG FOR RIPRAP DITCHES. VOLUME QUANTITIES SHOWN ON CROSS SECTION SHEETS DO NOT INCLUDE OVERDIG VOLUMES.		SEEDING, CLASS 2 (SPECIAL) STA. 1+50 TO 8+85	0.80	440
435	**IT IS ESTIMATED THAT 215 C.Y. OF CHANNEL EXCAVATION WILL BE SUITABLE FOR USE IN THE EMBANKMENT. UNSUITABLE MATERIAL SHALL BE DISPOSED OF BY THE CONTRACTOR.		AGGREGATE DITCH (SPECIAL) LT. STA. 3+45 TO 4+75 RT. STA. 3+65 TO 4+60	60 45 TOTAL 105 TONS	435
430	***QUANTITY INCLUDES ADDITIONAL 15 C.Y. AT LT. STA. 3+27 AND 10 C.Y. AT RT. STA. 3+46. VOLUME QUANTITIES SHOWN ON CROSS SECTION SHEETS DO NOT INCLUDE THESE ADDITIONAL EMBANKMENT VOLUMES.		TREE REMOVAL, ACRES	0.3 0.1 TOTAL 0.4 ACRES	430
425	PIPE CULVERTS, CLASS D, TYPE 1 18"	FOOT		40	425
420	PIPE CULVERTS, CLASS D, TYPE 1 24"	FOOT		60 40 TOTAL 100 FOOT	420
415	SIGN PANEL - TYPE 2	SQ FT	TRAFFIC BARRIER TERMINAL, TYPE 5A	18.0	415
410	TELESCOPING STEEL SIGN SUPPORT	FOOT	TRAFFIC BARRIER TERMINAL, TYPE 1	16.0	410
405					405




ROUTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
T.R. 142	18-06125-00-BR	LAWRENCE	20	5
CONTRACT 95867		ILLINOIS	PROJECT ST15(541)	




SECTION B-B



SECTION C-C
(Showing dimensions)




VIEW D-D



PLAN VIEW

Note: Spacing of S(E) and S2(E) bars may be adjusted up to 4" in the immediate area of the transverse tie diaphragms to miss the block outs for the transverse ties.



SECTION C-C
(Showing reinforcement and permissible strand locations)
Notes: 12 total strands.
Place the number of strands specified in each row symmetrically about the centerline of beam in the permissible strand locations shown.

BAR LIST ONE BEAM ONLY
(For information only)

Bar	No.	Size	Length	Shape
A(E)	7	#4	3'-7"	—
A1(E)	13	#4	3'-10"	—
B(E)	5	#5	25'-3"	—
B1(E)	4	#4	25'-3"	—
S(E)	34	#4	6'-9"	┌
S1(E)	8	#4	5'-3"	┌
S2(E)	26	#4	5'-6"	┌
S3(E)	10	#4	5'-3"	┌
S4(E)	10	#4	4'-6"	┌
U(E)	12	#5	3'-8"	┌
U1(E)	2	#4	7'-1"	┌

Note: See sheet 6 of 20 for additional details and Bill of Material.

MINIMUM BAR LAP


#4 bar = 1'-11"
#5 bar = 2'-6"

SPAN 1 OR 3


CHARLESTON ENGINEERING, INC.
CONSULTING ENGINEERS
105 NORTH KITCHELL
P.O. BOX 397
OLNEY, ILLINOIS 62450
(618) 392-0736
ILLINOIS DEPARTMENT OF PROFESSIONAL REGULATION REGISTRATION #184.003513

SUPERSTRUCTURE
SPAN 1 OR 3
STRUCTURE NO. 051-3306
T.R. 142
OVER INDIAN CREEK
SECTION 18-06125-00-BR
LAWRENCE COUNTY
STATION 5+03.00

ROUTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
T.R. 142	18-06125-00-BR	LAWRENCE	20	6
CONTRACT 95867		ILLINOIS	PROJECT ST15(541)	




FABRIC BEARING PAD
(Interior)
24 Required




FABRIC BEARING PAD
(Exterior)
8 Required

Notes:
All bearing pads shall be 1" thick.


FIXED



SECTION E-E



TYPICAL TRANSVERSE TIE ASSEMBLY




BAR S(E)


BAR S1(E)

BAR S2(E)

BAR S3(E)




PLAN VIEW




CROSS SECTION


SPAN 1 OR 3



BAR A1(E)



BAR U1(E)



LIFTING LOOP DETAIL

BILL OF MATERIAL

Precast Prestressed Conc. Deck Bms. (17" depth) - Spans 1 and 3	Sq. Ft.	1438
---	---------	------

CHARLESTON ENGINEERING, INC.
CONSULTING ENGINEERS
105 NORTH KITCHELL
P.O. BOX 397
OLNEY, ILLINOIS 62450
(618) 392-0736
ILLINOIS DEPARTMENT OF PROFESSIONAL REGULATION #184-003513

SUPERSTRUCTURE DETAILS
SPAN 1 OR 3
STRUCTURE NO. 051-3306
T.R. 142
OVER INDIAN CREEK
SECTION 18-06125-00-BR
LAWRENCE COUNTY
STATION 5+03.00


Note: Connect beams in pairs with the transverse tie configuration shown.

NOTES


Prestressing steel shall be uncoated high strength, low relaxation 7-wire strand, Grade 270. The nominal diameter shall be 1/2" and the nominal cross-sectional area shall be 0.153 sq. in. The 1" Ø rods in the transverse tie assembly shall be tightened to a snug fit and the threads set. Pockets on exterior faces of bridge shall be filled with grout after transverse tie assembly is in place. Reinforcement bars shall conform to ASTM A 706, Grade 60. See Standard Specifications. Two 1/8" fabric adjusting shims of the dimensions of the exterior bearing pad shall be provided for each bearing pad location. A minimum 2 1/2" Ø lifting pin shall be used to engage the lifting loops during handling. Corrosion Inhibitor, per Article 1020.05(b)(10) and 1021.07 of the Standard Specifications, shall be used in the concrete for precast prestressed concrete deck beams. Compressive strength of prestressed concrete, f'c, shall be 6000 psi. Compressive strength of prestressed concrete at release, f'ci, shall be 5000 psi.

PD-1748-LD


ROUTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
T.R. 142	18-06125-00-BR	LAWRENCE	20	7
CONTRACT 95867		ILLINOIS PROJECT ST15(541)		




SECTION F-F



SECTION G-G
(Showing dimensions)




VIEW H-H



PLAN VIEW

- Symmetrical about \bar{C}
- 1-#4 S2(E) bar at \bar{C} , Top
- 1-#4 S(E) bar at \bar{C} , Bottom
- 1-#4 A1(E) bar at \bar{C} , bottom of top slab
- 1-#4 A(E) bars at \bar{C} , top
- 24-#4 S2(E) bars at 9" cts., Top
- 24-#4 S(E) bars at 9" cts., Bottom
- 12-#4 A1(E) bars at 1'-6" cts., Bottom of Top slab
- 6-#4 A(E) bars at 3'-0" cts., Top
- 4-#4 S1(E) bars, Top
- 4-#4 S(E) bars, Bottom



SECTION G-G
(Showing reinforcement and permissible strand locations)

Notes: 24 total strands.
Place the number of strands specified in each row symmetrically about the centerline of beam in the permissible strand locations shown.

BAR LIST ONE BEAM ONLY
(For information only)

Bar	No.	Size	Length	Shape
A(E)	13	#4	3'-7"	—
A1(E)	25	#4	3'-10"	—
B(E)	10	#5	22'-8"	—
B1(E)	4	#4	22'-4"	—
S(E)	57	#4	6'-9"	U
S1(E)	8	#4	5'-3"	U
S2(E)	49	#4	5'-6"	U
S3(E)	10	#4	5'-3"	U
S4(E)	10	#4	4'-6"	U
U(E)	12	#5	3'-8"	U
U1(E)	2	#4	7'-1"	U

Note: See sheet 8 of 20 for additional details and Bill of Material.

Note: Spacing of S(E) and S2(E) bars may be adjusted up to 4" in the immediate area of the transverse tie diaphragms to miss the block outs for the transverse ties.


MINIMUM BAR LAP
#4 bar = 1'-11"
#5 bar = 2'-6"

SPAN 2


CHARLESTON ENGINEERING, INC.
CONSULTING ENGINEERS
105 NORTH KITCHELL
P.O. BOX 397
OLNEY, ILLINOIS 62450
(618) 392-0736
ILLINOIS DEPARTMENT OF PROFESSIONAL REGULATION REGISTRATION #184.003513

SUPERSTRUCTURE
SPAN 2
STRUCTURE NO. 051-3306
T.R. 142
OVER INDIAN CREEK
SECTION 18-06125-00-BR
LAWRENCE COUNTY
STATION 5+03.00

ROUTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
T.R. 142	18-06125-00-BR	LAWRENCE	20	8
CONTRACT 95867		ILLINOIS	PROJECT ST15(541)	




FABRIC BEARING PAD
(Interior)
12 Required




FABRIC BEARING PAD
(Exterior)
4 Required

Notes:
All bearing pads shall be 1" thick.


FIXED




SECTION I-I



TYPICAL TRANSVERSE TIE ASSEMBLY




BAR S(E)




BAR S1(E)


BAR S2(E)




BAR S3(E)



BAR S4(E)




BAR U(E)




PLAN VIEW


SPAN 2




CROSS SECTION



BAR A1(E)



BAR U1(E)



LIFTING LOOP DETAIL

BILL OF MATERIAL

Precast Prestressed Conc. Deck Bms. (17" depth) - Span 2	Sq. Ft.	1204
--	---------	------

CHARLESTON ENGINEERING, INC.
CONSULTING ENGINEERS
105 NORTH KITCHELL
P.O. BOX 397
OLNEY, ILLINOIS 62450
(618) 392-0736
ILLINOIS DEPARTMENT OF PROFESSIONAL REGULATION #184-003513


SUPERSTRUCTURE DETAILS
SPAN 2
STRUCTURE NO. 051-3306
T.R. 142
OVER INDIAN CREEK
SECTION 18-06125-00-BR
LAWRENCE COUNTY
STATION 5+03.00

Note: Connect beams in pairs with the transverse tie configuration shown.



PD-1748-LD

NOTES


- Prestressing steel shall be uncoated high strength, low relaxation 7-wire strand, Grade 270. The nominal diameter shall be 1/2" and the nominal cross-sectional area shall be 0.153 sq. in.
- The 1" Ø rods in the transverse tie assembly shall be tightened to a snug fit and the threads set. Pockets on exterior faces of bridge shall be filled with grout after transverse tie assembly is in place.
- Reinforcement bars shall conform to ASTM A 706, Grade 60. See Standard Specifications.
- Two 1/8" fabric adjusting shims of the dimensions of the exterior bearing pad shall be provided for each bearing pad location.
- A minimum 2 1/2" Ø lifting pin shall be used to engage the lifting loops during handling.
- Corrosion Inhibitor, per Article 1020.05(b)(10) and 1021.07 of the Standard Specifications, shall be used in the concrete for precast prestressed concrete deck beams.
- Compressive strength of prestressed concrete, f'c, shall be 6000 psi.
- Compressive strength of prestressed concrete at release, f'ci, shall be 5000 psi.




**VIEW J-J
ROUND HEAD BOLT**




SECTION K-K




SECTION AT RAILING POST




ANCHOR DEVICE




SECTION L-L




SECTIONS AT RAIL SPLICE



**RAIL SPLICE CONNECTION
AT EXPANSION JT.**



**PLAN-BOTT. SPLICE P
TYPICAL**



END OF RAIL DETAILS

SPLICE DIMENSIONS

T	D	A	B	C	E
≤ 4"	2 1/2"	1'-8"	2"	4"	2 1/2"
> 4" ≤ 6 1/2"	3 3/4"	2'-0"	2 1/2"	5 1/2"	3 1/2"
> 6 1/2" ≤ 9"	5"	2'-4"	3 1/2"	6 1/2"	9"
> 9" ≤ 13"	7"	2'-10"	4 1/2"	8 1/2"	11"
Rail Splice	1 1/4"	1'-8"	2"	4"	—


T = Total movement at expansion joint as shown on the design plans.

Notes:

For multi-span bridges, sufficient 1/4" x 6" x 1'-2" galvanized steel shims shall be provided to align rail between adjacent spans. Cast included with Steel Railing, Type S-1.

All steel rail elements shall be galvanized according to Article 509.05 of the Standard Specifications.

** The studs of the anchor devices shall be placed below the top reinforcement bars and the outermost longitudinal reinforcement bar shall be placed directly above the studs of the rail post anchor device.



VIEW M-M

BILL OF MATERIAL

Item	Unit	Quantity
Steel Railing, Type S-1	Foot	192


CHARLESTON ENGINEERING, INC.
CONSULTING ENGINEERS
105 NORTH KITCHELL
P.O. BOX 397
OLNEY, ILLINOIS 62450
(618) 392-0736
ILLINOIS DEPARTMENT OF PROFESSIONAL REGULATION REGISTRATION #184.003513

**STEEL RAILING, TYPE S-1
STRUCTURE NO. 051-3306
T.R. 142
OVER INDIAN CREEK
SECTION 18-06125-00-BR
LAWRENCE COUNTY
STATION 5+03.00**


(10'-9" Maximum Post Spacing)

ROUTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
T.R. 142	18-06125-00-BR	LAWRENCE	20	12
CONTRACT 95867		ILLINOIS PROJECT ST15(541)		

* Cast top of wingwall flush with exterior beam face after beams have been erected.




ELEVATION



SECTION P-P
(At Right Angles)


BILL OF MATERIAL
NORTH ABUTMENT

Bar	No.	Size	Length	Shape
h	28	#6	6'-6"	—
h ₁	12	#4	6'-9"	—
h ₂	6	#4	31'-8"	—
p	12	#7	31'-8"	—
s	42	#4	11'-11"	□
s ₁	16	#4	3'-10"	□
u	8	#6	11'-7"	—
v	12	#5	7'-10"	OUT IN FIELD
v ₁	64	#5	3'-7"	—
Concrete Structures		Cu. Yd.	16.2	
Reinforcement Bars		Pound	2090	
Furnishing Steel Piles HP 12 X 53		Foot	104	
Driving Piles		Foot	104	
Test Pile HP 12 X 53		Each	1	
Concrete Encasement		Cu. Yd.	2.1	
Pile Shoes		Each	4	



PLAN

PILE DATA
Type: HP 12 X 53
Nominal Required Bearing: 418 kips
Factored Resistance Available: 230 kips
Est. Length: 26 Feet
No. Production Piles: 4
No. Test Piles: 1 - North Abutment




FIELD CUTTING DIAGRAM

Order v bars full length. Cut as shown and use remainder of bars in opposite face.

- General Notes:**
1. Cast backwalls and top of Wingwalls after beams have been erected.
 2. The backwalls and the portion of the Wingwalls above the mandatory construction joint shall be cast against the in-place beam.
 3. Extend "h" bars into the abutment cap.
 4. For details of piles and Concrete Encasement, see sheet 14 of 20.
 5. Drawings not to scale.
 6. All clearances between rebar and form surface shall be 2" unless otherwise noted.
 7. Space reinforcement in cap to miss PPCDB dowel rods.
 8. All exposed edges shall have a standard 3/4" chamfer unless otherwise noted or as directed by the Engineer.
 9. s₁ bars: Alternate the position of the 90° and 135° hooked ends between adjacent s₁ bars.


CHARLESTON ENGINEERING, INC.
CONSULTING ENGINEERS
105 NORTH KITCHELL
P.O. BOX 397
OLNEY, ILLINOIS 62450
(618) 382-0736
ILLINOIS DEPARTMENT OF PROFESSIONAL REGULATION REGISTRATION #184.003513

NORTH ABUTMENT DETAILS
STRUCTURE NO. 051-3306
T.R. 142
OVER INDIAN CREEK
SECTION 18-06125-00-BR
LAWRENCE COUNTY
STATION 5+03.00




STEEL PILE TABLE


Designation	Depth d	Flange width bf	Web and Flange thickness t	Encasement diameter A
HP 12x53	11 ³ / ₄ "	12"	7 ¹ / ₁₆ "	24"




ELEVATION



**ELEVATION
PILES SET IN ROCK**




**ELEVATION
DRIVEN PILES
PILE ENCASEMENT**




SECTION S-S

Note: Forms for encasement may be omitted when soil conditions permit. If soil conditions are not favorable to use the soil as forms, the Contractor shall provide forms; the cost for the forms and all labor to install forms shall be included in item "Concrete Encasement."




ELEVATION




DETAIL A

H-PILE SHOE ATTACHMENT




DETAIL "B"




ISOMETRIC VIEW

**WELDED COMMERCIAL
SPLICE**




ELEVATION




DETAIL D

**WELDED PLATE FIELD
SPLICE**



END VIEW

Designation	F	F _t	F _w	W	W _t	W _w
HP 12x53	10"	5 ³ / ₈ "	1 ¹ / ₂ "	6 ¹ / ₂ "	1 ¹ / ₂ "	3 ³ / ₈ "



ISOMETRIC VIEW

WELDED COMMERCIAL SPLICE ALTERNATE

Note: The steel H-piles shall be according to AASHTO M270 Grade 50.

- * Interrupt welds 1/4" from end of web and/or each flange.
- ** Remove portions of backup plates that extend outside the flanges.
- ***Weld size per pile shoe manufacturer (5/16" min.).

CHARLESTON ENGINEERING, INC.
CONSULTING ENGINEERS
105 NORTH KITCHELL
P.O. BOX 397
OLNEY, ILLINOIS 62450
(618) 392-0736
ILLINOIS DEPARTMENT OF PROFESSIONAL REGULATION REGISTRATION #184.003513


PILE DETAILS
STRUCTURE NO. 051-3306
T.R. 142
OVER INDIAN CREEK
SECTION 18-06125-00-BR
LAWRENCE COUNTY
STATION 5+03.00

NOBLE							BORING No. B-1			water level reading		
ENGINEERING CONSULTANTS							County: Lawrence, IL		Sheet No. 1 of 1		1st encounter: Dry	
Client: Charleston Engineering							Weather: Sunny		Temperature: 30's		water level reading	
Driller: Noble Engineering Consultants							Date Start: 11-13-18		Surface Elevation: 423.7**		@completion	Dry Cave
Location: Sec. #18-06125-00-BR							Date Finished: 11-13-18		Driller: Tony Schocker		Backfill:	Soil cuttings
Depth:	Sample No.	Sample Depth	N-Value	Blow Count	Recovery (%)	Qp (tsf)*	Soil Description	USC Class.	Elev.**			
1							0.0'-9.5' Silt, Clay, Etc. FILL		422.7			
2	SS-1	1.0'-2.5'	19	4-7-12	20			FILL	421.7			
3									420.7			
4	SS-2	3.5'-5.0'	22	9-11-11	80			FILL	419.7			
5									418.7			
6	SS-3	6.0'-7.5'	17	8-8-9	80			FILL	417.7			
7									416.7			
8									415.7			
9	SS-4	8.5'-10.0'	10	5-8-2	100	0.8	9.5'-12.0' CLAY, trace to some sand, medium stiff, gray	CH	414.7			
10									413.7			
11									412.7			
12									411.7			
13									410.7			
14	SS-5	13.5'-15.0'	22	4-10-12	100	3.4	12.0'-17.1' SILTY CLAY, trace to some sand, very stiff, light brown	CL	409.7			
15									408.7			
16									407.7			
17									406.7			
18									405.7			
19	SS-6	18.5'-20.0'	100+	100/2"	100	-	17.1'-19.8' HIGHLY WEATHERED SHALE	-	404.7			
20							AR 19.8'		403.7			
21												
22												
23												
24												
25												
26												
27												
28												
29												
30												
Drilling Method: HSA (2-1/4" id)							comments		* Qp test is an estimate of the unconfined compressive strength performed			
Depth: 0' to 19.8'									by a compact calibrated spring loaded cylinder			
Drill Rig: Mobile B-47									** ground surface elevation at boring location is estimated from bridge deck			
Sampling: split-spoon (SS)									100.0 and is not surveyed			


NOBLE							BORING No. B-2			water level reading		
ENGINEERING CONSULTANTS							County: Lawrence, IL		Sheet No. 1 of 1		1st encounter: Dry	
Client: Charleston Engineering							Weather: Sunny		Temperature: 30's		water level reading	
Driller: Noble Engineering Consultants							Date Start: 11-13-18		Surface Elevation: 425.3**		@completion	Dry Cave
Location: Sec. #18-06125-00-BR							Date Finished: 11-13-18		Driller: Tony Schocker		Backfill:	Soil cuttings
Depth:	Sample No.	Sample Depth	N-Value	Blow Count	Recovery (%)	Qp (tsf)*	Soil Description	USC Class.	Elev.**			
1							0.0'-3.5' Silt, Clay, Etc. FILL		424.3			
2	SS-1	1.0'-2.5'	14	3-5-9	40			FILL	423.3			
3									422.3			
4	SS-2	3.5'-5.0'	12	4-5-7	80	1.0		CL	421.3			
5									420.3			
6	SS-3	6.0'-7.5'	13	4-6-7	80	1.1	3.5'-8.2' SILTY CLAY, trace to some sand, stiff, brown	CL	419.3			
7									418.3			
8									417.3			
9	SS-4	8.5'-10.0'	10	47-100/2"	80	-	8.2'-11.9' HIGHLY WEATHERED SHALE	-	416.3			
10									415.3			
11									414.3			
12							AR 11.9'		413.3			
13												
14												
15												
16												
17												
18												
19												
20												
21												
22												
23												
24												
25												
26												
27												
28												
29												
30												
Drilling Method: HSA (2-1/4" id)							comments		* Qp test is an estimate of the unconfined compressive strength performed			
Depth: 0' to 11.9'									by a compact calibrated spring loaded cylinder			
Drill Rig: Mobile B-47									** ground surface elevation at boring location is estimated from bridge deck			
Sampling: split-spoon (SS)									100.0 and is not surveyed			

CHARLESTON ENGINEERING, INC.
CONSULTING ENGINEERS
105 NORTH KITCHELL
P.O. BOX 397
OLNEY, ILLINOIS 62450
(618) 392-0736
ILLINOIS DEPARTMENT OF PROFESSIONAL REGULATION REGISTRATION #184.003513


BORING LOGS
STRUCTURE NO. 051-3306
T.R. 142
OVER INDIAN CREEK
SECTION 18-06125-00-BR
LAWRENCE COUNTY
STATION 5+03.00




Total Volume at Station 3+00.00	
Cut Area	12.9
Fill Area	9.5
Cumulative Cut Vol	79.0
Cumulative Fill Vol	11.3




Total Volume at Station 2+63.00	
Cut Area	6.3
Fill Area	2.4
Cumulative Cut Vol	65.8
Cumulative Fill Vol	3.1




Total Volume at Station 2+50.00	
Cut Area	8.6
Fill Area	2.2
Cumulative Cut Vol	62.2
Cumulative Fill Vol	2.0









Total Volume at Station 2+00.00	
Cut Area	16.5
Fill Area	0.0
Cumulative Cut Vol	39.0
Cumulative Fill Vol	0.0















Total Volume at Station 1+50.00	
Cut Area	12.8
Fill Area	0.0
Cumulative Cut Vol	11.9
Cumulative Fill Vol	0.0



Total Volume at Station 1+00.00	
Cut Area	0.0
Fill Area	0.0
Cumulative Cut Vol	0.0
Cumulative Fill Vol	0.0







ROUTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
T.R. 142	18-06125-00-BR	LAWRENCE	20	20
CONTRACT 95867		ILLINOIS	PROJECT ST15(541)	

