

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
549	117 T	OGLE	86	21
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		

# SCHEDULES OF QUANTITIES

40603310 HOT -MIX ASPHALT SURFACE COURSE, MIX 'C', N50

28100107	STONE RIPRAP, CLASS A4	LOCATION	REMARKS
	SQ YD		
	37	LT Sta. 803+63.0	BOX 1
	25	LT Sta. 812+64.0	BOX 2
	11	LT Sta. 1056+40.0	BOX 3
	25	LT Sta. 1081+10.0	BOX 4
	40	LT Sta. 1125+82.0	BOX 5
	138	TOTAL	

ION	LOCATION	THICKNESS (in)	REMARKS
16	LT & RT Sta 803+43.2 TO 803+83.6	2 1/2	OVER CLASS C PATCH
16	LT & RT Sta 803+43.2 TO 803+83.6	2 1/2	OVER CLASS C PATCH
25	LT & RT Sta 812+32.9 TO 812+94.8	2 1/2	OVER CLASS C PATCH
26	LT & RT Sta 1055+94.5 TO 1056+58.4	2 1/2	OVER CLASS C PATCH
22	LT & RT Sta 1080+85.7 TO 1081+39.8	2 1/2	OVER CLASS C PATCH
29	LT & RT Sta 1125+45.9 TO 1126+17.6	2 1/2	OVER CLASS C PATCH
134	TOTAL		

40800050 INCIDENTAL HOT -MIX ASPHALT SURFACING

28200200	FILTER FABRIC	LOCATION	REMARKS
	SQ YD		
	37	LT Sta. 803+63.0	Rip Rap -Area-Box 1
	25	LT Sta. 812+64.0	Rip Rap -Area-Box 2
	11	LT Sta. 1056+40.0	Rip Rap -Area-Box 3
	25	LT Sta. 1081+10.0	Rip Rap -Area-Box 4
	40	LT Sta. 1125+82.0	Rip Rap -Area-Box 5
	138	TOTAL	

ION	LOCATION	REMARKS
16	RT Sta. 813+03.0	PE
55	RT Sta. 1117+50.0	PE/ MB
12	RT Sta. 1126+50.0	PE
19	TOTAL	
83	TOTAL	

42001200 PAVEMENT FABRIC

31100910	SUB-BASE GRANULAR MATERIAL, TYPE A 12	LOCATION	REMARKS
	SQ YD		
	116.8	Lt & Rt Sta 803+43.2 TO 803+83.6	OVER PATCH
	204.0	Lt Sta. 810+99.0 TO 814+05.1	STAGE 1
	220.9	Rt Sta 810+85.3 TO 814+16.7	STAGE 2
	93.5	Lt Sta. 1054+90.0 TO 1057+70.6	STAGE 1
	298.1	Rt Sta 1054+30.8 TO 1058+14.0	STAGE 2
	184.2	Lt Sta. 1079+47.4 TO 1082+78.9	STAGE 1
	84.2	Rt Sta 1079+86.9 TO 1082+39.4	STAGE 2
	185.9	Lt Sta. 1124+14.0 TO 1127+48.6	STAGE 1
	297.8	Rt Sta 1123+89.5 TO 1127+72.3	STAGE 2
	1685	TOTAL	

SQ YD	LOCATION	REMARKS
116	LT & RT Sta 803+43.2 TO 803+83.6	
183	LT & RT Sta 812+32.9 TO 812+94.8	
174	LT & RT Sta 1055+94.5 TO 1056+58.4	
155	LT & RT Sta 1080+85.7 TO 1081+39.8	
208	LT & RT Sta 1125+45.9 TO 1126+17.6	
836	TOTAL	

44201373 CLASS C PATCHES, TYPE IV, 12 INCH

SQ YD	LOCATION	REMARKS
116	LT & RT Sta 803+43.2 TO 803+83.6	
183	LT & RT Sta 812+32.9 TO 812+94.8	
174	LT & RT Sta 1055+94.5 TO 1056+58.4	
155	LT & RT Sta 1080+85.7 TO 1081+39.8	
208	LT & RT Sta 1125+45.9 TO 1126+17.6	
836	TOTAL	

35101400	AGGREGATE BASE COURSE, TYPE B	LOCATION	THICKNESS (in)	REMARKS
	ION			
	96	RT Sta. 813+03.0	12	PE
	338	RT Sta. 1117+50.0	12	PE/ MB
	74	RT Sta. 1126+50.0	12	FE
	116	RT Sta. 1115+77.5	12	FE
	508	TOTAL		

42300300 PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 7 INCH

SQ YD	LOCATION	OFFSET (ft)	REMARKS
74	RT Sta. 117+53.0	96 to 112	used in the natural flow of the existing ditch(see detail sheet)

PLOT DATE = Fri, Dec 28, 13:52:59, 2007  
 FILE NAME = c:\projects\64b44\10705\10705.dgn  
 PLOT SCALE = 1/8" = 1'-0"  
 USER NAME = gpfj