



IMPACT ATTENUATORS (NON-REDIRECTIVE),  
TEST LEVEL 3 - 2.0 EACH

SAND MODULE IMPACT ATTENUATORS  
TO BE REMOVED - 28.0 EACH

CONCRETE REMOVAL SPECIAL  
(E) = 24.5 SQYD, (W) = 24.6 SQYD

NOTES:  
PIPE UNDERDRAINS 4" (SPECIAL) SHALL BE EXTENDED TO THE FLOW LINE OR NEAREST INLET. RESETTING OR REPLACING THE PIPE UNDERDRAIN HEADWALLS SHALL BE INCIDENTAL TO PIPE UNDERDRAINS 4".

**\* CRASHWALLS TO BE EXTENDED**

SEC.17, R11W, T19N, 2ND PM

FILE NAME =	USER NAME = collierbw	DESIGNED -	REVISED -
ct:\projects\d501407 (v8)\70643.plnsheet.dgn		DRAWN -	REVISED -
PLOT SCALE = 80.0000' / IN.		CHECKED -	REVISED -
PLOT DATE = 12/20/2007		DATE -	REVISED -

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

I-74 GUARDRAIL & IMPACT ATTENUATORS

SCALE: 1:40 SHEET NO. OF SHEETS STA. 1925+00 TO STA. 1936+00

** CHAMPAIGN & VERMILION COUNTIES			
F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS
74	FY08HSP	**	172
			SHEET NO. 54
CONTRACT NO. 70643			
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT			