



CONCRETE COLLAR DETAIL

GENERAL NOTES:

1. CLASS SI CONCRETE SHALL BE USED THROUGHOUT.
2. WHEN CONCRETE COLLARS ARE USED TO CONNECT PIPES OF DIFFERENT OUTSIDE DIMENSIONS, THE CONCRETE COLLAR SHALL BE FORMED USING THE LARGEST OUTSIDE DIMENSION. (SEE END VIEW)
3. THE WIRE MESH SHALL WEIGHT NOT LESS THAN 54 POUNDS PER 100 SQ. FT.
4. CONCRETE COLLARS WILL BE PAID FOR AS "CONCRETE COLLAR" EACH. THE PAY ITEM INCLUDES ALL LABOR AND MATERIAL REQUIRED TO EXPOSE EXISITNG PIPE, INSTALL WIRE MESH AND CONCRETE COLLAR.

FILE NAME = #FILE#	USER NAME = #USER#	DESIGNED - ---	REVISED - ---	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	DETAIL	F.A.P. RTE. 805	SECTION (101,102,61-1-1)RS	COUNTY MARION	TOTAL SHEETS 81	SHEET NO. 59		
PLOT SCALE = #SCALE#	CHECKED - ---	REVISED - ---	SCALE: _____ SHEET NO. ___ OF ___ SHEETS STA. _____ TO STA. _____			FED. ROAD DIST. NO. _ ILLINOIS FED. AID PROJECT						
PLOT DATE = #DATE#	DATE - -----	REVISED - ---	CONTRACT NO. 76833									