



**PARTIAL ROOF PLAN** 1/8" = 1'-0"

**NOTES:**

1. ROOF CONSTR: RIGID INSULATION ON 4'-0"x8" DP. (MAX.) PRESTRESSED HOLLOW CORE NORM. WT. CONC. SLAB. (TYPE 4HC8-66-S OR APPROVAL EQUAL), TOP OF SLAB VARIES DESIGN CRITERIA: DL = 20PSF LL = 30PSF
2. ALL EMBEDS ARE GALVANIZED WHERE EXPOSED.
3. PRECAST CONTRACTOR TO PROVIDE CONNECTION BETWEEN WALL PANEL TO WALL PANEL, WALL PANEL TO COL FOR 200 lbs/ft IN BOTH DIRECTIONS.
4. PRECASTER IS RESPONSIBLE FOR COORDINATING FABRICATION OF CONCRETE PANELS WITH LOCATION OF ALL ELECTRICAL, MECHANICAL, AND PLUMBING DEVICES. PANELS SHOULD BE DESIGNED TO INCLUDE ALL KNOCKOUTS AND VOIDS REQUIRED FOR DUCTWORK AND JUNCTION BOXES. THEY SHOULD ALSO INCLUDE CONDUIT FOR THE WIRING OF ALL DEVICES.

SHEET TITLE  
PARTIAL  
ROOF PLAN

REV. NO.	DATE	REMARKS

KENNEDY PROJECT NO  
KAI# 10-02048

ISSUE DATE  
20-DEC-07

SHEET NO  
**S2.4**

These drawings are the property of SSE Inc. They are furnished as contract documents only. Their use for reproductions for shop drawings is permitted, except for use as anchor setting plans, if approved by the Engineer, but at the users risk. The user shall remove all seals, firm names, titles, and sheet numbers, and shall assume full responsibility for their accuracy, completeness and status.

The seal(s) and signature(s) apply only to the document to which they are affixed, and expressly disclaim any responsibility for all other plans, specifications, estimates, reports or other documents or instruments relating to or intended to be used for any part or parts of the architectural or engineering project.