



**LEGEND**

- |  |   |  |   |
|--|---|--|---|
| ① EXIST. 4" SUB-BASE GRANULAR MATERIAL                     | ⑩ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2" | ⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8" | ⑲ PROP. HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 1 1/2"         |
| ② EXIST. 8" P.C.C. PAVEMENT                                | ⑪ PROP. CONCRETE MEDIAN SURFACE REMOVAL         | ⑭ PROP. HMA BASE COURSE 11" ***              | ⑳ PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24           |
| ③ EXIST. 8" H.M.A. SHOULDER                                | ⑫ PROP. SUBBASE GRANULAR MATERIAL, TYPE B 4"    | ⑮ PROP. PCC BASE COURSE WIDENING 9"          | ㉑ PROP. CONCRETE MEDIAN SURFACE, 4"                                 |
| ④ EXIST. 4" OVERLAY  | ⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"    |  | ㉒ PROP. CONCRETE MEDIAN, TYPE SM-4.24                               |
| ⑤ EXIST. COMBINATION CURB AND GUTTER, TYPE B-6.06          | ⑭ PROP. HMA BASE COURSE 11" ***                 |  | ㉓ PROP. AGGREGATE WEDGE SHOULDER, TYPE B                            |
| ⑥ PROP. PAVEMENT REMOVAL                                   | ⑮ PROP. PCC BASE COURSE WIDENING 9"             |  | ㉔ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 5"                |
| ⑦ PROP. PAVED SHOULDER REMOVAL                             |   |  | ㉕ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 8"                |
| ⑧ PROP. HOT-MIX ASPHALT SURFACE REMOVAL (VARIABLE DEPTH) * |   |  | ㉖ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 5" |
| ⑨ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"            |   |  | ㉗ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 6" |
|  |   |  |   |

**\*\*\* NOTES:**

- (A) PAINTED MEDIAN VAR. FR. 16'-0" TO 0' FR. STA. 307+04.18 TO 310+13.69 LT (WB PAVT).
- (B) SE TRANSITIONS FROM NORMAL CROWN TO 3.7% FROM STA. 311+21.00 TO 312+66.00
- (C) PAVED SHLDR REM ENDS AT STA.312+82.04 LT (WB PAVT).
- (D) LT TURN LANE WIDTH VAR. FR. 5'-0" TO 13'-0" FR. STA. 307+04.18 TO 308+65.72 LT AND FR. 13'-0" TO 0' FR. STA. 310+13.69 TO 311+90.09 RT.
- (E) LT TURN LANE WIDTH VAR. FR. 8'-0" TO 0' FR. STA. 307+04.18 TO 309+74.69 LT (WB PAVT).

\* NOMINAL MILLING DEPTH 1/2" @ CL OR PGL  
 \*\*\* WHERE WIDENING IS GREATER THAN 6' OR UNDER NEW TURN LANE

FILE NAME =	USER NAME = sparksgw	DESIGNED -	REVISED -	<b>STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION</b>	<b>TYPICAL SECTIONS</b>			F.A.P. 63 (US 24); FAP 63 (US 24/IL 96); FAP 506 (IL 96)
et:\pw\work\p\midot\sparksgw\10259630\0672E31-sht-typical.dgn		DRAWN -	REVISED -		SCALE: NTS	SHEET NO. 7 OF 15 SHEETS	STA. 307+04.18 TO STA. 312+74.92	F.A.P. RTE. SECTION COUNTY TOTAL SHEETS SHEET NO.
		CHECKED -	REVISED -					(1)N,TS-2RS-5&(78)RS-3 ADAMS 194 45
		DATE -	REVISED -					CONTRACT NO. 72E31 ILLINOIS FED. AID PROJECT