### GENERAL NOTES

THE CONTRACTOR SHALL PROVIDE INTERNET ACCESS TO THE HOT-MIX ASPHALT PLANT QUALITY CONTROL LAB SO THAT HOT-MIX ASPHALT PLANT REPORTS CAN BE E-MAILED TO THE DISTRICT HEADQUARTERS. THIS WORK SHALL BE INCLUDED IN THE COST OF HOT-MIX ASPHALT ITEMS.

CONCRETE HEADWALL REMOVAL SHALL BE INCLUDED IN THE COST OF PIPE CULVERT REMOVAL.

THE MATERIAL USED FOR AGGREGATE WEDGE SHOULDER. TYPE B SHALL BE CRUSHED STONE. CRUSHED CONCRETE. OR RAP.

THE MATERIAL USED FOR AGGREGATE SURFACE COURSE, TYPE B SHALL BE CRUSHED STONE OR CRUSHED CONCRETE.

THE MILLINGS COLLECTED FROM THE EXCAVATION OF THE HMA SHOULDERS SHALL BE USED AS BACKFILL FOR THE PROPOSED PIPE CULVERTS. THE PIPE CULVERTS SHALL BE BACKFILLED PER ARTICLE 542.06 (D) OF THE STANDARD SPECIFICATIONS. THE COST OF USING THE MILLINGS AS BACKFILL MATERIAL SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE PER UNIT FOR EXCAVATING AND GRADING EXISTING SHOULDER.

THE TOTAL QUANTITY OF PAINT PAVEMENT MARKING - LINE 4" CONSISTS OF 136,364 FEET OF WHITE AND 17,247 FEET OF YELLOW.

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT:

# HMA SHOULDER

MIXTURE USE: APPLICATION: HMA SHOULDERS, 8"

HOT-MIX ASPHALT SHOULDERS

PG GRADE:

PG 64-22

PG 64-22

11-9.5

DESIGN AIR VOIDS:

4.0% & NDESIGN = 30

4.0% • NDESIGN = 70

MIXTURE COMPOSITION:

POSITION: 1L-19. OL

FRICTION AGGREGATE:

# INCIDENTAL HMA SURFACING

MIXTURE USE: APPLICATION: INCIDENTAL HMA SURFACING (DRIVEWAYS/SIDEROADS) HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N70

PG GRADE: DESIGN AIR VOIDS:

S:

MIXTURE COMPOSITION:

FRICTION AGGREGATE: MIXTURE C

## INDEX OF SHEETS

701901-03 TRAFFIC CONTROL DEVICES

# SHEET NO. ITEM 1 COVER SHEET 2 INDEX OF SHEETS & GENERAL NOTES 3 SUMMARY OF QUANTITIES 4 TYPICAL SECTION 5-6 SCHEDULES 7 ENTRANCE SCHEDULE AND DETAILS 8 TYPICAL APPLICATIONS OF PAVEMENT MARKING THE FOLLOWING STANDARDS ARE A PART OF THESE PLANS AND ARE INCLUDED AFTER SHEET NO. 11:

STD. NO.	DESCRIPTION
000001-06	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001006	DECIMAL OF AN INCH AND OF A FOOT
482001-02	HMA SHOULDER ADJACENT TO FLEXIBLE PAVEMENT
642006	SHOULDER RUMBLE STRIPS, 8 in.
701011-03	OFF-RD MOVING OPERATIONS, 2L. 2W. DAY ONLY
701201-04	LANE CLOSURE, 2L 2W. DAY ONLY, FOR SPEEDS => 45 MPH
701311-03	LANE CLOSURE, 2L. 2W. MOVING OPERATIONS - DAY ONLY
701326-04	LANE CLOSURE, 21. 2W. PAVEMENT WIDENING, FOR SPEEDS => 45 MPH

FILE NAME s	USER NAME : temaloych	DESIGNED -	REVISED -		<u> </u>		GENER	AL NOTE	F,A,P.	SECTION	COUNTY	TOTAL	L SHEE	Ŧ		
cs\pw.work\pwidot\seasleych\d9279424\D7	4552-aht-gennote.dgn	DRAWN -	REVISED	STATE OF ILLINOIS	INDEX OF SHEETS							•	••	8	2	
	PL01 SCALE + 100.0000 17 in.	CHECKED ~	REVISED -	DEPARTMENT OF TRANSPORTATION					EIS				CONTRACT	T NO.	74552	2
Default	PLOT DATE + 9/11/2012	DATE -	REVISED -		SCALE:	SHEET	0F	SHEETS	STA.	TO STA.		president and a second	AID PROJECT			J
											<ul> <li>D7 HW</li> </ul>	A SAFETY SHLD 2013-1	•• Sh	nelby &	Moultr	/ le