

SUMMARY OF QUANTITIES			
CODE NO.	ITEM	UNIT	TOTAL CONSTRUCTION TYPE CODE 0011
20200100	EARTH EXCAVATION	CU YD	170
20300100	CHANNEL EXCAVATION	CU YD	140
20400800	FURNISHED EXCAVATION	CU YD	50
28000305	TEMPORARY DITCH CHECKS	FOOT	92
28000400	PERIMETER EROSION BARRIER	FOOT	165
28100207	STONE DUMPED RIPRAP, CLASS A4	TON	275
40200800	AGGREGATE SURFACE COURSE, TYPE B	TON	465
50100100	REMOVAL OF EXISTING STRUCTURES	EACH	1.0
50200100	STRUCTURE EXCAVATION	CU YD	65
50300225	CONCRETE STRUCTURES	CU YD	24.8
50400405	PRECAST PRESTRESSED CONCRETE DECK BEAMS (21" DEPTH)	SQ FT	1512
50800105	REINFORCEMENT BARS	POUND	2560
50900205	STEEL RAILING, TYPE S1	FOOT	109
51201400	FURNISHING STEEL PILES HP10X42	FOOT	680
51202305	DRIVING PILES	FOOT	680
51203400	TEST PILE STEEL HP10X42	EACH	2
51204650	PILE SHOES	EACH	10
51500100	NAME PLATES	EACH	1
59300100	CONTROLLED LOW-STRENGTH MATERIAL	CU YD	56
67100100	MOBILIZATION	L SUM	1
70101830	TRAFFIC CONTROL AND PROTECTION, STANDARD BLR 21	L SUM	1.0
78201000	TERMINAL MARKER - DIRECT APPLIED	EACH	4
Z0013798	CONSTRUCTION LAYOUT	L SUM	1.0
X2501000	SEEDING, CLASS 2 (SPECIAL)	ACRE	0.3
XX004566	CONCRETE CUT-OFF WALL	CU YD	6.4

^ SEE SPECIAL PROVISIONS
* SPECIALTY ITEMS

PERIMETER EROSION BARRIER	
LOCATION	PERIMETER EROSION BARRIER 28000400 FOOT
TR 143/2600N	
LT. STA 10+35 TO LT. STA 12+00	135
TOTAL	135

GENERAL NOTES

- ALL CONSTRUCTION SHALL BE DONE IN ACCORDANCE WITH THE STATE OF ILLINOIS "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION ADOPTED JANUARY 1, 2012," THESE PLANS AND THE SPECIAL PROVISIONS INCLUDED IN THE CONTRACT DOCUMENTS.
- THE REVISION NUMBERS OF THE STANDARDS LISTED IN THE PLANS ARE TO BE USED FOR CONSTRUCTING OF THIS SECTION.
- ALL CLEARING AND GRUBBING, FENCE REMOVAL AND REMOVAL OF EXISTING DRAINAGE STRUCTURES SHALL BE INCLUDED IN THE COST OF EARTH EXCAVATION.
- THE LOCATION OF EXISTING GAS MAINS, ELECTRIC POWER LINES, TELEPHONE LINES AND OTHER UTILITIES AS SHOWN ON THE PLANS ARE BASED ON CAREFUL FIELD INVESTIGATIONS AND THE BEST INFORMATION AVAILABLE, BUT THE LOCATIONS ARE NOT GUARANTEED. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO ASCERTAIN THEIR EXACT LOCATION FROM THE INDIVIDUAL UTILITY COMPANIES AND BY FIELD INSPECTION.
- WHERE SECTION OR SUBSECTION MONUMENTS ARE ENCOUNTERED, THE ENGINEER SHALL BE NOTIFIED BEFORE SUCH MONUMENTS ARE REMOVED. THE CONTRACTOR SHALL PROTECT AND CAREFULLY PRESERVE ALL PROPERTY MARKS AND MONUMENTS UNTIL THE OWNER, AN AUTHORIZED SURVEYOR OR AGENT HAS WITNESSED OR OTHERWISE REFERENCED THEIR LOCATION.
- THE FOLLOWING RATES OF APPLICATION HAVE BEEN USED IN CALCULATING PLAN QUANTITIES:
AGGREGATE SURFACE COURSE 1.80 TON/CU YD
STONE RIPRAP 1.75 TON/CU YD
- THE AREA TO BE SEEDED SHALL CONSIST OF ALL DISTURBED EARTH SURFACES WITHIN THE RIGHT OF WAY AS DIRECTED BY THE ENGINEER.
ESTIMATED QUANTITY: SEEDING, CLASS 2 (SPECIAL) = 0.3 ACRES

EARTHWORK SCHEDULE							
LOCATION	EARTH EXCAVATION	CHANNEL EXCAVATION	SHRINKAGE FACTOR	PERCENT USED	EARTH EXCAVATION ADJUSTED FOR SHRINKAGE	EMBANKMENT REQUIRED	EARTHWORK BALANCE
	20200100 CU.YD.	20300100 CU.YD.			CU.YD.	CU.YD.	CU.YD.
TR 143/2600N							
STA 7+50 TO STA 9+72	91		25.00%	100.00%	68	150	-82
STA 9+75.33 TO STA 10+32.67		140	25.00%	70.00%	74	0	74
STA 10+35 TO STA 12+00	77		25.00%	100.00%	58	100	-42
TOTAL	168	140			200	250	-50
USE	170	140					-50

FURNISHED EXCAVATION 50 CU YDS

ROADWAY SCHEDULE	
LOCATION	AGGREGATE SURFACE COURSE TYPE B 12" 40200800 TON
	TR 143/2600N
STA 7+50 TO STA 8+00	60.00
STA 8+00 TO STA 9+75.33	210.40
STA 10+32.67 TO STA 11+50	140.80
STA 11+50 TO STA 12+00	53.33
TOTAL	464.53
USE	465

TEMPORARY DITCH CHECKS	
LOCATION	TEMPORARY DITCH CHECKS 28000305 FOOT
TR 143/2600N	
RT. STA 8+40	11.5
LT. STA 8+70	11.5
RT. STA 9+05	11.5
LT. STA 9+20	11.5
RT. STA 9+70	11.5
LT. STA 9+70	11.5
RT. STA 10+40	11.5
RT. STA 10+90	11.5
TOTAL	92