

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
698	*	BUREAU	22	10
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		

* (102)RS-4 & (TX-1,17)RS-2

SIDEROADS & ENTRANCES

LOCATION	DESCRIPTION	AREA	HOT-MIX ASPHALT SURFACE REMOVAL VARIOUS DEPTH	BITUMINOUS MATERIALS PRIME COAT	AGGREGATE PRIME COAT	HOT MIX ASPHALT S.C. MIX "D" N70	INCIDENTAL HOT-MIX ASPHALT SURFACING
STATION		SQ YD	SQ YD	GALLON	TON	TON	TON
1723+00	LT						
1736+17.59	RT	CH 14	255.0	255.0	20.4	0.5	31.1
1736+17.59	LT	SR	170.8	170.8	13.7	0.3	20.8
1741+11	LT	CE		NO WORK			
1746+82	LT	CE		NO WORK			
1749+59	LT	FE					
1752+73	RT	SR	298.3	298.3	23.9	0.6	36.3
1756+38	RT	FE					
1756+60	LT	FE					
1761+67.31 BK = 1761+66.52 AH							
1763+35.03	RT	IL 29	287.0	287.0	23.0	0.6	35.0
1763+35.03	LT	PE	41.0	41.0	3.3	0.1	5.0
1767+59.42	RT	LADD RD		0.0	0.0	0.0	0.0
1770+97	LT	PE	123.0	123.0	9.8	0.2	15.0
1771+83	RT	PE	164.0	164.0	13.1	0.3	20.0
1772+16	LT	PONSETTI DR	82.0	82.0	6.6	0.2	10.0
1773+75	RT	PE	82.0	82.0	6.6	0.2	10.0
1774+37	RT	PE	82.0	82.0	6.6	0.2	10.0
1780+60	LT	CE / CHURCH	82.0	82.0	6.6	0.2	10.0
1780+89.33	RT	3RD ST.	82.0	82.0	6.6	0.2	10.0
1781+80	LT	CE	82.0	82.0	6.6	0.2	10.0
1785+25	RT	2ND ST.	82.0	82.0	6.6	0.2	10.0
1788+86	LT	CE	82.0	82.0	6.6	0.2	10.0
1791+61	RT	CE	82.0	82.0	6.6	0.2	10.0
1792+28	RT	CE	82.0	82.0	6.6	0.2	10.0
1793+32	LT	CE	82.0	82.0	6.6	0.2	10.0
1793+38.97 BK = 863+81.98 AH							
864+93.87	RT	DAKOTA ST	247.0	247.0	19.8	0.5	30.1
871+50	RT	CE	82.0	82.0	6.6	0.2	10.0
872+44	RT	CE	82.0	82.0	6.6	0.2	10.0
873+07.20 BK = 0+00 AH							
0+00	RT	STRONG ST	185.8	185.8	14.9	0.4	22.6
0+00	LT	STRONG ST	228.3	228.3	18.3	0.5	27.8
4+66	RT	RICHARD ST	166.7	166.7	13.3	0.3	20.3
4+66	LT	RICHARD ST	146.7	146.7	11.7	0.3	17.9
9+32	RT	TAYLOR ST	166.7	166.7	13.3	0.3	20.3
9+32	LT	TAYLOR ST	146.7	146.7	11.7	0.3	17.9
13+98	RT	TERRY ST	146.7	146.7	11.7	0.3	17.9
13+98	LT	TERRY ST	166.7	166.7	13.3	0.3	20.3
18+64	RT	HENNESSEY ST	160.8	160.8	12.9	0.3	19.6
18+64	LT	HENNESSEY ST	160.8	160.8	12.9	0.3	19.6
23+30	RT	IL 89		NO WORK			
23+30	LT	SPAULDING ST	199.2	199.2	15.9	0.4	24.3
27+96	RT	GREENWOOD ST	207.5	207.5	16.6	0.4	25.3
27+96	LT	GREENWOOD ST	187.5	187.5	15.0	0.4	22.8
32+62	RT	POWER ST	197.5	197.5	15.8	0.4	24.1
32+62	LT	POWER ST	146.7	146.7	11.7	0.3	17.9
37+00 BK = 8+99.50 AH							
9+27.50	RT	CORNELLA ST	166.7	166.7	13.3	0.3	20.3
9+27.50	LT	CORNELLA ST	167.7	167.7	13.4	0.3	20.4
12+34	LT	NORTH MARY ST	168.7	168.7	13.5	0.3	20.5
14+00	RT	SOUTH MARY ST	169.7	169.7	13.6	0.3	20.7
23+50	RT	PE	82.0	82.0	6.6	0.2	10.0
TOTAL			6021.2	481.7	12.0		698.4

MANHOLE AND WATER VALVE ADJUSTMENTS	
MANHOLE ADJUSTMENTS	WATER VALVE ADJUSTMENTS
12	4

LOCATED THROUGHOUT CURB AND GUTTER SECTION IN SPRING VALLEY

Station Eans. 1761+67.31(BK) = 1761+66.52 (AH)
 1793+38.97(BK) = 863+81.98 (AH)
 873+07.20(BK) = 0+00.00 (AH)
 37+00.00(BK) = 8+99.50 (AH)

SEEDING								
LOCATION	DESCRIPTION	AREA	NITROGEN FERTILIZER NUTRIENT	PHOSPHORUS FERTILIZER NUTRIENT	POTASSIUM FERTILIZER NUTRIENT	SEEDING CLASS 2	EROSION CONTROL BLANKET	FURNISHED EXCAVATION
STATION		SQ YD	POUNDS	POUNDS	POUNDS	ACRES	SQ YD	CU YD
1736+17.59	RT	C.H. 14	60.0	1.1	1.1	0.012	60.0	1.0
1736+17.59	LT	SR	40.0	0.7	0.7	0.008	40.0	0.8
1752+73	RT	SR	40.0	0.7	0.7	0.008	40.0	0.8
1763+35.03	RT	IL 29	60.0	1.1	1.1	0.012	60.0	1.0
1767+59.42	RT	LADD RD.	40.0	0.7	0.7	0.008	40.0	0.8
1780+89.33	RT	3RD ST.	40.0	0.7	0.7	0.008	40.0	0.8
1785+25	RT	2ND ST.	40.0	0.7	0.7	0.008	40.0	0.8
TOTALS			5.7	5.7	5.7	0.066	320.0	6.0

12/19/2006 10:02:15 AM c:\projects\ep01706\detail1.s.dgn