

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	*	VERMILION	8	4

• D5 CRACK & JOINT SEAL 2007-1

## GENERAL NOTES

G. N. - 100

ENGLISH UNITS OF MEASUREMENT SHALL GOVERN OVER AND SUPERSEDE ANY METRIC UNITS SHOWN IN THIS CONTRACT. WHERE INCLUDED, METRIC UNITS ARE FOR INFORMATION ONLY.

G. N. - 451 (SPECIAL)

CRACK ROUTING AND FILLING CONSISTS OF BOTH LONGITUDINAL AND TRANSVERSE CRACKS. AN APPLICATION RATE OF 0.40 LBS./FOOT WAS USED TO DETERMINE CRACK FILLING QUANTITIES. THE SEALANT WILL BE DUSTED WITH FINE SAND, PORTLAND CEMENT, OR MINERAL FILLER, OR COVERED WITH TISSUE PAPER TO PREVENT TRACKING.

THE INTENT AT THIS LOCATION, IS TO ROUT AND SEAL THE ENTIRE CENTERLINE & AUXILIARY LANE JOINTS, ALL TRANSVERSE CRACKS AND MISCELLANEOUS LONGITUDINAL CRACKS IN THE EXISTING PAVEMENT.

LONGITUDINAL: 31,622 LBS  
 TRANSVERSE : 4,097 LBS  
 TOTAL: 35,719 LBS

NOTE: ANY CHANGES TO THE INTENT OF ROUTING AND SEALING AT THE ABOVE LISTED LOCATIONS SHALL BE APPROVED BY THE ENGINEER.

G. N. - 451A (SPECIAL)

THE SECTION OF 452.04, WHICH REFERS TO BACKER ROD PLACEMENT, SHALL ALSO APPLY TO THIS CONTRACT. THIS WORK SHALL BE PERFORMED AT THE DISCRETION OF THE ENGINEER IN ORDER TO KEEP THE APPLICATION RATE OF JOINT FILLER AS CLOSE TO THE DESIGN RATE OF 0.40 LBS./FOOT AS POSSIBLE. FURNISHING AND INSTALLING BACKER ROD WHEN REQUIRED BY THE ENGINEER WILL BE PAID FOR ACCORDING TO ARTICLE 109.04.

NO COMMITMENTS