



METHOD OF FLAGGING

NOTE:

- SIGNS SHALL BE MOUNTED AT A MINIMUM CLEARANCE HEIGHT OF 5 FEET
- ALL SIGNS SHALL BE REMOVED WHEN THE FLAGGING OPERATION CEASES.
- THIS CASE ALSO APPLIES WHEN THE WORK ZONE IS ON THE RIGHT. UNDER THESE CONDITIONS "TRUCKS ENTERING FROM RIGHT" SIGNS SHALL BE SUBSTITUTED FOR "TRUCKS ENTERING FROM LEFT" SIGNS. ALSO THE ARROWBOARD AND "BE PREPARED TO STOP" SIGNS SHALL BE RELOCATED TO THE RIGHT SIDE OF THE ROAD.
- WORK ZONE ACCESS POINTS SHOULD BE A MINIMUM OF ONE HALF MILE APART. MEDIAN WORK ZONE ACCESS POINTS SHOULD NOT BE LOCATED OPPOSITE OF EACH OTHER.
- NIGHTTIME FLAGGING OPERATIONS: THE FLAG STATION SHALL BE LIGHTED WITH ADDITIONAL LIGHTS OTHER THAN STREET LIGHTS. THE FLAGGER CONTROL SIGN AND THE FLAGGER'S VEST SHALL BE REFLECTORIZED. IN ADDITION, THE FLAGGER SHALL HAVE A FLASHLIGHT OR LIGHTED WAND.

I:\SELG\051124\APP-DWG\From Graystone\051124-SH14.dwg - SH14
 Plotted: 11-30-06 @ 10:30am By: 362pmp
 Copyright © 2006, by Bexter & Woodman, Inc.
 State of Illinois Professional Design Firm
 License No. 154-001121 - Expires 4-20-07

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION
NAME	DATE	
RAY RITCHIE	5/10/00	METHOD OF FLAGGING SCALE: NOT TO SCALE DATE: 2/15/2006 DRAWN BY: C.A.D. CHECKED BY: BM-14