



LOAD TABLE
LIGHTING CONTROLLER "O"

CIRCUIT	RED PHASE		BLACK PHASE	
	AMPS	WATTS	AMPS	WATTS
A			B	
C			D	
E			F	
G			H	
I	6	1440	J	6 1440
K			L	6 1440
M	6	1440	N	
O			P	
TOTAL	12	2880	TOTAL	12 2880

LEGEND

- HIGH MAST LIGHT TOWER.
- 400 W. HPS LUMINAIRE (BLACK PHASE- SOLID SYMBOL, RED PHASE-OPEN SYMBOL)
- HIGH MAST TOWER DESIGNATION.
- LIGHTED SIGN STRUCTURE WITH 170 W. FLUORESCENT LUMINAIRES, QUANTITY OF LUMINAIRES AS REQUIRED. (BLACK PHASE- SOLID SYMBOL, RED PHASE, OPEN SYMBOL)
- 3 POLE SAFETY SWITCH
- ELECTRIC UTILITY SERVICE
- GROUND ROD
- LIGHTING CONTROLLER
- UNDERPASS LIGHTING UNIT, 70W HPS LUMINAIRE. (BLACK PHASE- SOLID SYMBOL, RED PHASE-OPEN SYMBOL)
- ELECTRIC CABLE ASSEMBLY
- UNDERPASS LIGHTING UNIT, 150W HPS LUMINAIRE (BLACK PHASE SOLID SYMBOL, RED PHASE OPEN SYMBOL)

**SINGLE LINE DIAGRAM
EXISTING LIGHTING CONTROLLER "O"**

NOTES:
1. SEE DRAWING ME-12 FOR WIRING DIAGRAM DETAILS.

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
F.A.I. 90/94 (DAN RYAN EXPRESSWAY)
31st STREET TO I-57

**SINGLE LINE DIAGRAM
LIGHTING CONTROLLER "O"
PROPOSED IMPROVEMENTS 2005**

SCALE: NOT TO SCALE DRAWN BY: YJ
DATE: OCTOBER 29, 2004 CHECKED BY: TM

SINGH
SINGH & ASSOCIATES, INC.
CONSULTING ENGINEERS

300 W. ADAMS ST.
CHICAGO, IL 60606
TEL: (312) 629-0240
FAX: (312) 629-8449

11/23/2004 1:32:15 PM