




GUTTER OUTLET (SPECIAL) DETAIL
NTS



- NOTES
1. PAINT CURB AND NOSE SOLID FOR 10 FEET OR RADIUS OF NOSE, WHICHEVER IS GREATER.
 2. PAINT MINIMUM OF 3 STRIPES IN DIRECTION OF TRAFFIC.
 3. REDUCED SPACING USED TO OBTAIN 3 STRIPES MINIMUM.
 4. STRIPING RECOMMENDED ONLY WHERE OPERATIONAL PROBLEMS DICTATE.
 5. PAINT SOLID WHERE A MINIMUM OF 3 STRIPES CANNOT BE PLACED.




CURB MARKING DETAIL
NTS



STATION TO STATION	LENGTH (FT)	W* (FT)	D (FT)	FORESLOPE	BACKSLOPE	RIP RAP A3 (SQ YD)	FILTER FABRIC (SQ YD)
136+90 LT TO 139+41 LT	251.0	2 to 6	3	1:3	1:3	672.3	672.3
140+33 LT TO 140+84 LT	51.0	2 to 6	3	1:3	1:3	127.9	127.9
					TOTAL	800.2	800.2

* SEE CROSS SECTIONS

STONE RIPRAP DITCH LINING DETAIL
NTS



PRISMATIC CURB REFLECTOR DETAIL
NTS