



WORK ZONE	W2-1115(10)-3618
SPEED LIMIT	R2-1-3648
RESUME	W2-1114(10)-3612
BOOK FINE MINIMUM	R2-1106-3618

- LEGEND AND NOTES:**
- WORK ZONE
 - ARROW BOARD
 - DIRECTION INDICATOR BARRICADE WITH STEADY BURNING MONODIRECTIONAL LIGHT AT 50' C-C SPACING
 - DRUM WITH STEADY BURNING MONODIRECTIONAL LIGHT AT 25' C-C SPACING AT RAMP, 50' C-C SPACING IN LANE TAPERS AND 100' C-C SPACING AT ALL OTHER LOCATIONS.
 - VERTICAL PANEL AT 200' C-C SPACING ON TANGENT AND 100' C-C SPACING ON CURVE. NOT REQUIRED WITH GUARDRAIL.
 - IMPACT ATTENUATORS, TEMPORARY (FULLY REDIRECTIVE, NARROW), TEST LEVEL 3

1. ALL PAVEMENT MARKINGS SHALL BE WET REFLECTIVE TEMPORARY TAPE, TYPE III.
2. SEE STANDARDS 701401-05 AND 701411-05 AND DISTRICT DETAIL TC-9 IN ADDITION TO TRAFFIC CONTROL ITEMS SHOWN ON THIS SHEET.

FILE NAME = D:\60021-045-STAGE_PLAN.STG2.dgn	USER NAME = dwozniczski	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	BISHOP FORD EXPRESSWAY (I-94) SUGGESTED MAINTENANCE OF TRAFFIC - STAGE II PLAN		F.A.I. RTE. 94	SECTION 10405,ETC,42-T&O707RS-11	COUNTY COOK	TOTAL SHEETS 133	SHEET NO. 45	
	PLOT SCALE = 100.00' / IN.	DRAWN - DMW	REVISED -		SCALE: 1" = 50'	SHEET NO. 17 OF 24 SHEETS	STA. 470+00 TO STA. 485+00	FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT		CONTRACT NO. 60021		
	PLOT DATE = 2/5/2009	CHECKED -	REVISED -									
		DATE - 2/5/2009	REVISED -									