



PROP. HOT MIX ASPHALT SURFACE REMOVAL (2 1/4") - (TYP.)
 PROP. POLYMERIZED LEVELING BINDER (MM) IL. - 4.75, N50 (3/4") - (TYP.)
 PROP. HOT MIX ASPHALT SURFACE COURSE, MIX "D", N70, (1 1/2") - (TYP.)

STRIPING LEGEND

- | | |
|--|---|
| ① 4" YELLOW - SOLID LINE | ⑧ 8" LINE - WHITE |
| ② 6" WHITE - SOLID LINE | ⑨ 12" LINE - WHITE |
| ③ 4" YELLOW - DOUBLE LINE | ⑩ 12" LINE - YELLOW |
| ④ 4" WHITE - CENTERLINE SKIP DASH (10' LINE, 30' SPACE) | ⑪ 12" LINE (SCHOOL CROSSING) - WHITE |
| ⑤ 4" YELLOW - CENTERLINE SKIP DASH (10' LINE, 30' SPACE) | ⑫ 24" STOP BAR - WHITE |
| ⑥ 6" WHITE - DOTTED LINE (2' LINE, 6' SPACE) | ⑬ 6" WHITE - DOTTED LINE (3' LINE, 12' SPACE) |
| ⑦ 6" LINE (CROSS WALK) - WHITE | ⑭ 4" WHITE - SOLID LINE |

PARKING LANES -- VARIABLE DEPTH MILLING AND RESURFACING. SEE TYPICAL SECTIONS.

NOTE:
 1. ALL PAVEMENT MARKING SHALL BE THERMOPLASTIC UNLESS OTHERWISE NOTED. SEE DISTRICT 1 DETAIL.
 2. RAISED REFLECTIVE PAVEMENT MARKERS SHALL BE USED THROUGHOUT THE IMPROVEMENT LIMITS. DOUBLE LANE LINE MARKERS SHALL BE INSTALLED, SEE DIST. 1 DETAIL.

FILE NAME =	USER NAME = gulllaumejp	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	26TH STREET /25TH PLACE (IL 43 TO IL 50) ROADWAY & PAVEMENT MARKING PLAN	F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
es:\pw_work\pwwidot\gulllaumejp\d0117416\DI	1984-Design.dgn	DRAWN -	REVISED -			1459	(0505.1, 0606 & 0707) RS-12	COOK	32	11
PLOT SCALE = 50.0000 ' / IN.	CHECKED -	REVISED -	REVISED -			CONTRACT NO. 62818				
PLOT DATE = 1/9/2009	DATE -	REVISED -	REVISED -			FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT				
						SCALE:	SHEET NO. OF SHEETS		STA. TO STA.	