CONTRACT NO. 68516

 			314 : 14	40.	140. 00	1310
F.A.P. RTE.	SECTIO	N	COUNT	Υ	TOTAL	SHEET NO.
22	•		FULTO	N	71	3
STA.	STA. TO STA.					
FED. ROA	DIST. NO.	ILLINOIS	FED.	AID	PROJECT	

• 133RS-3:134RS-2:135RS-5

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

The following mixture requirements are applicable to this project:

Mixture Use(s):	Mainline Surface Course (Single 2" Lift)	Incidental Surface	Class D Patches	HMA Shoulder (Surface Lift)	HMA Shoulder (Bottom Lift)
RAP % (Max)**:	PG 64-22	PG 64-22	PG 64-22	PG 64-22	PG 64-22
AC/PC:	15%	15%	25%	30%	30%
Design Air Voids:	4.0% @ N = 50	4.0% @ N=50	4.0% @ N = 50	3.0% @ N = 30	4.0% @ N = 30
Mixture Composition: (Gradation Mixture)	IL 9.5 or IL 12.5	IL 9.5 or IL 12.5	IL 19.0	IL 9.5	IL 19.0
Friction Aggregate	Mixture D (dolomite only)	Mixture C	N.A.	Mixture C	N.A.

^{**} If the RAP option is selected, the asphalt cement grade may need to be adjusted; this will be determined by the Engineer.

AGGREGATE (DESCRIPTION), TYPE B

Aggregate (Description), Type B shall be required for all granular construction of side roads, entrances, and mailbox turnouts, whether or not portions of the surfaces thus constructed are to be covered with a bituminous surface, except where noted differently on the plans.

MINIMUM VERTICAL CLEARANCE

The Contractor shall verify the existing structure vertical clearance prior to placing bituminous overlay under any structure. A minimum 14'—3" vertical clearance shall be maintained under all structures.

BUTT JOINT CUTTING TIME RESTRICTION

Butt joints shall not be milled more than three (3) days prior to placement of the bituminous surface course.

PAVING SURFACE COURSE

Continuous paving operations on the main roadway shall be maintained at all times during the construction of the hot—mix asphalt surface. No interruptions for side roads, entrances, turn lanes, etc. will be allowed.

ORDERING LENGTH CONFIRMATION - DRAINAGE ITEMS

The Contractor shall consult with the Engineer in regard to the exact length of the box/pipe culverts, storm sewers, and/or pipe drains required prior to ordering these items.

ENGINEERS FIELD OFFICE

Add the following sentence to the end of paragraph 670.02 (i) and 670.04 (e): All of the telephone lines provided shall have unpublished numbers.

REVISIONS		ILLINOIS DEPARTMENT O	TOANCOODTATION	
NAME	DATE	ILLINUIS DEPARTMENT U	T IRANSPURIATION	
	↓			
	╀	GENERAL	NOTES	
	 	GENERAL	NOIES	
	 			
	1			
	1	CONT. VERT.		
		SCALE: VERT. HORIZ.	DRAWN BY	
		DATE	CHECKED BY	