

TABULATION OF PARTIAL DEPTH PAVEMENT PATCHING

STATION	DIRECTION	LENGTH (FT)	WIDTH (FT)	EXISTING OVERLAY THICKNESS (INCH)	PARTIAL DEPTH REMOVAL X4401705 (SQ YD)	PARTIAL DEPTH PATCHING X4421000 (TON)
2062+10	EB	5	12	2.5	6.7	2.1
2062+66	EB	5	12	2.5	6.7	2.1
2063+18	EB	5	12	2.5	6.7	2.1
2063+56	EB	5	12	2.5	6.7	2.1
2064+19	EB	5	12	2.5	6.7	2.1
2065+19	EB	8	12	2.5	10.7	3.3
2066+19	EB	5	12	2.5	6.7	2.1
2067+22	EB	5	12	2.5	6.7	2.1
2068+22	EB	5	12	2.5	6.7	2.1
2069+73	EB	5	12	2.5	6.7	2.1
2070+73	EB	15	12	2.5	20.0	6.2
2072+74	EB	5	12	2.5	6.7	2.1
2073+73	EB	5	12	2.5	6.7	2.1
2080+39	EB	5	12	2.5	6.7	2.1
2083+16	EB	5	12	2.5	6.7	2.1
2087+72	EB	5	12	2.5	6.7	2.1
2091+08	EB	5	12	2.5	6.7	2.1
2091+85	EB	5	12	2.5	6.7	2.1
2093+58	EB	5	12	2.5	6.7	2.1
2101+23	EB	5	12	2.5	6.7	2.1
2101+62	EB	5	12	2.5	6.7	2.1
2105+83	EB	5	12	2.5	6.7	2.1
2107+94	EB	5	12	2.5	6.7	2.1
2108+88	EB	5	12	2.5	6.7	2.1
2117+60	EB	5	12	2.5	6.7	2.1
2120+35	EB	5	12	2.5	6.7	2.1
2120+87	EB	5	12	2.5	6.7	2.1
2122+78	EB	5	12	2.5	6.7	2.1
2124+87	EB	5	12	2.5	6.7	2.1
2062+10	WB	5	12	2.5	6.7	2.1
2062+66	WB	5	12	2.5	6.7	2.1
2064+19	WB	5	12	2.5	6.7	2.1
2065+19	WB	5	12	2.5	6.7	2.1
2066+19	WB	5	12	2.5	6.7	2.1
2067+22	WB	5	12	2.5	6.7	2.1
2068+22	WB	5	12	2.5	6.7	2.1
2069+73	WB	5	12	2.5	6.7	2.1
2070+73	WB	15	12	2.5	20.0	6.2
2072+74	WB	5	12	2.5	6.7	2.1
2073+73	WB	5	12	2.5	6.7	2.1
2080+39	WB	5	12	2.5	6.7	2.1

TOTAL 304.0 93.6

USE 304.0 94.0

XX005938 SOLAR-POWERED FLASHING BEACON ASSEMBLY (COMPLETE)

STATION	LOCATION	QUANTITY (FT)
US 136/ DEWEY FISHER RD. INTERSECTION	1 RED @ NB STOP SIGN IN ISLAND	1.0
US 136/ DEWEY FISHER RD. INTERSECTION	1 RED @ SB STOP SIGN	1.0
RT 1917+75	1 YELLOW @ EB INTERSECTION ADVANCE WARNING SIGN	1.0
LT 1933+12	1 YELLOW @ WB INTERSECTION ADVANCE WARNING SIGN	1.0
TOTAL=		4.0 EACH