

ENTRANCE & SIDEROAD IMPROVEMENT SCHEDULE FOR RURAL/URBAN "PPP" PROJECTS																	
LOCATION		TYPE OF ENTRANCE	EX MATERIAL TYPE	WIDTH	LT OFFSET	RT OFFSET	LENGTH (FROM EDGE OF PVT/BIT SHLD TO LIMITS OF IMPROVEMENTS)	PR HOT-MIX ASPHALT CONC THICKNESS	HOT-MIX ASPHALT SURF. REM BUTT JOINT	P. C. C. SURF. REM. - BUTT JOINT	PREP OF BASE	AGG. BASE REPAIR	AGGREGATE BASE COURSE TY-B	AGGREGATE SURF COURSE TY-B	BIT (P. C.)	AGG (P. C.)	INCIDENTAL HOT-MIX ASPHALT SURFACING N50
LT/RT/STA	FE/PE/CE/MB/SR	EARTH/AGG/BIT/PCC	FOOT	FOOT	FOOT	FOOT	INCH	SQ YD	SQ YD	SQ YD	TON	TON	TON	TON	TON	TON	TON
RT	126+08.00	MB	BIT	0	27		0	0.0	0		0	0.00		0.00	0.00	0.00	0.00
RT	126+35.00	PE	BIT	16			8	1.5	5		3	0.20		0.00	0.00	0.01	0.29
RT	130+10.00	PE	AGG	20			15	3.5	0		58	3.32		1.79	0.01	0.07	7.32
LT	135+35.00	SR	BIT	45			10	1.5	58		74	4.24		0.00	0.03	0.15	6.25
RT	137+09.00	MB	BIT	0		21	8	3.5	20		20	1.16		0.00	0.02	0.08	8.01
RT	137+30.00	PE	AGG	10			15	3.5	0		42	2.37		1.13	0.01	0.06	5.58
LT	142+91.00	CE	AGG	35			15	8.0	0		83	4.75		1.90	0.02	0.12	27.38
LT	143+79.00	PE	AGG	35			15	3.5	0		83	4.75		2.79	0.02	0.10	9.93
RT	148+50.00	PE	AGG	15			15	3.5	0		50	2.85		1.46	0.01	0.07	6.45
RT	148+65.00	MB	BIT	0	15		8	3.5	21		21	1.21		0.00	0.02	0.09	8.36
RT	148+82.00	PE	AGG	10			15	3.5	0		42	2.37		1.13	0.01	0.06	5.58
LT	149+04.00	PE	AGG	20			15	3.5	0		58	3.32		1.79	0.01	0.07	7.32
LT	154+25.00	SR	BIT	40			10	1.5	58		69	3.92		0.00	0.03	0.14	5.79
RT	154+59.00	PE	AGG	20			8	3.5	0		25	1.42		1.79	0.00	0.01	0.76
RT	155+05.00	PE	AGG	20			8	3.5	0		25	1.42		1.79	0.00	0.01	0.76
RT	155+31.00	MB	BIT	0	26		0	0.0	0		0	0.00		0.00	0.00	0.00	0.00
RT	155+33.00	MB	BIT	0	28		0	0.0	0		0	0.00		0.00	0.00	0.00	0.00
RT	155+35.00	MB	BIT	0	30		0	0.0	0		0	0.00		0.00	0.00	0.00	0.00
RT	156+37.00	PE	AGG	25			8	3.5	0		29	1.67		2.13	0.00	0.01	0.87
RT	159+35.00	PE	EARTH	30			15	3.5	0		75	4.27		2.46	0.02	0.09	9.06
RT	168+18.00	MB	BIT	0	38		8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+20.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+22.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+23.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+23.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+24.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+25.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+26.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+27.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+29.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+31.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+33.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+36.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+38.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+41.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+42.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
RT	168+43.00	MB	BIT	0			8	3.5	43		43	2.43		0.00	0.03	0.17	16.73
LT	168+56.00	SR	AGG	30			15	8.0	0		75	4.27		1.66	0.02	0.11	24.89
RT	168+56.00	SR	AGG	30			15	8.0	0		75	4.27		1.66	0.02	0.11	24.89
RT	171+07.00	MBTO	BIT	0			8	3.5	37		37	2.13		0.00	0.03	0.15	14.63
RT	174+89.00	CE	AGG	118			15	8.0	0		222	12.62		5.84	0.06	0.31	68.69
RT	177+60.00	PE	AGG	35			15	3.5	0		83	4.75		2.79	0.02	0.10	9.93
RT	177+85.00	MB	BIT	0	25		8	3.5	17		17	0.96		0.00	0.01	0.07	6.62
RT	178+71.00	MBTO	BIT	0			8	3.5	40		40	2.28		0.00	0.03	0.16	15.68
RT	178+74.00	MBTO	BIT	0			8	3.5	40		40	2.28		0	0.03	0.16	15.68
RT	180+60.00	PE	AGG	25			15	3.5	0		67	3.80		2.13	0.02	0.08	8.19
RT	185+95.00	PE	AGG	20			8	3.5	0		25	1.42		1.79	0.00	0.01	0.76
RT	186+21.00	MB	BIT	0			0	0.0	0		0	0.00		0.00	0.00	0.00	0.00
LT	188+27.00	PE	BIT	20			8	1.5	46		37	2.13		0.00	0.01	0.07	3.14
RT	188+93.00	SR	AGG	40			15	8.0	15		92	5.22		2.14	0.01	0.04	7.91
LT	189+02.00	PE	BIT	25			8	3.5	46		42	2.38		0.00	0.02	0.08	8.19