

SIGNAL HEAD, 1-FACE, 1-SECTION  
 THE BOTTOM OF THE HOUSING SHALL  
 BE NOT LESS THAN 12" (305mm) NOR  
 MORE THAN 24" (610mm) ABOVE THE  
 TOP OF THE SIGN.

4" (102 mm) X 6" (152 mm)  
 WOOD POST AND SIGN

FLASHER  
 CONTROLLER  
 AND CABINET

7' (2.134m) MIN. URBAN  
 5' (1.524m) MIN. RURAL

1/2" (38mm) G.S. CONDUIT, FIVE  
 EVENLY SPACED CONDUIT  
 CLAMPS SHALL BE USED TO  
 ATTACH CONDUIT TO POST

1/2" (38mm) DRILLED HOLE CENTERED  
 AT 18" (457mm) FROM GROUND LEVEL

1/2" (38mm) DRILLED HOLE CENTERED  
 AT 4" (102mm) FROM GROUND LEVEL

30" (76mm) MIN.

FLASHER  
 CONTROLLER  
 AND CABINET

CONDUIT CLAMP

POST MOUNTED FLASHING BEACON  
 WITH CONTROLLER AND CABINET

FILE NAME = W:\distatd\22x34\ts04.dgn	USER NAME = geglentobt	DESIGNED -	REVISED - 01-01-07
		DRAWN -	REVISED -
	PLOT SCALE = 50,0000' / IN.	CHECKED -	REVISED -
	PLOT DATE = 1/4/2008	DATE -	REVISED -

STATE OF ILLINOIS  
 DEPARTMENT OF TRANSPORTATION

POST MOUNTED FLASHING BEACON WITH CONTROLLER AND CABINET	
SCALE: NONE	SHEET NO. 2 OF 3 SHEETS
STA.	TO STA.

* 525/345 (US 20) ** McHENRY & KANE				
F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
*	2009-089 I	**	46	39
TS-04		CONTRACT NO. 60134		
FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT				