



SEE FOLLOWING SHEET FOR ASSOCIATED DRAINAGE PROFILES.

NOTES:

1. EXISTING 3'x2' BOX CULVERT WAS EXTENDED WITH 36" PIPE TO BE VERIFIED IN THE FIELD.
2. OFFSETS TO STRUCTURES ARE GIVEN AS FOLLOWS:
 - LOCATED IN CURB LINE - OFFSET TO EDGE OF PAVEMENT
 - LOCATED IN GRASS - OFFSET TO CENTER OF STRUCTURE
 - LOCATED IN PAVEMENT - OFFSET TO FUTURE EDGE OF PAVEMENT
 - FES - OFFSET TO END OF STORM SEWER
3. ALL CONNECTIONS TO EXISTING STRUCTURES SHALL BE CORE DRILLED, COST OF THE CONNECTION SHALL BE CONSIDERED AS INCLUDED IN THE INSTALLATION OF THE APPROPRIATE STORM SEWER.

FILE NAME =	USER NAME = #USER#	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	DRAINAGE & UTILITIES	F.A.P. RTE. 353	SECTION 13-1	COUNTY WILL	TOTAL SHEETS 67	SHEET NO. 24	
#FILE#		DRAWN -	REVISED -			SCALE: 1:50 SHEET NO. 5 OF 6 SHEETS STA. 179+50.00 TO STA. 194+50.00					
		CHECKED -	REVISED -			CONTRACT NO. 60152					
		DATE -	REVISED -			ILLINOIS FED. AID PROJECT					