

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	GENERAL NOTES AND INDEX OF SHEETS
3-4	SUMMARY OF QUANTITIES
5-8	SCHEDULE OF QUANTITIES
9-13	TYPICAL SECTIONS
14-20	ALIGNMENT, TIES AND BENCHMARKS
21-22	MAINTENANCE OF TRAFFIC GENERAL NOTES
23	MAINTENANCE OF TRAFFIC UTILITY STAGING - STAGE 1
24	MAINTENANCE OF TRAFFIC UTILITY STAGING - STAGE 2
25	MAINTENANCE OF TRAFFIC UTILITY STAGING - STAGE 3
26-29	MAINTENANCE OF TRAFFIC TYPICAL SECTIONS
30-38	MAINTENANCE OF TRAFFIC PLANS - STAGE 1
39-51	MAINTENANCE OF TRAFFIC PLANS - STAGE 2
52-63	MAINTENANCE OF TRAFFIC PLANS - STAGE 3
64-78	REMOVAL PLAN
79-93	DESIGN PLAN AND PROFILE
94-108	DRAINAGE AND UTILITIES PLAN AND PROFILE
109-123	DRAINAGE PROFILE
124-129	DRAINAGE SCHEDULE
130-137	EROSION AND SEDIMENT CONTROL
138-152	PROPOSED AND EXISTING ELEVATIONS
153-157	PAVEMENT MARKING PLAN
158	SIGN LEGEND
159-165	SIGNING PLAN
166	LANDSCAPE PLANTING NOTES
167-181	LANDSCAPING PLAN
182	LANDSCAPE SCHEDULE AND DETAILS
183-193	LANDSCAPE DETAILS
194-220	TRAFFIC SIGNAL PLANS
221	ELECTRICAL NOTES, LEGEND AND ELECTRICAL LOAD SCHEDULE
222-223	VOLTAGE DROP CALCULATION FOR CABINETS
224	WIRING DIAGRAM FOR RECEPTACLE CABINET FOR ONE RECEPTACLE
225	WIRING DIAGRAM FOR RECEPTACLE CABINET FOR TWO RECEPTACLES
226	WIRING DIAGRAM FOR RECEPTACLE CABINET FOR THREE RECEPTACLES
227-242	LIGHTING INSTALLATION AND REMOVAL PLAN
243-245	ELECTRICAL CABINET SINGLE LINE DIAGRAM AND LEGEND
246	LIGHTING POLE, WIRING IN TRENCH, SPLICING ELECTRICAL CABLES AND HANDHOLE DETAILS
247	AUSTIN CABINET WIRING DIAGRAM-EXISTING
248	AUSTIN CABINET WIRING DIAGRAM-REMOVAL
249	AUSTIN CABINET WIRING DIAGRAM-PROPOSED
250-258	PROJECT SPECIFIC DETAILS
259-274	DISTRICT 1 DETAILS

HIGHWAY STANDARDS

000001-05	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
424001-05	CURB RAMPS FOR SIDEWALKS
604001-03	FRAME AND LIDS TYPE 1
606001-04	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
701501-05	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
701502-03	URBAN LANE CLOSURE, 2L, 2W, WITH BIDIRECTIONAL LEFT TURN LANE
701602-04	URBAN LANE CLOSURE, MULTILANE, 2W WITH BIDIRECTIONAL LEFT TURN LANE
701701-06	URBAN LANE CLOSURE, MULTILANE INTERSECTION
701801-04	LANE CLOSURE MULTILANE 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE
701901-01	TRAFFIC CONTROL DEVICES
704001-06	TEMPORARY CONCRETE BARRIER
720001-01	SIGN PANEL MOUNTING DETAILS
720006-02	SIGN PANEL ERECTION DETAILS
720016-02	MAST ARM MOUNTED STREET NAME SIGNS
780001-02	TYPICAL PAVEMENT MARKINGS
814001-02	HANDHOLES

GENERAL NOTES

- THE LOCATION OF DRAINAGE STRUCTURES, STORM SEWERS, WATER MAINS, SANITARY SEWERS, AND OTHER PUBLIC OR PRIVATE UTILITIES AS SHOWN ON THE PLANS IS APPROXIMATE AND THEIR EXACT LOCATION IS TO BE DETERMINED IN THE FIELD BY THE CONTRACTOR. THIS WORK SHALL BE CONSIDERED INCLUDED IN THE COST OF MOBILIZATION UNIT BID PRICE OF THE CONTRACT, AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.
- ALL AREAS DISTURBED DURING CONSTRUCTION OPERATIONS AND NOT PART OF THE WORK AS SHOWN HEREON SHALL BE RESTORED TO ORIGINAL CONDITION TO THE SATISFACTION OF THE ENGINEER AT NO ADDITIONAL COMPENSATION TO THE CONTRACTOR. IT IS INCUMBENT UPON THE CONTRACTOR TO SHOW THAT DAMAGED AREAS WERE NOT DISTURBED BY CONSTRUCTION OPERATIONS.
- THESE DRAWINGS ASSUME THAT THE CONTRACTOR WILL UTILIZE AN ELECTRONIC DRAWING FILE AND STAKE ALL SITE IMPROVEMENTS USING COORDINATES TIED INTO THE PROVIDED CONTROL POINTS. THE DIMENSIONS INDICATED ON THE DRAWINGS ARE FOR THE CONVENIENCE OF THE CONTRACTOR ONLY.
- THE CONTRACTOR SHALL TAKE ALL NECESSARY SAFETY PRECAUTIONS TO PROTECT ABUTTING PROPERTY, UTILITIES, PEDESTRIANS, AND VEHICULAR TRAFFIC.
- THE CONTRACTOR IS RESPONSIBLE FOR ADJUSTING ALL EXISTING UTILITIES AND STRUCTURES AS NECESSARY TO THE FINAL PROPOSED SURFACE PROFILE GRADES. CONTRACTOR SHALL OBTAIN ALL PERMITS NECESSARY FOR ADJUSTING EXISTING UTILITIES AND STRUCTURES AND ALL COORDINATION WITH CITY AND/OR VILLAGE DEPARTMENTS AND UTILITY OWNERS.
- CONTRACTOR IS RESPONSIBLE FOR REMOVAL, STORAGE, AND RE-INSTALLATION OF ALL EXISTING SIGNAGE, BENCHES, SIDEWALK RAILINGS, AND OTHER ITEMS THAT ARE IMPACTED BY THIS CONTRACT AND ARE NOT SHOWN AS BEING REPLACED. THE CONTRACTOR IS RESPONSIBLE FOR REPLACING ANY OF THESE ITEMS THAT ARE DAMAGED AS A RESULT OF THIS CONTRACT FOR NO ADDITIONAL COST. THE REMOVAL AND RE-INSTALLATION OF THESE ITEMS IS NOT QUANTIFIED SEPARATELY AND ARE INCLUDED IN THE COST OF MOBILIZATION.
- THE CONTRACTOR SHALL MAINTAIN SURFACE DRAINAGE OF THE ROAD DURING CONSTRUCTION.

DISTRICT 1 STANDARD DETAILS

BD500-01 (BD-7)	DETAIL OF STORM SEWER CONNECTION TO EXISTING SEWER
BD600-03 (BD-8)	DETAIL FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
BD600-05 (BD-16)	DROP MANHOLE DETAILS
BD400-04 (BD-22)	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
BD400-05 (BD-32)	BUTT JOINT AND HMA TAPER DETAILS
BD400-06 (BD-33)	HMA TAPER AT EDGE OF P.C.C. PAVEMENT
BD-36	FIRE HYDRANT TO BE MOVED
BE215	LIGHT CONTROLLER SINGLE DOOR
BE300	LIGHT POLE FOUNDATION 30' (9.144 m) TO 35' (10.668 m) M.H. 1 1/2" (292 mm) BOLT CIRCLE
BE305	LIGHT POLE FOUNDATION, METAL
BE702	MISC. ELECTRICAL DETAILS SHEET A
TC-10	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS
TC-11	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
TC-13	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
TC-16	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
TC-22	ARTERIAL ROAD INFORMATION SIGN

- THE CONTRACTOR SHALL NOTIFY ALL UTILITY COMPANIES FOR FIELD LOCATIONS OF THEIR FACILITIES PRIOR TO BEGINNING CONSTRUCTION. THE CONTRACTOR WILL BE RESPONSIBLE FOR THE MAINTENANCE AND PRESERVATION OF THESE FACILITIES. ALL UTILITY LOCATIONS SHOWN MUST BE VERIFIED BY THE CONTRACTOR IN THE FIELD.
- CARE MUST BE TAKEN FOR ANY EARTH EXCAVATION NEAR EXISTING TREES SO THAT DAMAGE TO THE TREE ROOTS DOES NOT OCCUR.
- WHEN CONCRETE REMOVAL IS REQUIRED, IT MUST BE ACCOMPLISHED BY SAWCUT, SLEDGES, AND PNEUMATIC HAND TOOLS. EQUIPMENT AND METHODS USED MUST BE SUCH AS TO PREVENT CRACKING, SHATTERING OR SPALLING OF CONCRETE THAT IS TO REMAIN.
- ACCESS MUST BE MAINTAINED TO ALL EXISTING PROPERTIES DURING CONSTRUCTION PER ARTICLE 107.09 UNLESS ARRANGEMENTS ARE MADE IN WRITING BY THE CONTRACTOR WITH THE PROPERTY OWNERS WITH A COPY TO THE ENGINEER FOR SHORT TERM CLOSURES.
- IF THE CONTRACTOR CAUSES DEBRIS TO ENTER THE EXISTING SEWERS, THAT ENTIRE SECTION OF SEWER BETWEEN MANHOLES MUST AT ONCE BE THOROUGHLY CLEANED AND RODDED BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE CONTRACT. ALL SEWER AND WATER STRUCTURES SO CONTAMINATED MUST AT ONCE BE THOROUGHLY CLEANED BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE CONTRACT.
- IN LOCATIONS WHERE THE MAIN STORM SEWER IS NOT BEING REPLACED AND THE EXISTING DRAINAGE FACILITIES ARE DISTURBED OR DAMAGED DURING CONSTRUCTION BY THE CONTRACTOR, THE CONTRACTOR MUST RESTORE AND REPLACE THE DAMAGE AT HIS/HER EXPENSE TO THE SATISFACTION OF THE ENGINEER. THE STORM SEWER FLOW MUST BE MAINTAINED AT ALL TIMES.
- ALL HMA PAVEMENT SURFACE COURSES, CONCRETE BASE COURSES, CONCRETE PAVEMENTS, CURBS, GUTTERS AND SIDEWALKS WHICH ARE TO BE REMOVED MUST BE SAW CUT AT THE LIMITS OF REMOVAL. SAW CUTTING SHALL BE INCLUDED WITHIN THE REMOVAL PAY ITEM FOR WHICH THE SAW CUTTING IS BEING PROVIDED.
- CONTRACTOR MUST SAWCUT AND HAND BREAK FOR SIDEWALK REMOVAL AT THE R.O.W/ BUILDING LINE TO AVOID DAMAGE TO ADJACENT PROPERTIES. SAW CUTTING SHALL BE INCLUDED WITHIN THE REMOVAL PAY ITEM FOR WHICH THE SAW CUTTING IS BEING PROVIDED.
- WHEN PLACING CONCRETE ADJACENT TO PRIVATE PROPERTY, THE CONTRACTOR MUST PROTECT PROPERTY (VISQUEEN, ETC.) TO AVOID CONCRETE SPLATTER AND/OR DAMAGE.
- THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING OF WORK FOR LOCATIONS OF UDERGROUND TRAFFIC SIGNAL LINES AND INTERCONNECT CABLES AND (847) 221-3078 TO LOCATE UNDERGROUND LIGHTING CABLE.
- THE CONTRACTOR SHALL ADVISE THE POLICE AND FIRE DEPARTMENTS DAILY AS TO WHAT STREETS, IF ANY, ARE TO BE CLOSED OR PARTIALLY BLOCKED SO THAT THEY CAN EFFICIENTLY ROUTE THEIR EMERGENCY VEHICLES.

	POLICE DEPARTMENT TELEPHONE NO.	FIRE DEPARTMENT TELEPHONE NO.
VILLAGE OF OAK PARK	(708) 386-3800	(708) 445-3300
CITY OF BERWYN	(708) 795-5600 EXT. 3100	(708) 788-2660 EXT. 3280
TOWN OF CICERO	(708) 652-2130	(708) 652-0174

- THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS, AREA TRAFFIC FIELD TECHNICIAN, AT 708-597-9800 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.

MWRD GENERAL NOTES

- THE MWRD LOCAL SEWER SYSTEMS SECTION FIELD OFFICE MUST BE NOTIFIED AT LEAST TWO (2) WORKING DAYS PRIOR TO THE COMMENCEMENT OF ANY WORK (CALL 708-588-4055).
- ELEVATIONS ARE BASED ON VILLAGE OF OAK PARK DATUM. VILLAGE OF OAK PARK DATUM IS BASED ON CITY OF CHICAGO ELEVATION DATUM WHERE A FACTOR OF 579.48 CAN BE ADDED TO THE ELEVATIONS TO ACHIEVE NGVD 1929 ELEVATIONS.
- NO FLOOR DRAINS EXCEPT AS NOTED.
- NO FOOTING DRAINS AND DOWNSPOUTS.
- ALL SANITARY PIPE MATERIALS AND JOINTS (AND STORM SEWER PIPE MATERIALS AND JOINTS IN A COMBINED SEWER AREA) SHALL CONFORM TO: WATER MAIN QUALITY PVC SDR 26 8" TO 12" DIAMETER PRESSURE PIPE AND FABRICATED FITTINGS IN ACCORDANCE WITH ASTM D 2241. PVC MATERIAL SHALL CONFORM TO NSF STANDARD 14 AND BE DESIGNATED CLASS 12454 C (PVC 1120) IN CONFORMANCE WITH ASTM D 1784. THE SDR RATING SHALL BE LIMITED TO A MINIMUM PRESSURE RATING OF 160 PSI OR GREATER AT 23°C (73.4°F).

ELASTOMERIC SEALS (GASKETS) USED FOR PUSH-ON JOINTS SHALL COMPLY WITH ASTM STANDARD F477 AND SHALL BE PRESSURE RATED IN ACCORDANCE WITH ASTM D3139.
- ALL SANITARY SEWER CONSTRUCTION (AND STORM SEWER CONSTRUCTION IN COMBINED SEWER AREAS), REQUIRES STONE BEDDING WITH STONE 1/4" TO 1" IN SIZE, WITH MINIMUM BEDDING THICKNESS EQUAL TO 1/4 THE OUTSIDE DIAMETER OF THE SEWER PIPE, BUT NOT LESS THAN FOUR (4) INCHES NOR MORE THAN EIGHT (8) INCHES. MATERIAL SHALL BE CA-11 OR CA-13 AND SHALL BE EXTENDED AT LEAST 12" ABOVE THE TOP OF THE PIPE WHEN USING PVC.
- "BAND SEAL" OR SIMILAR FLEXIBLE-TYPE COUPLINGS SHALL BE USED IN THE CONNECTION OF SEWER PIPES OF DISSIMILAR MATERIALS.
- WHEN CONNECTING TO AN EXISTING SEWER MAIN BY MEANS OTHER THAN AN EXISTING WYE, TEE, OR AN EXISTING MANHOLE, ONE OF THE FOLLOWING METHODS SHALL BE USED:
 - CIRCULAR SAW-CUT OF SEWER MAIN BY PROPER TOOLS ("SEWER-TAP" OR SIMILAR) AND PROPER INSTALLATION OF HUB-WYE SADDLE OR HUB-TEE SADDLE.
 - REMOVE AN ENTIRE SECTION OF PIPE (BREAKING ONLY THE TOP OF ONE BELL) AND REPLACE WITH A WYE OR TEE BRANCH SECTION.
 - WITH PIPE CUTTER, NEATLY AND ACCURATELY CUT OUT DESIRED LENGTH OF PIPE FOR INSERTION OF PROPER FITTING, USING "BAND SEAL" OR SIMILAR COUPLINGS TO HOLD IT FIRMLY IN PLACE.
- WHENEVER A SANITARY/COMBINED SEWER CROSSES UNDER A WATERMAIN, THE MINIMUM VERTICAL DISTANCE FROM THE TOP OF THE SEWER TO THE BOTTOM OF THE WATERMAIN SHALL BE 18 INCHES. FURTHERMORE, A MINIMUM HORIZONTAL DISTANCE OF 10 FEET BETWEEN SANITARY/COMBINED SEWERS AND WATERMANS SHALL BE MAINTAINED UNLESS: THE SEWER IS LAID IN A SEPARATE TRENCH, KEEPING A MINIMUM 18" VERTICAL SEPARATION; OR THE SEWER IS LAID IN THE SAME TRENCH WITH THE WATERMAIN LOCATED AT THE OPPOSITE SIDE ON A BENCH OF UNDISTURBED EARTH, KEEPING A MINIMUM 18" VERTICAL SEPARATION. IF EITHER THE VERTICAL OR HORIZONTAL DISTANCES DESCRIBED ABOVE CAN NOT BE MAINTAINED, OR THE SEWER CROSSES ABOVE THE WATERMAIN, THE SEWER SHALL BE CONSTRUCTED TO WATERMAIN STANDARDS.
- ALL SANITARY MANHOLES, (AND STORM MANHOLES IN COMBINED SEWER AREAS), SHALL HAVE A MINIMUM INSIDE DIAMETER OF 48 INCHES, AND SHALL BE CAST IN PLACE OR PRE-CAST REINFORCED CONCRETE.
- ALL CONNECTIONS TO MANHOLES AND CATCH BASINS SHALL INCORPORATE A RUBBER BOOT CONNECTION CONFORMING TO ASTM C-923.
- MANHOLE, TYPE A AND CATCH BASIN, TYPE A SHALL CONFORM TO THE PROJECT SPECIFIC DETAILS. A "DOGHOUSE MANHOLE" SHALL BE USED FOR MANHOLE, TYPE A 5' DIAMETER FOR THOSE MANHOLES INSTALLED ON EXISTING LIVE SEWERS HAVING A 15" DIAMETER OR GREATER.



FILE NAME =	USER NAME = JDOT	DESIGNED = TM	REVISED =
DIRTE38-sh-t-gennote@1.dgn		DRAWN = BB	REVISED =
	PLOT SCALE = 20.0000' / IN.	CHECKED = JB	REVISED =
	PLOT DATE = 3/23/2012	DATE =	REVISED =

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

GENERAL NOTES AND INDEX OF SHEETS		F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
SCALE: 1" = 20'	SHEET NO. OF SHEETS STA. TO STA.	347	09-00248-00-RS	COOK	274	2
						CONTRACT NO. 63432
ILLINOIS FED. AID PROJECT						